

ALFA25 - ALFA26



Features	Unit	ALFA2000BP	ALFA2500BP	ALFA2510BP	ALFA2524BPT	ALFA2548BPT	ALFA2600BP	ALFA2610BP	ALFA2640BP
Air flow rate (free blow)	m³/h	-	230(260)		230		370(400)		
Flow rate with exit filter	m³/h	-	180(210)		180		250(270)		
Power supply	V/Hz	-	230/50-60	115/50-60	24DC	48DC	230/50-60	115/50-60	400/50-60
Dimensions HxWxD	mm	250x250x30	250x250x119				250x250x110		
Power consumption	W	-	40(38)		26	33	70(90)		60(70)
Current consumption	A	-	0.17(0.16)	0.34(0.32)	1.08	0.68	0.40(0.38)	0.80(0.76)	0.18(0.15)
Overcurrent protection	-	-	thermal		impedance		thermal		
Electric connection	-	-	3-pole terminal 2.5 mm²				4-pole terminal 1.5 mm²		
Duty cycle	-	-	100%						
Operating temperature	°C	-	-10/+70						
Protection degree/class	-	IP54	IP54/Class I						
Noise level	dB(A)	-	53(58)		61		65(68)		
Flow direction	-	-	outside-in						
Bearing	-	-	ball						
Filter mat (Eurovent)	-	EU3							
Service life (at 40°C)	hr	-	50,000						
Material	-	ABS UL94V-0 Color RAL7032							
Wall thickness	mm	1.2-2.4							
Gasket	-	self-adhesive							
Weight (with packaging)	kg	0.42(0.52)	1.60(1.80)		1.20(1.40)		2.50(2.70)		
Package dimensions	mm	280x260x40	270x270x130						
Mounting	-	Fast Clip-on							
Conformity/Approvals	-	CE							

Versions

UL c File n. E301228	ALFA2000BPU	ALFA2500BPU	ALFA2510BPU	ALFA2524BPTU	ALFA2548BPTU	ALFA2600BPU	ALFA2610BPU	-
RAL7035 - Code ending	B							
EMC - Code ending	M							
Reverse flow - Code ending	-	PR						

Accessories

Filter mat, standard type	ALFAFBP20							
Filter mat, high efficiency	ALFAFBP20X							
Thermostat 0-60°C, N. Open	-	THV02						

