

Series 04

Characteristics

The modular 22.5 mm Series 04 is especially suited for:

- Flush design
- Raised design

The modular design caters to a broad range of applications and combinations.

Owing to its robust, user-friendly design, this series is ideally suited for rail vehicles.

Functions

The Series 04 incorporates the following functions:


- Indicator
- Pushbutton
- Illuminated pushbutton
- E-STOP switch
- Stop switch
- Mushroom-head pushbutton
- Key lock switch
- Key insert switch
- Selector switch
- Lever switch

Market segments

The EAO Series 04 is especially suited for applications in the segments:

- Public transportation
- Machinery and Automation
- Construction machines and special-purpose vehicles
- Lifting and moving
- Panel building

Please refer to the EAO website to obtain detailed information regarding this series www.products.eao.com
Configure a product to your exact needs and request a quotation.



Overview**Flush design**

Indicator	4
Flasher	8
Buzzer	12
Pushbutton	13
Illuminated pushbutton	17
Stop switch	21
Mushroom-head pushbutton	22
Keylock switch	23
Selector switch	27
Selector rotary switch	46
Keylock rotary switch	50
Key insert switch	51
Lever switch	54

Raised design

Indicator	55
Flasher	65
Buzzer	73
Pushbutton	74
Illuminated pushbutton	79
Emergency-stop switch	84
Stop switch	85
Mushroom-head pushbutton	86
Keylock switch	89
Selector switch	93
Selector rotary switch	113


Accessories 117**Technical data 161****Marking 171****Application guidelines 177****Index 178**

04 Flush design

Indicator, IP 65




Product can differ from the current configuration.







Dimensions [mm]

- Additional Information**
- Housing plastic black
 - The colour of anodized aluminium parts can vary due to technical production reasons



Mounting cut-outs [mm]

Equipment consisting of (schematic overview)


-  **Lens**
-  **Lens holder**
-  **Actuator**
-  **Press frame**
-  **Bayonet flange**
-  **LED** page 147
-  **Lamp block**

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.

Front ring	Front bezel	Lens	Terminal	Part No.	Wiring diagram	Weight
						
Indicator actuator, Front dimension 35 x 35 mm						
	Plastic black	Plastic red	Screw	704.206.200	1	0.061 kg
		Plastic yellow	Screw	704.206.400	1	0.061 kg
		Plastic green	Screw	704.206.500	1	0.061 kg
		Plastic blue	Screw	704.206.600	1	0.061 kg
		Plastic colourless	Screw	704.206.700	1	0.061 kg
						
Indicator actuator, Front dimension 35 x 35 mm						
	Plastic silver	Plastic red	Screw	704.202.208	1	0.061 kg
		Plastic yellow	Screw	704.202.408	1	0.061 kg
		Plastic green	Screw	704.202.508	1	0.061 kg
		Plastic blue	Screw	704.202.608	1	0.061 kg
		Plastic colourless	Screw	704.202.708	1	0.061 kg

Front ring	Front bezel	Lens	Terminal	Part No.	Wiring diagram	Weight
 Indicator actuator, Front dimension Ø 35 mm						
Aluminium natural anodized		Plastic red	Screw	704.006.218	1	0.061 kg
		Plastic yellow	Screw	704.006.418	1	0.061 kg
		Plastic green	Screw	704.006.518	1	0.061 kg
		Plastic blue	Screw	704.006.618	1	0.061 kg
		Plastic colourless	Screw	704.006.718	1	0.061 kg




04 Flush design

Indicator square, IP 65




Product can differ from the current configuration.



Dimensions [mm]
X = Screw terminal




Additional Information

- Housing plastic black
- Other terminal options from the part lamp block see «Accessories»



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Equipment consisting of (schematic overview)

	Lens	page 123
	Lens holder	page 125
	Actuator	
	Press frame	
	Bayonet flange	page 136
	LED	page 151
	Lamp block	page 137

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.

Front bezel		Part No.	Weight
		Indicator actuator square, flush design, Front dimension 35 x 35 mm	
Plastic black		704.743.0	0.020 kg
Plastic silver		704.743.8	0.020 kg

Indicator round, IP 65

Equipment consisting of (schematic overview)


**Front bezel set** *page 128*

**Lens** *page 123*


**Marking plate** *page 127*

**Actuator**

**Part of front bezel set**


**Bayonet flange** *page 136*

**LED** *page 151*

**Lamp block** *page 137*

Each Part Number listed below includes all the black components shown in the 3D-drawing.


To obtain a complete unit, please select the red components from the pages shown.



Dimensions [mm]
X = Screw terminal



Product can differ from the current configuration.



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Additional Information

- For front dimension Ø 35 mm
- Housing plastic grey
- Lens flat or raised possible; equal choose marking plate or marking cap
- Other terminal options from the part lamp block see «Accessories»

Part No.

Weight



Indicator actuator round

704.633.1


0.020 kg

04 Flush design

Flasher, IP 65




Product can differ from the current configuration.



Dimensions [mm]
X = Screw terminal

Additional Information

- Housing plastic black
- The lamp block will be delivered with screw terminal
- Other terminal options of the part flasher element see «Accessories»
- The colour of anodized aluminium parts can vary due to technical production reasons



Mounting cut-outs [mm]
PIT = Push-in terminal,
X = Screw terminal

Equipment consisting of (schematic overview)


- Lens**
- Marking foil**
- Lens holder**
- Actuator**
- Press frame**
- Bayonet flange**
- LED** page 151
- Lamp block**
- Flasher element** page 135

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.

Front ring	Front bezel	Lens	Part No.	Wiring diagram	Weight
					
Flasher actuator, Front dimension 35 x 35 mm					
	Plastic black	Plastic red	704.206.200	1	0.061 kg
		Plastic yellow	704.206.400	1	0.061 kg
		Plastic green	704.206.500	1	0.061 kg
		Plastic blue	704.206.600	1	0.061 kg
		Plastic colourless	704.206.700	1	0.061 kg
					
Flasher actuator, Front dimension 35 x 35 mm					
	Plastic silver	Plastic red	704.202.208	1	0.061 kg
		Plastic yellow	704.202.408	1	0.061 kg
		Plastic green	704.202.508	1	0.061 kg
		Plastic blue	704.202.608	1	0.061 kg
		Plastic colourless	704.202.708	1	0.061 kg

Front ring	Front bezel	Lens	Part No.	Wiring diagram	Weight
 Flasher actuator, Front dimension Ø 35 mm					
Aluminium natural anodized		Plastic red	704.006.218	1	0.061 kg
		Plastic yellow	704.006.418	1	0.061 kg
		Plastic green	704.006.518	1	0.061 kg
		Plastic blue	704.006.618	1	0.061 kg
		Plastic colourless	704.006.718	1	0.061 kg




04 Flush design

Flasher square, IP 65




Product can differ from the current configuration.



Dimensions [mm]
X = Screw terminal

- Additional Information**
- Housing plastic black
 - Other terminal options from the part flasher element and lamp block see «Accessories»



Mounting cut-outs [mm]
PIT = Push-in terminal,
X = Screw terminal

Equipment consisting of (schematic overview)

	Lens	page 123
	Lens holder	page 125
	Actuator	
	Press frame	
	Bayonet flange	page 136
	LED	page 151
	Lamp block	page 137
	Flasher element	page 135

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.

Front bezel		Part No.	Weight
Flasher actuator square, Front dimension 35 x 35 mm			
Plastic black		704.743.0	0.020 kg
Plastic silver		704.743.8	0.020 kg

Flasher round, IP 65

Equipment consisting of (schematic overview)


**Front bezel set** *page 128*

**Lens** *page 123*


**Marking plate** *page 127*


**Actuator**


**Part of front bezel set**

**Bayonet flange** *page 136*

**LED** *page 151*

**Lamp block** *page 137*


**Flasher element** *page 135*



Dimensions [mm]
X = Screw terminal



Product can differ from the current configuration.



Mounting cut-outs [mm]
PIT = Push-in terminal,
X = Screw terminal

Additional Information

- For front dimension Ø 35 mm
- Housing plastic grey
- Lens flat or raised possible; equal choose marking plate or marking cap
- Other terminal options from the part flasher element and lamp block see «Accessories»

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.

Part No.

Weight



Flasher actuator round

704.633.1


0.020 kg

04 Flush design

Buzzer, IP 40




Product can differ from the current configuration.



Dimensions [mm]


Equipment consisting of (schematic overview)

**Buzzer**

**Pressure ring**

**Fixing nut**


- Additional Information
- Further information see «Technical data»
 - The colour of anodized aluminium parts can vary due to technical production reasons



Mounting cut-outs [mm]





Each Part Number listed below includes all the black components shown in the 3D-drawing.

Operating voltage	Front cap	Terminal	Part No.	Wiring diagram	Weight
Buzzer, Front dimension Ø 35 mm					
24 VDC	Aluminium black anodized	Solder 2.8 x 0.5 mm	14-810.910	1	0.016 kg
	Aluminium natural anodized	Solder 2.8 x 0.5 mm	14-810.918	1	0.016 kg



Pushbutton, IP 65

Equipment consisting of (schematic overview)



Additional Information

- Other terminal options from the part switching element see «Accessories»
- The colour of anodized aluminium parts can vary due to technical production reasons
- Max. 3 switching elements can be clipped on

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.

Housing	Front ring	Front bezel	Lens	Switching action	Part No.	Wiring diagram	Weight
 Pushbutton actuator, Front dimension 35 x 35 mm							
Plastic black		Plastic black	Plastic black	B	704.209.000	1	0.051 kg
			Plastic red	B	704.209.200	1	0.051 kg
			Plastic yellow	B	704.209.400	1	0.051 kg
			Plastic green	B	704.209.500	1	0.051 kg
			Plastic blue	B	704.209.600	1	0.051 kg
			Plastic colourless	B	704.209.700	1	0.051 kg
		Plastic silver	Plastic black	B	704.210.008	1	0.051 kg
			Plastic red	B	704.210.208	1	0.051 kg
			Plastic yellow	B	704.210.408	1	0.051 kg
			Plastic green	B	704.210.508	1	0.051 kg
			Plastic blue	B	704.210.608	1	0.051 kg
			Plastic colourless	B	704.210.708	1	0.051 kg
		Plastic black	Plastic black	C	704.239.000	2	0.051 kg
			Plastic red	C	704.239.200	2	0.051 kg
			Plastic yellow	C	704.239.400	2	0.051 kg
			Plastic green	C	704.239.500	2	0.051 kg
			Plastic blue	C	704.239.600	2	0.051 kg
			Plastic colourless	C	704.239.700	2	0.051 kg

04 Flush design

Housing	Front ring	Front bezel	Lens	Switching action	Part No.	Wiring diagram	Weight
Plastic black		Plastic silver	Plastic black	C	704.240.008	2	0.051 kg
			Plastic red	C	704.240.208	2	0.051 kg
			Plastic yellow	C	704.240.408	2	0.051 kg
			Plastic green	C	704.240.508	2	0.051 kg
			Plastic blue	C	704.240.608	2	0.051 kg
			Plastic colourless	C	704.240.708	2	0.051 kg



Pushbutton actuator, Front dimension Ø 35 mm


Plastic grey	Aluminium natural anodized	Aluminium black anodized	B	704.011.018	1	0.051 kg
		Aluminium red anodized	B	704.011.218	1	0.051 kg
		Aluminium gold anodized	B	704.011.418	1	0.051 kg
		Aluminium olive-green anodized	B	704.011.518	1	0.051 kg
		Aluminium blue anodized	B	704.011.618	1	0.051 kg
		Aluminium natural anodized	B	704.011.818	1	0.051 kg
		Plastic black	B	704.012.018	1	0.051 kg
		Plastic red	B	704.012.218	1	0.051 kg
		Plastic yellow	B	704.012.418	1	0.051 kg
		Plastic green	B	704.012.518	1	0.051 kg
		Plastic blue	B	704.012.618	1	0.051 kg
		Plastic colourless	B	704.012.718	1	0.051 kg
		Plastic black	C	704.042.018	2	0.051 kg
		Plastic red	C	704.042.218	2	0.051 kg
		Plastic yellow	C	704.042.418	2	0.051 kg
		Plastic green	C	704.042.518	2	0.051 kg
		Plastic blue	C	704.042.618	2	0.051 kg
		Plastic colourless	C	704.042.718	2	0.051 kg

Switching action : B = Momentary, C = Maintain

E---	E~--
Wiring diagram 1	Wiring diagram 2


Pushbutton square, IP 65

Equipment consisting of (schematic overview)




Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.



Dimensions [mm]
X = Screw terminal



Mounting cut-outs [mm]
 PIT = Push-in terminal,
 P3 = Plug-in terminal 6.3 x 0.8 mm,
 P4 = Double plug-in terminal 6.3 x 0.8 mm,
 X = Screw terminal



Product can differ from the current configuration.

Additional Information

- Housing plastic black
- Other terminal options from the part switching element see «Accessories»
- Max. 3 switching elements can be clipped on

Front bezel	Switching action	Part No.	Wiring diagram	Weight
 Pushbutton actuator square, Front dimension 35 x 35 mm				
Plastic black	B	704.741.0	1	0.020 kg
Plastic silver	B	704.741.8	1	0.020 kg
Plastic black	C	704.742.0	2	0.020 kg
Plastic silver	C	704.742.8	2	0.020 kg

Switching action : B = Momentary, C = Maintain


	
Wiring diagram 1	Wiring diagram 2

04 Flush design

Pushbutton round, IP 65




Product can differ from the current configuration.





Dimensions [mm]
X = Screw terminal

- Additional Information**
- For front dimension Ø 35 mm
 - Metal lens to be ordered with marking plates
 - Housing plastic grey
 - Other terminal options from the part switching element see «Accessories»
 - Max. 3 switching elements can be clipped on



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Equipment consisting of (schematic overview)


-  **Front bezel set** *page 128*
-  **Lens** *page 124*
-  **Marking plate** *page 127*
-  **Actuator**
-  **Part of front bezel set**
-  **Bayonet flange** *page 136*
-  **Switching element** *page 139*

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.

Switching action	Part No.	Wiring diagram	Weight
			
Pushbutton actuator round			
B	704.631.1	1	0.009 kg
C	704.632.1	2	0.009 kg

Switching action : B = Momentary, C = Maintain



Illuminated pushbutton, IP 65

Equipment consisting of (schematic overview)


**Front bezel set**

**Lens**


**Marking plate**


**Actuator**


**Pressure ring**

**Bayonet flange**

**LED** page 151

**Lamp block**


**Switching element** page 139



Dimensions [mm]
X = Screw terminal



Product can differ from the current configuration.



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Additional Information

- The lamp block will be delivered with screw terminal
- Other terminal options from the part switching element see «Accessories»
- The colour of anodized aluminium parts can vary due to technical production reasons
- Max. 3 switching elements can be clipped on

Each Part Number listed below includes all the black components shown in the 3D-drawing.


To obtain a complete unit, please select the red components from the pages shown.

Housing	Front ring	Front bezel	Lens	Switching action	Part No.	Wiring diagram	Weight
 Illuminated pushbutton actuator, Front dimension 35 x 35 mm							
Plastic black		Plastic black	Plastic red	B	704.229.200	1	0.051 kg
			Plastic yellow	B	704.229.400	1	0.051 kg
			Plastic green	B	704.229.500	1	0.051 kg
			Plastic blue	B	704.229.600	1	0.051 kg
			Plastic colourless	B	704.229.700	1	0.051 kg
		Plastic silver	Plastic red	B	704.230.208	1	0.051 kg
			Plastic yellow	B	704.230.408	1	0.051 kg
			Plastic green	B	704.230.508	1	0.051 kg
			Plastic blue	B	704.230.608	1	0.051 kg
			Plastic colourless	B	704.230.708	1	0.051 kg
		Plastic black	Plastic red	C	704.259.200	2	0.051 kg
			Plastic yellow	C	704.259.400	2	0.051 kg
			Plastic green	C	704.259.500	2	0.051 kg
			Plastic blue	C	704.259.600	2	0.051 kg
			Plastic colourless	C	704.259.700	2	0.051 kg

04 Flush design

Housing	Front ring	Front bezel	Lens	Switching action	Part No.	Wiring diagram	Weight
Plastic black		Plastic silver	Plastic red	C	704.260.208	2	0.051 kg
			Plastic yellow	C	704.260.408	2	0.051 kg
			Plastic green	C	704.260.508	2	0.051 kg
			Plastic blue	C	704.260.608	2	0.051 kg
			Plastic colourless	C	704.260.708	2	0.051 kg
 Illuminated pushbutton actuator, Front dimension Ø 35 mm							
Plastic grey	Aluminium natural anodized		Plastic red	B	704.032.218	1	0.067 kg
			Plastic yellow	B	704.032.418	1	0.067 kg
			Plastic green	B	704.032.518	1	0.067 kg
			Plastic blue	B	704.032.618	1	0.067 kg
			Plastic colourless	B	704.032.718	1	0.067 kg
			Plastic red	C	704.062.218	2	0.067 kg
			Plastic yellow	C	704.062.418	2	0.067 kg
			Plastic green	C	704.062.518	2	0.067 kg
			Plastic blue	C	704.062.618	2	0.067 kg
			Plastic colourless	C	704.062.718	2	0.067 kg

Switching action : B = Momentary, C = Maintain





Illuminated pushbutton square, IP 65


Equipment consisting of (schematic overview)

**Lens**
page 123


**Lens holder**
page 125


**Actuator**


**Press frame**

**Bayonet flange**
page 136

**LED**
page 151

**Lamp block**
page 137


**Switching element**
page 139



Dimensions [mm]
X = Screw terminal



Product can differ from the current configuration.



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Additional Information

- Housing plastic black
- Other terminal options from the parts switching element and lamp block see «Accessories»
- Max. 3 switching elements can be clipped on

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.

Front bezel	Switching action	Part No.	Wiring diagram	Weight
 Illuminated pushbutton actuator square, Front dimension 35 x 35 mm				
Plastic black	B	704.741.0	1	0.020 kg
Plastic silver	B	704.741.8	1	0.020 kg
Plastic black	C	704.742.0	2	0.020 kg
Plastic silver	C	704.742.8	2	0.020 kg

Switching action : B = Momentary, C = Maintain


Wiring diagram 1



Wiring diagram 2

04 Flush design

Illuminated pushbutton round, IP 65




Product can differ from the current configuration.



Dimensions [mm]
X = Screw terminal

Additional Information

- For front dimension Ø 35 mm
- Housing plastic grey
- Choose lens plastic or lens metal with spot round
- Other terminal options from the parts switching element and lamp block see «Accessories»
- Max. 3 switching elements can be clipped on



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Equipment consisting of (schematic overview)

	Front bezel set	page 128
	Lens	page 123
	Marking plate	page 127
	Actuator	
	Part of front bezel set	
	Bayonet flange	page 136
	LED	page 151
	Lamp block	page 137
	Switching element	page 139

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.


Switching action	Part No.	Wiring diagram	Weight
Illuminated pushbutton actuator round			
B	704.631.1	1	0.009 kg
C	704.632.1	2	0.009 kg

Switching action : B = Momentary, C = Maintain

E---	E~--
Wiring diagram 1	Wiring diagram 2


Stop switch, IP 65

Equipment consisting of (schematic overview)



Each Part Number listed below includes all the black components shown in the 3D-drawing.


To obtain a complete unit, please select the red components from the pages shown.



Dimensions [mm]
X = Screw terminal



Product can differ from the current configuration.



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Additional Information

- Other terminal options from the part switching element see «Accessories»
- Twist to unlock clockwise
- Max. 3 switching elements can be clipped on
- The colour of anodized aluminium parts can vary due to technical production reasons

Front ring	Lens	Marking	Switching action	Part No.	Wiring diagram	Weight
 Stop switch actuator, Front dimension Ø 40 mm						
Aluminium natural anodized	Plastic red	Arrows	C	704.075.218	1	0.048 kg
		Stop	C	704.075.318	1	0.048 kg
Aluminium black anodized	Plastic red	Arrows	C	704.074.210	1	0.048 kg
		Stop	C	704.075.310	1	0.048 kg

Switching action : C = Maintain




04 Flush design

Mushroom-head pushbutton, IP 65




Product can differ from the current configuration.



Dimensions [mm]
X = Screw terminal

Equipment consisting of (schematic overview)




Actuator



Pressure ring



Bayonet flange



Switching element


page 139

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.

Additional Information

- Other terminal options from the part switching element see «Accessories»
- Max. 3 switching elements can be clipped on
- The colour of anodized aluminium parts can vary due to technical production reasons



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Front ring	Lens	Switching action	Part No.	Wiring diagram	Weight
 Mushroom-head pushbutton actuator, Front dimension Ø 40 mm					
Aluminium natural anodized	Plastic red	B	704.071.218	1	0.041 kg
	Plastic yellow	B	704.071.418	1	0.041 kg
Aluminium black anodized	Plastic red	B	704.071.210	1	0.041 kg
	Plastic yellow	B	704.071.410	1	0.041 kg
 Mushroom-head pushbutton actuator, Front dimension Ø 60 mm					
Aluminium natural anodized	Aluminium red anodized	B	704.079.2F	1	0.069 kg


Switching action : B = Momentary

E---

Wiring diagram 1


Keylock switch 2 positions, IP 65

Equipment consisting of (schematic overview)




Each Part Number listed below includes all the black components shown in the 3D-drawing.


To obtain a complete unit, please select the red components from the pages shown.



Switching positions (A = Rest, B = Momentary, C = Maintained)



Dimensions [mm]
X = Screw terminal



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal



Product can differ from the current configuration.

Additional Information

- Other terminal options from the part switching element see «Accessories»
- The colour of anodized aluminium parts can vary due to technical production reasons
- The standard lock Ronis 251
- Two keys are supplied with each key lock switch
- Further lock numbers see «Technical data»
- Max. 3 switching elements can be clipped on

Front ring	Front bezel	Switching action	Switching angle	Key remove	Part No.	Wiring diagram	Weight
 Keylock switch actuator 2 positions, Front dimension 35 x 35 mm							
	Plastic black	A - B	B = 42°	A	704.343.000	1	0.099 kg
	Plastic silver	A - B	B = 42°	A	704.343.008	1	0.099 kg
	Plastic black	A - C	C = 90°	C	704.340.000	2	0.099 kg
				A	704.341.000	2	0.099 kg
				A + C	704.342.000	2	0.099 kg
	Plastic silver	A - C	C = 90°	C	704.340.008	2	0.099 kg
				A	704.341.008	2	0.099 kg
				A + C	704.342.008	2	0.099 kg

04 Flush design


Front ring	Front bezel	Switching action	Switching angle	Key remove	Part No.	Wiring diagram	Weight
 Keylock switch actuator 2 positions, Front dimension Ø 35 mm							
Aluminium natural anodized		A - B	B = 42°	A	704.123.018	1	0.099 kg
		A - C	C = 90°	C	704.120.018	2	0.099 kg
				A	704.121.018	2	0.099 kg
				A + C	704.122.018	2	0.099 kg

Switching action : A = Rest, B = Momentary, C = Maintain

	
Wiring diagram 1	Wiring diagram 2


Keylock switch 3 positions, IP 65

Equipment consisting of (schematic overview)




Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.



Dimensions [mm]
X = Screw terminal




Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal



Product can differ from the current configuration.

Additional Information

- Other terminal options from the part switching element see «Accessories»
- The colour of anodized aluminium parts can vary due to technical production reasons
- Locknumbers 251, lock type Ronis
- Two keys are supplied with each key lock switch
- Further lock numbers see «Technical data»
- Max. 3 switching elements can be clipped on






Switching positions (A = Rest, B = Momentary, C = Maintained)

Front ring	Front bezel	Switching action	Switching angle	Key remove	Part No.	Wiring diagram	Weight
 Keylock switch actuator 3 positions, Front dimension 35 x 35 mm							
	Plastic black	B - A - C	B = 42°, C = 42°	A	704.338.000	1	0.099 kg
	Plastic silver	B - A - C	B = 42°, C = 42°	A	704.338.008	1	0.099 kg
	Plastic black	C - A - B	C = 42°, B = 42°	C	704.337.000	2	0.099 kg
				C + A	704.344.000	2	0.099 kg
	Plastic silver	C - A - B	C = 42°, B = 42°	C	704.337.008	2	0.099 kg
				C + A	704.344.008	2	0.099 kg
	Plastic black	B - A - B	B = 42° / 42°	A	704.335.000	3	0.099 kg
	Plastic silver	B - A - B	B = 42° / 42°	A	704.335.008	3	0.099 kg
	Plastic black	C - A - C	C = 42° / 42°	A	704.334.000	4	0.099 kg
				C + C	704.336.000	4	0.099 kg
	Plastic silver	C - A - C	C = 42° / 42°	A	704.334.008	4	0.099 kg
				C + C	704.336.008	4	0.099 kg
	Plastic black	C - A - C	C = 90° / 90°	C + A + C	704.333.000	4	0.099 kg
	Plastic silver	C - A - C	C = 90° / 90°	C + A + C	704.333.008	4	0.099 kg

04 Flush design


Front ring	Front bezel	Switching action	Switching angle	Key remove	Part No.	Wiring diagram	Weight
 Keylock switch actuator 3 positions, Front dimension Ø 35 mm							
Aluminium natural anodized		B - A - C	B = 42°, C = 42°	A	704.118.018	1	0.099 kg
		C - A - B	C = 42°, B = 42°	C	704.117.018	2	0.099 kg
				C + A	704.124.018	2	0.099 kg
		B - A - B	B = 42° / 42°	A	704.115.018	3	0.099 kg
		C - A - C	C = 42° / 42°	A	704.114.018	4	0.099 kg
				C + C	704.116.018	4	0.099 kg
			C = 90° / 90°	C + A + C	704.113.018	4	0.099 kg

Switching action : A = Rest, B = Momentary, C = Maintain


			
Wiring diagram 1	Wiring diagram 2	Wiring diagram 3	Wiring diagram 4

Selector switch actuator illuminable, 2 positions short lever, IP 65


Equipment consisting of (schematic overview)



Actuator




Press frame




Bayonet flange




LED *page 151*



Lamp block *page 138*




Switching element *page 139*



Dimensions [mm]
X = Screw terminal



Product can differ from the current configuration.




Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

- Additional Information**
- Other terminal options from the part switching element see «Accessories»
 - The colour of anodized aluminium parts can vary due to technical production reasons
 - Max. 3 switching elements can be clipped on

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.





Switching positions (A = Rest, B = Momentary, C = Maintained)

Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator illuminable, 2 positions, short lever, Front dimension 35 x 35 mm							
Plastic black		Plastic black	A - B	B = 42°	704.512.000I	1	0.056 kg
		Plastic silver	A - B	B = 42°	704.512.008I	1	0.056 kg
		Plastic black	A - C	C = 90°	704.510.000I	2	0.056 kg
		Plastic silver	A - C	C = 90°	704.510.008I	2	0.056 kg

04 Flush design


Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator illuminable, 2 positions, short lever, Front dimension Ø 35 mm							
Plastic black	Aluminium black anodized		A - B	B = 42°	704.413.010I	1	0.056 kg
	Aluminium natural anodized		A - B	B = 42°	704.413.018I	1	0.056 kg
	Aluminium black anodized		A - C	C = 90°	704.411.010I	2	0.056 kg
	Aluminium natural anodized		A - C	C = 90°	704.411.018I	2	0.056 kg

Switching action : A = Rest, B = Momentary, C = Maintain

	
Wiring diagram 1	Wiring diagram 2


Selector switch actuator 2 positions short lever, IP 65

Equipment consisting of (schematic overview)



Each Part Number listed below includes all the black components shown in the 3D-drawing.


To obtain a complete unit, please select the red components from the pages shown.



Dimensions [mm]
X = Screw terminal




Product can differ from the current configuration.



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Additional Information

- Other terminal options from the part switching element see «Accessories»
- The colour of anodized aluminium parts can vary due to technical production reasons
- Max. 3 switching elements can be clipped on





Switching positions (A = Rest, B = Momentary, C = Maintained)

Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator 2 positions, short lever, Front dimension 35 x 35 mm							
Plastic black		Plastic black	A - B	B = 42°	704.512.000	1	0.056 kg
		Plastic silver	A - B	B = 42°	704.512.008	1	0.056 kg
		Plastic black	A - C	C = 90°	704.510.000	2	0.056 kg
		Plastic silver	A - C	C = 90°	704.510.008	2	0.056 kg

04 Flush design

Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator 2 positions, short lever, Front dimension Ø 35 mm							
Plastic black	Aluminium black anodized		A - B	B = 42°	704.413.010	1	0.056 kg
	Aluminium natural anodized		A - B	B = 42°	704.413.018	1	0.056 kg
	Aluminium black anodized		A - C	C = 90°	704.411.010	2	0.056 kg
	Aluminium natural anodized		A - C	C = 90°	704.411.018	2	0.056 kg

Switching action : A = Rest, B = Momentary, C = Maintain

	
Wiring diagram 1	Wiring diagram 2

Selector switch 2 positions 12 o'clock short lever , IP 65

Equipment consisting of (schematic overview)

The schematic overview shows four components arranged vertically. At the top is the **Actuator**, a black plastic component with a trapezoidal top and a cylindrical base. Below it is the **Press frame**, a black square frame with a central rectangular opening. Next is the **Bayonet flange**, a black circular component with a central hole and a rectangular slot on one side. At the bottom is the **Switching element**, a red plastic component with a complex, multi-faceted shape and several protrusions.

Actuator

Press frame

Bayonet flange

Switching element


page 139




page 139

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.



Dimensions [mm]
X = Screw terminal



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal



Product can differ from the current configuration.

Additional Information


- Other terminal options from the part switching element see «Accessories»
- The colour of anodized aluminium parts can vary due to technical production reasons
- Max. 3 switching elements can be clipped on



Switching positions (A = Rest, B = Momentary, C = Maintained)

Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator 2 positions 12 o'clock, short lever , Front dimension 35 x 35 mm							
Plastic black		Plastic black	A - C	C = 90°	704.510.000.12	1	0.056 kg
		Plastic silver	A - C	C = 90°	704.510.008.12	1	0.056 kg
 Selector switch actuator 2 positions 12 o'clock, short lever , Front dimension Ø 35 mm							
Plastic black	Aluminium black anodized		A - C	C = 90°	704.411.010.12	1	0.056 kg
	Aluminium natural anodized		A - C	C = 90°	704.411.018.12	1	0.056 kg

Switching action : A = Rest, C = Maintain




Wiring diagram 1

04 Flush design

Selector switch illuminable, 2 positions, long lever, IP 65




Product can differ from the current configuration.



Dimensions [mm]
X = Screw terminal


Additional Information

- Other terminal options from the part switching element see «Accessories»
- The colour of anodized aluminium parts can vary due to technical production reasons
- Max. 3 switching elements can be clipped on




Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal


Equipment consisting of (schematic overview)



Actuator




Press frame




Bayonet flange



LED [page 151](#)




Lamp block [page 138](#)



Switching element [page 139](#)

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.





Switching positions (A = Rest, B = Momentary, C = Maintained)

Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator illuminable, 2 positions, long lever, Front dimension 35 x 35 mm							
Plastic black		Plastic black	A - B	B = 42°	704.302.000I	1	0.056 kg
		Plastic silver	A - B	B = 42°	704.302.008I	1	0.056 kg
		Plastic black	A - C	C = 90°	704.300.000I	2	0.056 kg
		Plastic silver	A - C	C = 90°	704.300.008I	2	0.056 kg

Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator illuminable, 2 positions, long lever, Front dimension Ø 35 mm							
Plastic black	Aluminium natural anodized		A - B	B = 42°	704.103.018I	1	0.056 kg
	Aluminium black anodized		A - C	C = 90°	704.101.010I	2	0.056 kg
	Aluminium natural anodized		A - C	C = 90°	704.101.018I	2	0.056 kg

Switching action : A = Rest, B = Momentary, C = Maintain


	
Wiring diagram 1	Wiring diagram 2

04 Flush design

Selector switch 2 positions long lever, IP 65




Product can differ from the current configuration.



Dimensions [mm]
X = Screw terminal


Additional Information

- Other terminal options from the part switching element see «Accessories»
- The colour of anodized aluminium parts can vary due to technical production reasons
- Max. 3 switching elements can be clipped on




Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal


Equipment consisting of (schematic overview)




Actuator



Press frame




Bayonet flange



Switching element [page 139](#)

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.





Switching positions (A = Rest, B = Momentary, C = Maintained)

Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator 2 positions, long lever, Front dimension 35 x 35 mm							
Plastic black		Plastic black	A - B	B = 42°	704.302.000	1	0.056 kg
		Plastic silver	A - B	B = 42°	704.302.008	1	0.056 kg
		Plastic black	A - C	C = 90°	704.300.000	2	0.056 kg
		Plastic silver	A - C	C = 90°	704.300.008	2	0.056 kg

Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator 2 positions, long lever, Front dimension Ø 35 mm							
Plastic black	Aluminium natural anodized		A - B	B = 42°	704.103.018	1	0.056 kg
	Aluminium black anodized		A - C	C = 90°	704.101.010	2	0.056 kg
	Aluminium natural anodized		A - C	C = 90°	704.101.018	2	0.056 kg

Switching action : A = Rest, B = Momentary, C = Maintain


	
Wiring diagram 1	Wiring diagram 2

04 Flush design

Selector switch 2 positions 12 o'clock long lever, IP 65




Product can differ from the current configuration.




Dimensions [mm]
X = Screw terminal


Equipment consisting of (schematic overview)




Actuator



Press frame



Bayonet flange




Switching element [page 139](#)

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.

Additional Information

- Other terminal options from the part switching element see «Accessories»
- The colour of anodized aluminium parts can vary due to technical production reasons
- Max. 3 switching elements can be clipped on



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal




Switching positions (A = Rest, B = Momentary, C = Maintained)

Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator 2 positions 12 o'clock long lever, Front dimension 35 x 35 mm							
Plastic black		Plastic black	A - C	C = 90°	704.300.000.12	1	0.056 kg
		Plastic silver	A - C	C = 90°	704.300.008.12	1	0.056 kg

Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator 2 positions 12 o'clock, long lever, Front dimension Ø 35 mm							
Plastic black	Plastic black		A - C	C = 90°	704.101.010.12	1	0.056 kg
	Aluminium natural anodized		A - C	C = 90°	704.101.018.12	1	0.056 kg

Switching action : A = Rest, C = Maintain




04 Flush design

Selector switch illuminable, 3 positions, short lever, IP 65




Product can differ from the current configuration.




Dimensions [mm]
X = Screw terminal


- Additional Information**
- Other terminal options from the part switching element see «Accessories»
 - The colour of anodized aluminium parts can vary due to technical production reasons
 - Max. 3 switching elements can be clipped on




Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal


Equipment consisting of (schematic overview)


**Actuator**

**Press frame**

**Bayonet flange**


**LED** page 151

**Lamp block** page 138

**Switching element** page 139

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.







Switching positions (A = Rest, B = Momentary, C = Maintained)

Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator illuminable, 3 positions, short lever, Front dimension Ø 35 mm							
Plastic black		Plastic black	B - A - C	B = 42°, C = 42°	704.508.000I	1	0.056 kg
		Plastic silver	B - A - C	B = 42°, C = 42°	704.508.008I	1	0.056 kg
		Plastic black	C - A - B	C = 42°, B = 42°	704.506.000I	2	0.056 kg
		Plastic silver	C - A - B	C = 42°, B = 42°	704.506.008I	2	0.056 kg
		Plastic black	B - A - B	B = 42° / 42°	704.504.000I	3	0.056 kg
		Plastic silver	B - A - B	B = 42° / 42°	704.504.008I	3	0.056 kg
		Plastic black	C - A - C	C = 42° / 42°	704.502.000I	4	0.056 kg
		Plastic silver	C - A - C	C = 42° / 42°	704.502.008I	4	0.056 kg

Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator illuminable, 3 positions, short lever, Front dimension Ø 35 mm							
Plastic black	Aluminium black anodized		B - A - C	B = 42°, C = 42°	704.409.010I	1	0.056 kg
	Aluminium natural anodized		B - A - C	B = 42°, C = 42°	704.409.018I	1	0.056 kg
	Aluminium black anodized		C - A - B	C = 42°, B = 42°	704.407.010I	2	0.056 kg
	Aluminium natural anodized		C - A - B	C = 42°, B = 42°	704.407.018I	2	0.056 kg
	Aluminium black anodized		B - A - B	B = 42° / 42°	704.405.010I	3	0.056 kg
	Aluminium natural anodized		B - A - B	B = 42° / 42°	704.405.018I	3	0.056 kg
	Aluminium black anodized		C - A - C	C = 42° / 42°	704.403.010I	4	0.056 kg
	Aluminium natural anodized		C - A - C	C = 42° / 42°	704.403.018I	4	0.056 kg

Switching action : A = Rest, B = Momentary, C = Maintain


			
Wiring diagram 1	Wiring diagram 2	Wiring diagram 3	Wiring diagram 4

04 Flush design

Selector switch 3 positions short lever, IP 65




Product can differ from the current configuration.




Dimensions [mm]
X = Screw terminal


Equipment consisting of (schematic overview)




Actuator



Press frame



Bayonet flange




Switching element [page 139](#)

Each Part Number listed below includes all the black components shown in the 3D-drawing.


To obtain a complete unit, please select the red components from the pages shown.

Additional Information

- Other terminal options from the part switching element see «Accessories»
- The colour of anodized aluminium parts can vary due to technical production reasons
- Max. 3 switching elements can be clipped on



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal






Switching positions (A = Rest, B = Momentary, C = Maintained)

Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator 3 positions, short lever, Front dimension 35 x 35 mm							
Plastic black		Plastic black	B - A - C	B = 42°, C = 42°	704.508.000	1	0.056 kg
		Plastic silver	B - A - C	B = 42°, C = 42°	704.508.008	1	0.056 kg
		Plastic black	C - A - B	C = 42°, B = 42°	704.506.000	2	0.056 kg
		Plastic silver	C - A - B	C = 42°, B = 42°	704.506.008	2	0.056 kg
		Plastic black	B - A - B	B = 42° / 42°	704.504.000	3	0.056 kg
		Plastic silver	B - A - B	B = 42° / 42°	704.504.008	3	0.056 kg
		Plastic black	C - A - C	C = 42° / 42°	704.502.000	4	0.056 kg
		Plastic silver	C - A - C	C = 42° / 42°	704.502.008	4	0.056 kg

Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator 3 positions, short lever, Front dimension Ø 35 mm							
Plastic black	Aluminium black anodized		B - A - C	B = 42°, C = 42°	704.409.010	1	0.056 kg
	Aluminium natural anodized		B - A - C	B = 42°, C = 42°	704.409.018	1	0.056 kg
	Aluminium black anodized		C - A - B	C = 42°, B = 42°	704.407.010	2	0.056 kg
	Aluminium natural anodized		C - A - B	C = 42°, B = 42°	704.407.018	2	0.056 kg
	Aluminium black anodized		B - A - B	B = 42° / 42°	704.405.010	3	0.056 kg
	Aluminium natural anodized		B - A - B	B = 42° / 42°	704.405.018	3	0.056 kg
	Aluminium black anodized		C - A - C	C = 42° / 42°	704.403.010	4	0.056 kg
	Aluminium natural anodized		C - A - C	C = 42° / 42°	704.403.018	4	0.056 kg

Switching action : A = Rest, B = Momentary, C = Maintain


			
Wiring diagram 1	Wiring diagram 2	Wiring diagram 3	Wiring diagram 4

04 Flush design

Selector switch illuminable, 3 positions, long lever, IP 65




Product can differ from the current configuration.



Dimensions [mm]
X = Screw terminal


Additional Information

- Other terminal options from the part switching element see «Accessories»
- The colour of anodized aluminium parts can vary due to technical production reasons
- Max. 3 switching elements can be clipped on




Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal


Equipment consisting of (schematic overview)



Actuator




Press frame




Bayonet flange



LED [page 151](#)




Lamp block [page 138](#)



Switching element [page 139](#)

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.



Switching positions (A = Rest, B = Momentary, C = Maintained)

Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator illuminable, 3 positions, long lever, Front dimension 35 x 35 mm							
Plastic black		Plastic black	B - A - C	B = 42°, C = 42°	704.298.000I	1	0.056 kg
		Plastic silver	B - A - C	B = 42°, C = 42°	704.298.008I	1	0.056 kg
		Plastic black	C - A - B	C = 42°, B = 42°	704.296.000I	2	0.056 kg
		Plastic silver	C - A - B	C = 42°, B = 42°	704.296.008I	2	0.056 kg
		Plastic black	B - A - B	B = 42° / 42°	704.294.000I	3	0.056 kg
		Plastic silver	B - A - B	B = 42° / 42°	704.294.008I	3	0.056 kg
		Plastic black	C - A - C	C = 42° / 42°	704.292.000I	4	0.056 kg
		Plastic silver	C - A - C	C = 42° / 42°	704.292.008I	4	0.056 kg

Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator illuminable, 3 positions, long lever, Front dimension Ø 35 mm							
Plastic black	Aluminium black anodized		B - A - C	B = 42°, C = 42°	704.099.010I	1	0.056 kg
	Aluminium natural anodized		B - A - C	B = 42°, C = 42°	704.099.018I	1	0.056 kg
	Aluminium black anodized		C - A - B	C = 42°, B = 42°	704.097.010I	2	0.056 kg
	Aluminium natural anodized		C - A - B	C = 42°, B = 42°	704.097.018I	2	0.056 kg
	Aluminium black anodized		B - A - B	B = 42° / 42°	704.095.010I	3	0.056 kg
	Aluminium natural anodized		B - A - B	B = 42° / 42°	704.095.018I	3	0.056 kg
	Aluminium black anodized		C - A - C	C = 42° / 42°	704.093.010I	4	0.056 kg
	Aluminium natural anodized		C - A - C	C = 42° / 42°	704.093.018I	4	0.056 kg

Switching action : A = Rest, B = Momentary, C = Maintain


Wiring diagram 1	Wiring diagram 2	Wiring diagram 3	Wiring diagram 4

04 Flush design

Selector switch 3 positions long lever, IP 65




Product can differ from the current configuration.




Dimensions [mm]
X = Screw terminal


Equipment consisting of (schematic overview)




Actuator



Press frame



Bayonet flange




Switching element [page 139](#)

Each Part Number listed below includes all the black components shown in the 3D-drawing.


To obtain a complete unit, please select the red components from the pages shown.

Additional Information

- Other terminal options from the part switching element see «Accessories»
- The colour of anodized aluminium parts can vary due to technical production reasons
- Max. 3 switching elements can be clipped on



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal





Switching positions (A = Rest, B = Momentary, C = Maintained)

Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator 3 positions, long lever, Front dimension 35 x 35 mm							
Plastic black		Plastic black	B - A - C	B = 42°, C = 42°	704.298.000	1	0.056 kg
		Plastic silver	B - A - C	B = 42°, C = 42°	704.298.008	1	0.056 kg
		Plastic black	C - A - B	C = 42°, B = 42°	704.296.000	2	0.056 kg
		Plastic silver	C - A - B	C = 42°, B = 42°	704.296.008	2	0.056 kg
		Plastic black	B - A - B	B = 42° / 42°	704.294.000	3	0.056 kg
		Plastic silver	B - A - B	B = 42° / 42°	704.294.008	3	0.056 kg
		Plastic black	C - A - C	C = 42° / 42°	704.292.000	4	0.056 kg
		Plastic silver	C - A - C	C = 42° / 42°	704.292.008	4	0.056 kg

Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator 3 positions, long lever, Front dimension Ø 35 mm							
Plastic black	Aluminium black anodized		B - A - C	B = 42°, C = 42°	704.099.010	1	0.056 kg
	Aluminium natural anodized		B - A - C	B = 42°, C = 42°	704.099.018	1	0.056 kg
	Aluminium black anodized		C - A - B	C = 42°, B = 42°	704.097.010	2	0.056 kg
	Aluminium natural anodized		C - A - B	C = 42°, B = 42°	704.097.018	2	0.056 kg
	Aluminium black anodized		B - A - B	B = 42° / 42°	704.095.010	3	0.056 kg
	Aluminium natural anodized		B - A - B	B = 42° / 42°	704.095.018	3	0.056 kg
	Aluminium black anodized		C - A - C	C = 42° / 42°	704.093.010	4	0.056 kg
	Aluminium natural anodized		C - A - C	C = 42° / 42°	704.093.018	4	0.056 kg

Switching action : A = Rest, B = Momentary, C = Maintain


			
Wiring diagram 1	Wiring diagram 2	Wiring diagram 3	Wiring diagram 4

04 Flush design

Selector rotary switch short lever rounded, IP 65




Product can differ from the current configuration.



Dimensions [mm]
L = (Number of stages x 12) + 66.5 mm


Additional Information

- The colour of anodized aluminium parts can vary due to technical production reasons




Mounting cut-outs [mm]


Equipment consisting of (schematic overview)




Actuator



Press frame



Bayonet flange



Switching element

page 142


Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.

Lever	Front ring	Switching positions	Part No.	Weight
 Selector rotary switch actuator, short lever rounded, Front dimension Ø 35 mm				
Plastic black	Aluminium black anodized	Rest = 12 o'clock	704.411.010KNI	0.056 kg
 Selector rotary switch actuator, short lever rounded, Front dimension Ø 35 mm				
Plastic black	Aluminium natural anodized	Rest = 9 o'clock	704.411.118KNI	0.056 kg
		Rest = 12 o'clock	704.411.018KNI	0.056 kg


Selector rotary switch short lever, IP 65

Equipment consisting of (schematic overview)




Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.



Dimensions [mm]
L = (Anzahl Fluchten x 12) + 66.5 mm



Mounting cut-outs [mm]



Product can differ from the current configuration.

Additional Information

- The colour of anodized aluminium parts can vary due to technical production reasons


Lever	Front ring	Front bezel	Switching positions	Part No.	Weight
					
Selector rotary switch actuator, short lever, Front dimension 35 x 35 mm					
Plastic black		Plastic black	Rest = 9 o'clock	704.510.100KN	0.056 kg
		Plastic silver	Rest = 9 o'clock	704.510.108KN	0.056 kg
					
Selector rotary switch actuator, short lever, Front dimension Ø 35 mm					
Plastic black	Aluminium black anodized		Rest = 9 o'clock	704.411.110KN	0.056 kg
	Aluminium natural anodized		Rest = 9 o'clock	704.411.118KN	0.056 kg
	Aluminium black anodized		Rest = 12 o'clock	704.411.010KN	0.056 kg
	Aluminium natural anodized		Rest = 12 o'clock	704.411.018KN	0.056 kg

04 Flush design

Selector rotary switch long lever rounded, IP 65




Product can differ from the current configuration.



Dimensions [mm]
L = (Number of stages x 12) + 66.5 mm


Additional Information

- The colour of anodized aluminium parts can vary due to technical production reasons




Mounting cut-outs [mm]


Equipment consisting of (schematic overview)




Actuator



Press frame



Bayonet flange



Switching element

page 142


Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.

Lever	Front ring	Switching positions	Part No.	Weight
 Rotary selector switch actuator, long lever rounded, Front dimension Ø 35 mm				
Plastic black	Aluminium black anodized	Rest = 9 o'clock	704.101.110KNI	0.056 kg
 Rotary selector switch actuator, long lever rounded, Front dimension Ø 35 mm				
Plastic black	Aluminium natural anodized	Rest = 9 o'clock	704.101.118KNI	0.056 kg
		Rest = 12 o'clock	704.101.018KNI	0.056 kg


Selector rotary switch long lever, IP 65

Equipment consisting of (schematic overview)




Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.



Dimensions [mm]
L = (Anzahl Fluchten x 12) + 66.5 mm



Mounting cut-outs [mm]



Product can differ from the current configuration.

Additional Information

- The colour of anodized aluminium parts can vary due to technical production reasons


Lever	Front ring	Front bezel	Switching positions	Part No.	Weight
					
Rotary selector switch actuator, long lever, Front dimension 35 x 35 mm					
Plastic black		Plastic black	Rest = 9 o'clock	704.300.100KN	0.056 kg
		Plastic silver	Rest = 9 o'clock	704.300.108KN	0.056 kg
					
Rotary selector switch actuator, long lever, Front dimension Ø 35 mm					
Plastic black	Aluminium black anodized		Rest = 9 o'clock	704.101.110KN	0.056 kg
	Aluminium natural anodized		Rest = 9 o'clock	704.101.118KN	0.056 kg
	Aluminium natural anodized		Rest = 12 o'clock	704.101.018KN	0.056 kg

04 Flush design

Keylock rotary switch, IP 65




Product can differ from the current configuration.



Dimensions [mm]
 $L = (\text{Anzahl Fluchten} \times 12) + 66.5 \text{ mm}$


Additional Information

- Locknumbers 251, lock type Ronis
- Two keys are supplied with each key lock switch
- Further lock numbers see «Technical data»
- The colour of anodized aluminium parts can vary due to technical production reasons



Mounting cut-outs [mm]

Equipment consisting of (schematic overview)



Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.




Switching positions (A = Rest, B = Momentary, C = Maintained)

Front ring	Switching action	Switching positions	Switching angle	Key remove	Part No.	Weight
 Keylock rotary switch actuator, Front dimension Ø 35 mm						
Aluminium natural anodized	C - A	Rest = 12 o'clock	C = 90°	12 o'clock	704.123.018KN	0.12 kg
Aluminium natural anodized	C - A	Rest = 9 o'clock	C = 90°	9 o'clock	704.123.118KN	0.12 kg


Key-insert switch 2 positions, IP 67

Equipment consisting of (schematic overview)



Each Part Number listed below includes all the black components shown in the 3D-drawing.


To obtain a complete unit, please select the red components from the pages shown.



Dimensions [mm]
X = Screw terminal



Product can differ from the current configuration.



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Additional Information

- Other terminal options from the part switching element see «Accessories»
- In the Part-No. «x» stands for not defined actuator
- Max. 3 switching element can be clipped on
- The actuator of the key insert switch is being produced according to customer specification. Please contact your local EAO Sales Office

Front ring	Switching action	Switching angle	Part No.	Weight
 Key-insert switch actuator 2 positions, Front dimension Ø 38 mm				
Stainless-steel natural	A - C	C = 90°	704.101.0x28	0.130 kg
	A - B	B = 45°	704.103.0x28	0.130 kg


Switching action : A = Rest, B = Momentary, C = Maintain

04 Flush design

Key-insert switch 3 positions, IP 67




Product can differ from the current configuration.



Dimensions [mm]
X = Screw terminal

Equipment consisting of (schematic overview)




Actuator



Fixing nut



Bayonet flange




Switching element *page 139*

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.

Additional Information

- Other terminal options from the part switching element see «Accessories»
- In the Part-No. «x» stands for not defined actuator
- Max. 3 switching element can be clipped on
- The actuator of the key insert switch is being produced according to customer specification. Please contact your local EAO Sales Office




Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Front ring	Switching action	Switching angle	Part No.	Weight
	Key-insert switch actuator 3 positions, Front dimension Ø 38 mm			
	C - A - C	C = 45° / 45°	704.093.0x28	0.130 kg
	B - A - B	B = 45° / 45°	704.095.0x28	0.130 kg
	C - A - B	C = 45°, B = 45°	704.097.0x28	0.130 kg
	B - A - C	B = 45°, C = 45°	704.099.0x28	0.130 kg

Switching action : A = Rest, B = Momentary, C = Maintain


Key-insert switch 3 positions conductor switch, IP 67

Equipment consisting of (schematic overview)



Each Part Number listed below includes all the black components shown in the 3D-drawing.


To obtain a complete unit, please select the red components from the pages shown.



Dimensions [mm]
X = Screw terminal



Product can differ from the current configuration.



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Additional Information

- Other terminal options from the part switching element see «Accessories»
- Max. 1 switching element can be clipped on
- The actuator of the key insert switch is being produced according to customer specification. Please contact your local EAO Sales Office
- Torque clockwise min. 17 Ncm
- Torque anti-clockwise min. 35 Ncm

Product attribute	Front ring	Switching action	Switching angle	Part No.	Weight
 Key-insert switch actuator 3 positions conductor switch, Front dimension Ø 38 mm					
RIC-key 9x9 mm, EN 14752	Stainless-steel natural	B - A - B	B = 45° / 45°	704.095.0T28	0.190 kg

Switching action: A = Rest, B = Momentary

04 Flush design

Lever switch, IP 54



Product can differ from the current configuration.

Additional Information

- For all units are the levers 02 (yellow), 03, 04, 05, 06 (black) 13, 14, 15 and 16 available (levers 6 + 16 according UIC 612). Special levers on request
- Front bezel can also be delivered in black version
- The colour of anodized aluminium parts can vary due to technical production reasons
- Functions and properties, including lever style and switching positions of the lever switch are being produced according to customer specifications. Please contact your local EAO Sales Office

S41: Cage clamp 1.0 ... 1.5 mm²

S42: JST connector max. 0.2 mm² (counter plug is supplied)

S43: Plug-in terminal 6.3 x 0.8 mm

S44: Cage clamp 1.0 ... 1.5 mm²

S45: Screw terminal or plug-in terminal 6.3 x 0.8 mm

Micro-switch contacts

The micro-switch is available with a silver contact or a gold plated silver contact.

Contact without positive opening operation is used in the lever switches S41, S42 and S43. Each lever switch includes a maximum of five micro-switches.

Contact with positive opening operation is used in the lever switches S44 and S45. Each lever switch includes a maximum of four micro-switches.


Product attribute	Lever	Front ring	Switching system	Contacts	Switching action	Part No.	Weight
 Lever switch, Front dimension Ø 40 mm							
Type S41, 1 contact element	Plastic black	Aluminium natural anodized	Snap-action switching element	1 NC / 1 NO	C / B	704.151.XXX	0.23 kg
Type S42, 1 contact element	Plastic black	Aluminium natural anodized	Snap-action switching element	1 NC / 1 NO	C / B	704.152.XXX	0.23 kg
Type S43, 1 contact element	Plastic black	Aluminium natural anodized	Snap-action switching element	1 NC / 1 NO	C / B	704.153.XXX	0.23 kg
Type S44, 1 contact element positive opened	Plastic black	Aluminium natural anodized	Snap-action switching element	1 NC / 1 NO	C / B	704.154.XXX	0.23 kg
Type S45, 1 contact element positive open	Plastic black	Aluminium natural anodized	Snap-action switching element	1 NC / 1 NO	C / B	704.155.XXX	0.23 kg

Contacts: NC = Normally closed, NO = Normally open

Switching action : B = Momentary, C = Maintain

Indicator full-face illumination compact, IP 65


Equipment consisting of (schematic overview)




page 151

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.



Dimensions [mm]



Mounting cut-outs [mm]




Product can differ from the current configuration.

Additional Information

- Housing plastic grey

Product attribute	Marking cap	Lens cap	Terminal	Part No.	Wiring diagram	Weight
 Indicator full-face illumination compact, Front dimension Ø 29 mm						
Filament lamp 130 V, max. 2.6 W with integrated series resistor 230/130 V	white translucent	Plastic red translucent	Screw	704.022.2	1	0.025 kg
		Plastic yellow translucent	Screw	704.022.4	1	0.025 kg
		Plastic green translucent	Screw	704.022.5	1	0.025 kg
		Plastic blue translucent	Screw	704.022.6	1	0.025 kg
		Plastic colourless translucent	Screw	704.022.7	1	0.025 kg
Filament lamp max. 2.6 W or LED	white translucent	Plastic red translucent	Screw	704.020.2	2	0.020 kg
		Plastic yellow translucent	Screw	704.020.4	2	0.020 kg
		Plastic green translucent	Screw	704.020.5	2	0.020 kg
		Plastic blue translucent	Screw	704.020.6	2	0.020 kg
		Plastic colourless translucent	Screw	704.020.7	2	0.020 kg
	colourless transparent ripped	Plastic red transparent	Screw	704.021.2	2	0.020 kg
		Plastic yellow transparent	Screw	704.021.4	2	0.020 kg
		Plastic green transparent	Screw	704.021.5	2	0.020 kg
		Plastic blue transparent	Screw	704.021.6	2	0.020 kg
		Plastic colourless transparent	Screw	704.021.7	2	0.020 kg




04 Raised design

Indicator full face illumination compact round, IP 65



Product can differ from the current configuration.




Dimensions [mm]

Equipment consisting of (schematic overview)

	Lens cap	page 125
	Marking cap	page 128
	LED	page 151
	Actuator	
	Fixing nut	

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.



Mounting cut-outs [mm]

Product attribute	Part No.	Wiring diagram	Weight
Indicator actuator full face illumination compact			
with series resistor for 220/240 V and incandescent lamp 130 V, 20 mA	704.642.2	1	0.009 kg
without built-in series resistor	704.642.0	1	0.006 kg
with series resistor for 220/240 V and filament lamp 130 V, 20 mA	704.642.1	2	0.020 kg

Wiring diagram 1	Wiring diagram 2

Indicator full face illumination, IP 65

Equipment consisting of (schematic overview)


**Lens cap**

**Marking cap**

**Actuator**


**Bayonet flange**

**LED** *page 151*


**Lamp block**

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.



Dimensions [mm]



Mounting cut-outs [mm]



Product can differ from the current configuration.


Additional Information

- Housing plastic grey

Product attribute	Marking cap	Front bezel	Lens cap	Terminal	Part No.	Wiring diagram	Weight
	Indicator actuator full-face illumination, Front dimension 30 x 30 mm						
	white translucent	Plastic grey	Plastic red	Screw	704.200.2	1	0.050 kg
			Plastic yellow	Screw	704.200.4	1	0.050 kg
			Plastic green	Screw	704.200.5	1	0.050 kg
			Plastic blue	Screw	704.200.6	1	0.050 kg
			Plastic colourless	Screw	704.200.7	1	0.050 kg
		Plastic black	Plastic red	Screw	704.199.2	1	0.050 kg
			Plastic yellow	Screw	704.199.4	1	0.050 kg
			Plastic green	Screw	704.199.5	1	0.050 kg
			Plastic blue	Screw	704.199.6	1	0.050 kg
			Plastic colourless	Screw	704.199.7	1	0.050 kg
Filament lamp or LED							

04 Raised design

Product attribute	Marking cap	Front bezel	Lens cap	Terminal	Part No.	Wiring diagram	Weight
 Indicator actuator full-face illumination, Front dimension Ø 29 mm							
Filament lamp or LED	white translucent		Plastic red	Screw	704.000.2	1	0.050 kg
			Plastic yellow	Screw	704.000.4	1	0.050 kg
			Plastic green	Screw	704.000.5	1	0.050 kg
			Plastic blue	Screw	704.000.6	1	0.050 kg
			Plastic colourless	Screw	704.000.7	1	0.050 kg
	colourless transparent ripped		Plastic red	Screw	704.001.2	1	0.050 kg
			Plastic yellow	Screw	704.001.4	1	0.050 kg
			Plastic green	Screw	704.001.5	1	0.050 kg
			Plastic blue	Screw	704.001.6	1	0.050 kg
			Plastic colourless	Screw	704.001.7	1	0.050 kg





Indicator full face illumination square, IP 65

Equipment consisting of (schematic overview)


**Lens cap***page 126*

**Diffusor cap***page 128*

**Actuator**


**Bayonet flange***page 136*

**LED***page 151*


**Lamp block***page 137*

Each Part Number listed below includes all the black components shown in the 3D-drawing.


To obtain a complete unit, please select the red components from the pages shown.



Dimensions [mm]
X = Screw terminal



Product can differ from the current configuration.



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Additional Information

- For front dimension 30 x 30 mm
- Housing plastic grey
- Other terminal options from the part lamp block see «Accessories»


Part No.		Weight
 Indicator actuator full face illumination square		
704.730.0		0.005 kg
704.730.1		0.005 kg

04 Raised design

Indicator full face illumination round, IP 65




Product can differ from the current configuration.



Dimensions [mm]
X = Screw terminal

Additional Information

- For front dimension Ø 29 mm
- Housing plastic grey
- Other terminal options from the part lamp block see «Accessories»



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Equipment consisting of (schematic overview)

	Lens cap	page 125
	Marking cap	page 128
	Actuator	
	Bayonet flange	page 136
	LED	page 151
	Lamp block	page 137

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.


Part No.		Weight
	Indicator actuator full face illumination round	
704.630.1		0.005 kg

Indicator front illumination, IP 65


Equipment consisting of (schematic overview)



Front bezel



Lens



Lens holder



Actuator




Bayonet flange




LED *page 151*




Lamp block



Dimensions [mm]



Mounting cut-outs [mm]



Product can differ from the current configuration.


Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.

Product attribute	Marking plate	Housing	Front ring	Front bezel	Lens	Terminal	Part No.	Wiring diagram	Weight
 Indicator actuator front illumination, Front dimension 30 x 30 mm									
Filament lamp or LED	white translucent	Plastic black		Plastic grey	Plastic red	Screw	704.202.2	1	0.050 kg
					Plastic yellow	Screw	704.202.4	1	0.050 kg
					Plastic green	Screw	704.202.5	1	0.050 kg
					Plastic blue	Screw	704.202.6	1	0.050 kg
					Plastic colourless	Screw	704.202.7	1	0.050 kg
				Plastic black	Plastic red	Screw	704.206.2	1	0.050 kg
					Plastic yellow	Screw	704.206.4	1	0.050 kg
					Plastic green	Screw	704.206.5	1	0.050 kg
					Plastic blue	Screw	704.206.6	1	0.050 kg
					Plastic colourless	Screw	704.206.7	1	0.050 kg
	colourless transparent	Plastic black		Plastic grey	Plastic red	Screw	704.203.2	1	0.050 kg
					Plastic yellow	Screw	704.203.4	1	0.050 kg
					Plastic green	Screw	704.203.5	1	0.050 kg
					Plastic blue	Screw	704.203.6	1	0.050 kg
					Plastic colourless	Screw	704.203.7	1	0.050 kg
				Plastic black	Plastic red	Screw	704.207.2	1	0.050 kg
					Plastic yellow	Screw	704.207.4	1	0.050 kg
					Plastic green	Screw	704.207.5	1	0.050 kg
					Plastic blue	Screw	704.207.6	1	0.050 kg
					Plastic colourless	Screw	704.207.7	1	0.050 kg

04 Raised design

Product attribute	Marking plate	Housing	Front ring	Front bezel	Lens	Terminal	Part No.	Wiring diagram	Weight
 Indicator actuator front illumination, Front dimension Ø 29 mm									
Filament lamp or LED	white translucent	Plastic grey	Plastic grey		Plastic red	Screw	704.002.2	1	0.050 kg
					Plastic yellow	Screw	704.002.4	1	0.050 kg
					Plastic green	Screw	704.002.5	1	0.050 kg
					Plastic blue	Screw	704.002.6	1	0.050 kg
					Plastic colourless	Screw	704.002.7	1	0.050 kg
			Plastic black		Plastic red	Screw	704.006.2	1	0.050 kg
					Plastic yellow	Screw	704.006.4	1	0.050 kg
					Plastic green	Screw	704.006.5	1	0.050 kg
					Plastic blue	Screw	704.006.6	1	0.050 kg
					Plastic colourless	Screw	704.006.7	1	0.050 kg
	colourless transparent ripped	Plastic grey	Plastic grey		Plastic red	Screw	704.003.2	1	0.050 kg
					Plastic yellow	Screw	704.003.4	1	0.050 kg
					Plastic green	Screw	704.003.5	1	0.050 kg
					Plastic blue	Screw	704.003.6	1	0.050 kg
					Plastic colourless	Screw	704.003.7	1	0.050 kg



Indicator front illumination square, IP 65

Equipment consisting of (schematic overview)




Front bezel *page 129*



Lens *page 123*



Lens holder *page 125*




Actuator



Bayonet flange *page 136*




LED *page 151*




Lamp block *page 137*

Each Part Number listed below includes all the black components shown in the 3D-drawing.


To obtain a complete unit, please select the red components from the pages shown.



Dimensions [mm]
X = Screw terminal



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal



Product can differ from the current configuration.

Additional Information

- For front dimension 30 x 30 mm
- Other terminal options from the part lamp block see «Accessories»

Housing



Indicator actuator front illumination square

Part No.

Weight

Plastic black

704.733.0

0.020 kg

Plastic grey

704.733.1


0.020 kg

04 Raised design

Indicator front illumination round, IP 65




Product can differ from the current configuration.



Dimensions [mm]
X = Screw terminal



Additional Information

- For front dimension Ø 29 mm
- Lens flat or raised possible; equal choose marking plate or marking cap
- Housing plastic grey
- Other terminal options from the part lamp block see «Accessories»



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Equipment consisting of (schematic overview)

	Front ring	page 130
	Lens	page 123
	Marking plate	page 127
	Actuator	
	Bayonet flange	page 136
	LED	page 151
	Lamp block	page 137

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.


Part No.		Weight
		
Indicator actuator front illumination round		
704.633.1		0.020 kg


Flasher full face illumination, IP 65

Equipment consisting of (schematic overview)


**Lens cap**


**Diffusor cap**


**Actuator**

**Bayonet flange**

**LED** *page 151*

**Lamp block**


**Flasher element** *page 135*



Dimensions [mm]
X = Screw terminal



Product can differ from the current configuration.



Mounting cut-outs [mm]
PIT = Push-in terminal,
X = Screw terminal

- Additional Information**
- The lamp block will be delivered with screw terminal
 - Other terminal options of the part flasher element see «Accessories»


Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.

Product attribute	Diffusor cap	Housing	Front bezel	Lens cap	Part No.	Wiring diagram	Weight
 Flasher actuator full face illumination, Front dimension 30 x 30 mm							
Filament lamp or LED	white translucent	Plastic black	Plastic grey	Plastic red	704.200.2	1	0.050 kg
				Plastic yellow	704.200.4	1	0.050 kg
				Plastic green	704.200.5	1	0.050 kg
				Plastic blue	704.200.6	1	0.050 kg
				Plastic colourless	704.200.7	1	0.050 kg
			Plastic black	Plastic red	704.199.2	1	0.050 kg
				Plastic yellow	704.199.4	1	0.050 kg
				Plastic green	704.199.5	1	0.050 kg
				Plastic blue	704.199.6	1	0.050 kg
				Plastic colourless	704.199.7	1	0.050 kg

04 Raised design

Product attribute	Diffusor cap	Housing	Front bezel	Lens cap	Part No.	Wiring diagram	Weight
 Flasher actuator full face illumination, Front dimension Ø 29 mm							
Filament lamp or LED	white translucent	Plastic grey		Plastic red	704.000.2	1	0.050 kg
				Plastic yellow	704.000.4	1	0.050 kg
				Plastic green	704.000.5	1	0.050 kg
				Plastic blue	704.000.6	1	0.050 kg
				Plastic colourless	704.000.7	1	0.050 kg
	colourless transparent ripped	Plastic grey		Plastic red	704.001.2	1	0.050 kg
				Plastic yellow	704.001.4	1	0.050 kg
				Plastic green	704.001.5	1	0.050 kg
				Plastic blue	704.001.6	1	0.050 kg
				Plastic colourless	704.001.7	1	0.050 kg





Flasher full face illumination square, IP 65

Equipment consisting of (schematic overview)


**Lens cap** *page 126*


**Diffusor cap** *page 128*


**Actuator**

**Bayonet flange** *page 136*

**LED** *page 151*

**Lamp block** *page 137*


**Flasher element** *page 135*



Dimensions [mm]
X = Screw terminal



Product can differ from the current configuration.



Mounting cut-outs [mm]
PIT = Push-in terminal,
X = Screw terminal

Additional Information

- For front dimension 30 x 30 mm
- Other terminal options from the part flasher element and lamp block see «Accessories»

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.


Housing		Part No.	Weight
			
Flasher actuator full face illumination square			
Plastic black		704.730.0	0.050 kg
Plastic grey		704.730.1	0.050 kg

04 Raised design

Flasher full face illumination round, IP 65




Product can differ from the current configuration.



Dimensions [mm]
X = Screw terminal

- Additional Information**
- For front dimension Ø 29 mm
 - Housing plastic grey
 - Other terminal options from the part flasher element and lamp block see «Accessories»



Mounting cut-outs [mm]
PIT = Push-in terminal,
X = Screw terminal

Equipment consisting of (schematic overview)		
	Lens cap	page 125
	Marking cap	page 128
	Actuator	
	Bayonet flange	page 136
	LED	page 151
	Lamp block	page 137
	Flasher element	page 135

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.

Part No.		Weight
	Flasher actuator full face illumination round	
704.630.1		0.020 kg

Flasher front illumination, IP 65

Equipment consisting of (schematic overview)

**Front ring**


**Lens**


**Marking plate**


**Actuator**

**Bayonet flange**

**LED** *page 151*

**Lamp block**


**Flasher element** *page 135*



Dimensions [mm]
X = Screw terminal



Product can differ from the current configuration.



Mounting cut-outs [mm]
PIT = Push-in terminal,
X = Screw terminal

Additional Information

- The lamp block will be delivered with screw terminal
- Other terminal options of the part flasher element see «Accessories»

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.

Product attribute	Marking plate	Housing	Front ring	Front bezel	Lens	Part No.	Wiring diagram	Weight
	white translucent	Plastic black		Plastic grey	Plastic red	704.202.2	1	0.050 kg
					Plastic yellow	704.202.4	1	0.050 kg
					Plastic green	704.202.5	1	0.050 kg
					Plastic blue	704.202.6	1	0.050 kg
					Plastic colourless	704.202.7	1	0.050 kg
				Plastic black	Plastic red	704.206.2	1	0.050 kg
					Plastic yellow	704.206.4	1	0.050 kg
					Plastic green	704.206.5	1	0.050 kg
					Plastic blue	704.206.6	1	0.050 kg
					Plastic colourless	704.206.7	1	0.050 kg


04 Raised design

Product attribute	Marking plate	Housing	Front ring	Front bezel	Lens	Part No.	Wiring diagram	Weight
	colourless transparent	Plastic black		Plastic grey	Plastic red	704.203.2	1	0.050 kg
					Plastic yellow	704.203.4	1	0.050 kg
					Plastic green	704.203.5	1	0.050 kg
					Plastic blue	704.203.6	1	0.050 kg
					Plastic colourless	704.203.7	1	0.050 kg
				Plastic black	Plastic red	704.207.2	1	0.050 kg
					Plastic yellow	704.207.4	1	0.050 kg
					Plastic green	704.207.5	1	0.050 kg
					Plastic blue	704.207.6	1	0.050 kg
					Plastic colourless	704.207.7	1	0.050 kg



Flasher actuator front illumination, Front dimension Ø 29 mm





Filament lamp or LED	white translucent	Plastic grey	Plastic grey		Plastic red	704.002.2	1	0.050 kg	
					Plastic yellow	704.002.4	1	0.050 kg	
					Plastic green	704.002.5	1	0.050 kg	
					Plastic blue	704.002.6	1	0.050 kg	
					Plastic colourless	704.002.7	1	0.050 kg	
			Plastic black			Plastic red	704.006.2	1	0.050 kg
						Plastic yellow	704.006.4	1	0.050 kg
						Plastic green	704.006.5	1	0.050 kg
						Plastic blue	704.006.6	1	0.050 kg
						Plastic colourless	704.006.7	1	0.050 kg
	colourless transpa- rent ripped	Plastic grey	Plastic grey			Plastic red	704.003.2	1	0.050 kg
						Plastic yellow	704.003.4	1	0.050 kg
						Plastic green	704.003.5	1	0.050 kg
						Plastic blue	704.003.6	1	0.050 kg
						Plastic colourless	704.003.7	1	0.050 kg




Wiring diagram 1


Flasher front illumination square, IP 65

Equipment consisting of (schematic overview)


- **Front bezel** *page 129*
- **Lens** *page 123*
- **Lens holder** *page 125*
- **Actuator**
- **Bayonet flange** *page 136*
- **LED** *page 151*
- **Lamp block** *page 137*
- **Flasher element** *page 135*



Dimensions [mm]
X = Screw terminal



Mounting cut-outs [mm]
PIT = Push-in terminal,
X = Screw terminal



Product can differ from the current configuration.

Additional Information

- For front dimension 30 x 30 mm
- Other terminal options from the part flasher element and lamp block see «Accessories»

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.


Housing		Part No.	Weight
			
Flasher front illumination square			
Plastic black		704.733.0	0.020 kg
Plastic grey		704.733.1	0.020 kg

04 Raised design

Flasher front illumination round, IP 65




Product can differ from the current configuration.



Dimensions [mm]
X = Screw terminal

Additional Information

- For front dimension Ø 29 mm
- Lens flat or raised possible; equal choose marking plate or marking cap
- Housing plastic grey
- Other terminal options from the part flasher element and lamp block see «Accessories»



Mounting cut-outs [mm]
PIT = Push-in terminal,
X = Screw terminal

Equipment consisting of (schematic overview)

	Front ring	page 130
	Lens	page 123
	Marking plate	page 127
	Actuator	
	Bayonet flange	page 136
	LED	page 151
	Lamp block	page 137
	Flasher element	page 135


Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.


Part No.	Weight
 Flasher actuator front illumination round	
704.633.1	0.020 kg

Buzzer, IP 65

Equipment consisting of (schematic overview)




Each Part Number listed below includes all the black components shown in the 3D-drawing.



Dimensions [mm]



Product can differ from the current configuration.




Mounting cut-outs [mm]

Additional Information


- Further information see «Technical data»

Operating voltage	Front cap	Terminal	Part No.	Wiring diagram	Weight
 Buzzer, Front dimension Ø 29 mm					
24 VDC	Plastic black	Solder 2.8 x 0.5 mm	14-810.002	1	0.016 kg
	Brass nickel-plated	Solder 2.8 x 0.5 mm	14-810.902	1	0.016 kg




04 Raised design

Pushbutton




Product can differ from the current configuration.



Dimensions [mm]
X = Screw terminal


Additional Information

- Other terminal options from the part switching element see «Accessories»
- The colour of anodized aluminium parts can vary due to technical production reasons
- Frontring with protective cover to be mounted with a torque of 40 Ncm onto actuator
- Max. 3 switching elements can be clipped on



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Equipment consisting of (schematic overview)



Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.

Front protection	Front ring	Front bezel	Lens	Switching action	Part No.	Wiring diagram	Weight
 Pushbutton actuator, Front dimension 30 x 30 mm							
IP 65		Plastic grey	Plastic black	B	704.210.0	1	0.040 kg
			Plastic red	B	704.210.2	1	0.040 kg
			Plastic yellow	B	704.210.4	1	0.040 kg
			Plastic green	B	704.210.5	1	0.040 kg
			Plastic blue	B	704.210.6	1	0.040 kg
			Plastic colourless	B	704.210.7	1	0.040 kg
		Plastic black	Plastic black	B	704.209.0	1	0.040 kg
			Plastic red	B	704.209.2	1	0.040 kg
			Plastic yellow	B	704.209.4	1	0.040 kg
			Plastic green	B	704.209.5	1	0.040 kg
			Plastic blue	B	704.209.6	1	0.040 kg
			Plastic colourless	B	704.209.7	1	0.040 kg
		Plastic grey	Plastic black	C	704.240.0	2	0.040 kg
			Plastic red	C	704.240.2	2	0.040 kg
			Plastic yellow	C	704.240.4	2	0.040 kg
			Plastic green	C	704.240.5	2	0.040 kg
			Plastic blue	C	704.240.6	2	0.040 kg
			Plastic colourless	C	704.240.7	2	0.040 kg

Front protection	Front ring	Front bezel	Lens	Switching action	Part No.	Wiring diagram	Weight
IP 65		Plastic black	Plastic black	C	704.239.0	2	0.040 kg
			Plastic red	C	704.239.2	2	0.040 kg
			Plastic yellow	C	704.239.4	2	0.040 kg
			Plastic green	C	704.239.5	2	0.040 kg
			Plastic blue	C	704.239.6	2	0.040 kg
			Plastic colourless	C	704.239.7	2	0.040 kg



Pushbutton actuator, Front dimension Ø 29 mm

IP 65	Plastic grey		Plastic black	B	704.010.0	1	0.040 kg
			Plastic red	B	704.010.2	1	0.040 kg
			Plastic yellow	B	704.010.4	1	0.040 kg
			Plastic green	B	704.010.5	1	0.040 kg
			Plastic blue	B	704.010.6	1	0.040 kg
			Plastic colourless	B	704.010.7	1	0.040 kg
	Plastic black		Plastic black	B	704.009.0	1	0.040 kg
			Plastic red	B	704.009.2	1	0.040 kg
			Plastic yellow	B	704.009.4	1	0.040 kg
			Plastic green	B	704.009.5	1	0.040 kg
			Plastic blue	B	704.009.6	1	0.040 kg
			Plastic colourless	B	704.009.7	1	0.040 kg
	Plastic grey		Plastic black	C	704.040.0	2	0.040 kg
			Plastic red	C	704.040.2	2	0.040 kg
			Plastic yellow	C	704.040.4	2	0.040 kg
			Plastic green	C	704.040.5	2	0.040 kg
			Plastic blue	C	704.040.6	2	0.040 kg
			Plastic colourless	C	704.040.7	2	0.040 kg
	Plastic black		Plastic black	C	704.039.0	2	0.040 kg
			Plastic red	C	704.039.2	2	0.040 kg
			Plastic yellow	C	704.039.4	2	0.040 kg
			Plastic green	C	704.039.5	2	0.040 kg
			Plastic blue	C	704.039.6	2	0.040 kg
			Plastic colourless	C	704.039.7	2	0.040 kg
	Aluminium natural anodized		Aluminium black anodized	B	704.011.0	1	0.040 kg
			Aluminium red anodized	B	704.011.2	1	0.040 kg
			Aluminium gold anodized	B	704.011.4	1	0.040 kg
			Aluminium olive-green anodized	B	704.011.5	1	0.040 kg
			Aluminium blue anodized	B	704.011.6	1	0.040 kg
			Aluminium natural anodized	B	704.011.8	1	0.040 kg
			Plastic black	B	704.012.0	1	0.040 kg
			Plastic red	B	704.012.2	1	0.040 kg
			Plastic yellow	B	704.012.4	1	0.040 kg
			Plastic green	B	704.012.5	1	0.040 kg
			Plastic blue	B	704.012.6	1	0.040 kg
			Plastic colourless	B	704.012.7	1	0.040 kg
			Aluminium black anodized	C	704.041.0	2	0.040 kg
			Aluminium red anodized	C	704.041.2	2	0.040 kg
			Aluminium gold anodized	C	704.041.4	2	0.040 kg
			Aluminium olive-green anodized	C	704.041.5	2	0.040 kg
			Aluminium blue anodized	C	704.041.6	2	0.040 kg
			Aluminium natural anodized	C	704.041.8	2	0.040 kg

04 Raised design


Front protection	Front ring	Front bezel	Lens	Switching action	Part No.	Wiring diagram	Weight
IP 65	Aluminium natural anodized		Kunststoff schwarz	C	704.042.0	2	0.040 kg
			Plastic red	C	704.042.2	2	0.040 kg
			Plastic yellow	C	704.042.4	2	0.040 kg
			Plastic green	C	704.042.5	2	0.040 kg
			Plastic blue	C	704.042.6	2	0.040 kg
			Plastic colourless	C	704.042.7	2	0.040 kg
IP 67	Aluminium natural anodized with protective cap		Plastic black	B	704.013.0	1	0.040 kg
			Plastic red	B	704.013.2	1	0.040 kg
			Plastic yellow	B	704.013.4	1	0.040 kg
			Plastic green	B	704.013.5	1	0.040 kg
			Plastic blue	B	704.013.6	1	0.040 kg
			Plastic colourless	B	704.013.7	1	0.040 kg
			Plastic black	C	704.043.0	2	0.040 kg
			Plastic red	C	704.043.2	2	0.040 kg
			Plastic yellow	C	704.043.4	2	0.040 kg
			Plastic green	C	704.043.5	2	0.040 kg
			Plastic blue	C	704.043.6	2	0.040 kg
			Plastic colourless	C	704.043.7	2	0.040 kg

Switching action : B = Momentary, C = Maintain

E---	E~--
Wiring diagram 1	Wiring diagram 2


Pushbutton square, IP 65

Equipment consisting of (schematic overview)




Each Part Number listed below includes all the black components shown in the 3D-drawing.


To obtain a complete unit, please select the red components from the pages shown.



Dimensions [mm]
X = Screw terminal



Product can differ from the current configuration.




Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Additional Information

- For front dimension 30 x 30 mm
- Other terminal options from the part switching element see «Accessories»
- Max. 3 switching elements can be clipped on


Housing	Switching action	Part No.	Wiring diagram	Weight
				
Pushbutton actuator square				
Plastic black	B	704.731.0	1	0.020 kg
Plastic grey	B	704.731.1	1	0.020 kg
Plastic black	C	704.732.0	2	0.020 kg
Plastic grey	C	704.732.1	2	0.020 kg

Switching action : B = Momentary, C = Maintain




04 Raised design

Pushbutton front illumination round, IP 65




Product can differ from the current configuration.



Dimensions [mm]
X = Screw terminal

- Additional Information**
- For front dimension Ø 29 mm
 - Housing plastic grey
 - Other terminal options from the part switching element see «Accessories»
 - Max. 3 switching elements can be clipped on



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Equipment consisting of (schematic overview)

	Front ring	page 130
	Lens	page 124
	Marking plate	page 127
	Actuator	
	Bayonet flange	page 136
	Switching element	page 139

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.


Switching action	Part No.	Wiring diagram	Weight
Pushbutton actuator round			
B	704.631.1	1	0.009 kg
C	704.632.1	2	0.009 kg

Switching action : B = Momentary, C = Maintain

Wiring diagram 1	Wiring diagram 2

Illuminated pushbutton

Equipment consisting of (schematic overview)




Front bezel




Lens



Lens holder



Actuator




Bayonet flange




LED

page 151




Lamp block




Switching element


page 139



Dimensions [mm]
X = Screw terminal



Product can differ from the current configuration.



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Additional Information

- Other terminal options from the part switching element see «Accessories»
- The lamp block will be delivered with screw terminal
- Frontring with protective cover to be mounted with a torque of 40 Ncm onto actuator
- Max. 3 switching elements can be clipped on
- The colour of anodized aluminium parts can vary due to technical production reasons

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.

Front protection	Housing	Front ring	Front bezel	Lens	Switching action	Part No.	Wiring diagram	Weight
 Illuminated pushbutton actuator, Front dimension 30 x 30 mm								
IP 65	Plastic black		Plastic grey	Plastic red	B	704.230.2	1	0.056 kg
				Plastic yellow	B	704.230.4	1	0.056 kg
				Plastic green	B	704.230.5	1	0.056 kg
				Plastic blue	B	704.230.6	1	0.056 kg
				Plastic colourless	B	704.230.7	1	0.056 kg
			Plastic black	Plastic red	B	704.229.2	1	0.056 kg
				Plastic yellow	B	704.229.4	1	0.056 kg
				Plastic green	B	704.229.5	1	0.056 kg
				Plastic blue	B	704.229.6	1	0.056 kg
				Plastic colourless	B	704.229.7	1	0.056 kg
			Plastic grey	Plastic red	C	704.260.2	2	0.056 kg
				Plastic yellow	C	704.260.4	2	0.056 kg
				Plastic green	C	704.260.5	2	0.056 kg
				Plastic blue	C	704.260.6	2	0.056 kg
				Plastic colourless	C	704.260.7	2	0.056 kg

04 Raised design

Front protection	Housing	Front ring	Front bezel	Lens	Switching action	Part No.	Wiring diagram	Weight
IP 65	Plastic black		Plastic black	Plastic red	C	704.259.2	2	0.056 kg
				Plastic yellow	C	704.259.4	2	0.056 kg
				Plastic green	C	704.259.5	2	0.056 kg
				Plastic blue	C	704.259.6	2	0.056 kg
				Plastic colourless	C	704.259.7	2	0.056 kg




Illuminated pushbutton actuator, Front dimension Ø 29 mm

IP 65	Plastic grey	Plastic grey		Plastic red	B	704.030.2	1	0.056 kg
				Plastic yellow	B	704.030.4	1	0.056 kg
				Plastic green	B	704.030.5	1	0.056 kg
				Plastic blue	B	704.030.6	1	0.056 kg
				Plastic colourless	B	704.030.7	1	0.056 kg
		Plastic black		Plastic red	B	704.029.2	1	0.056 kg
				Plastic yellow	B	704.029.4	1	0.056 kg
				Plastic green	B	704.029.5	1	0.056 kg
				Plastic blue	B	704.029.6	1	0.056 kg
				Plastic colourless	B	704.029.7	1	0.056 kg
		Plastic grey		Plastic red	C	704.060.2	2	0.056 kg
				Plastic yellow	C	704.060.4	2	0.056 kg
				Plastic green	C	704.060.5	2	0.056 kg
				Plastic blue	C	704.060.6	2	0.056 kg
				Plastic colourless	C	704.060.7	2	0.056 kg
		Plastic black		Plastic red	C	704.059.2	2	0.056 kg
				Plastic yellow	C	704.059.4	2	0.056 kg
				Plastic green	C	704.059.5	2	0.056 kg
				Plastic blue	C	704.059.6	2	0.056 kg
				Plastic colourless	C	704.059.7	2	0.056 kg
		Aluminium natural anodized		Plastic red	B	704.032.2	1	0.056 kg
				Plastic yellow	B	704.032.4	1	0.056 kg
				Plastic green	B	704.032.5	1	0.056 kg
				Plastic blue	B	704.032.6	1	0.056 kg
				Plastic colourless	B	704.032.7	1	0.056 kg
		Aluminium natural anodized with protective cap		Plastic red	B	704.033.2	1	0.056 kg
				Plastic yellow	B	704.033.4	1	0.056 kg
				Plastic green	B	704.033.5	1	0.056 kg
				Plastic blue	B	704.033.6	1	0.056 kg
				Plastic colourless	B	704.033.7	1	0.056 kg
		Aluminium natural anodized		Plastic red	C	704.062.2	2	0.056 kg
				Plastic yellow	C	704.062.4	2	0.056 kg
				Plastic green	C	704.062.5	2	0.056 kg
				Plastic blue	C	704.062.6	2	0.056 kg
				Plastic colourless	C	704.062.7	2	0.056 kg


Front protection	Housing	Front ring	Front bezel	Lens	Switching action	Part No.	Wiring diagram	Weight
IP 67	Plastic grey	Aluminium natural anodized with protective cap		Plastic red	C	704.063.2	2	0.056 kg
				Plastic yellow	C	704.063.4	2	0.056 kg
				Plastic green	C	704.063.5	2	0.056 kg
				Plastic blue	C	704.063.6	2	0.056 kg
				Plastic colourless	C	704.063.7	2	0.056 kg

Switching action : B = Momentary, C = Maintain




04 Raised design

Illuminated pushbutton square, IP 65




Product can differ from the current configuration.



Dimensions [mm]
X = Screw terminal

Additional Information

- For front dimension 30 x 30 mm
- Other terminal options from the parts switching element and lamp block see «Accessories»
- Max. 3 switching elements can be clipped on



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Equipment consisting of (schematic overview)

	Front bezel	page 129
	Lens	page 123
	Lens holder	page 125
	Actuator	
	Bayonet flange	page 136
	LED	page 151
	Lamp block	page 137
	Switching element	page 139

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.




Housing	Switching action	Part No.	Wiring diagram	Weight
	Illuminated pushbutton actuator square			
Plastic black	B	704.731.0	1	0.020 kg
Plastic grey	B	704.731.1	1	0.020 kg
	C	704.732.1	2	0.020 kg
Plastic black	C	704.732.0	2	0.020 kg

Switching action : B = Momentary, C = Maintain

Wiring diagram 1	Wiring diagram 2


Illuminated pushbutton round, IP 65

Equipment consisting of (schematic overview)

- **Front ring** *page 130*
- **Lens** *page 123*
- **Marking plate** *page 127*
- **Actuator**
- **Bayonet flange** *page 136*
- **LED** *page 151*
- **Lamp block** *page 137*
- **Switching element** *page 139*

Each Part Number listed below includes all the black components shown in the 3D-drawing.


To obtain a complete unit, please select the red components from the pages shown.



Dimensions [mm]
X = Screw terminal



Product can differ from the current configuration.



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Additional Information

- For front dimension Ø 29 mm
- Lens flat or raised possible; equal choose marking plate or marking cap
- Lens metal with spot possible
- Housing plastic grey
- Other terminal options from the parts switching element and lamp block see «Accessories»
- Max. 3 switching elements can be clipped on

Switching action	Part No.	Wiring diagram	Weight
 Illuminated pushbutton actuator round			
B	704.631.1	1	0.009 kg
C	704.632.1	2	0.009 kg

Switching action : B = Momentary, C = Maintain


	
Wiring diagram 1	Wiring diagram 2

04 Raised design

Emergency-stop switch, foolproof EN IEC 60947-5-5, IP 65




Product can differ from the current configuration.




Dimensions [mm]
X = Screw terminal

- Additional Information**
- Other terminal options from the part switching element see «Accessories»
 - Shaft yellow
 - Lock type Euro-Locks 9500
 - Two keys are supplied with each key lock switch
 - Optional lock numbers on request
 - Max. 3 slow-make elements can be clipped on
 - Application as per DIN EN ISO 13850 and EN 60204-1




Mounting cut-outs [mm]


Equipment consisting of (schematic overview)



Actuator



Bayonet flange




Switching element *page 135*

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.


Product attribute	Lens	Marking	Switching action	Part No.	Wiring diagram	Weight
 Emergency-stop switch actuator, foolproof EN IEC 60947-5-5, Front dimension Ø 37 mm						
Twist to unlock anti-clockwise	Plastic red	Arrows	C	704.064.2	1	0.300 kg
 Emergency-stop switch actuator, foolproof EN IEC 60947-5-5, Front dimension Ø 37 mm						
Key to unlock anti-clockwise	Plastic red	Arrows	C	704.066.2	1	0.300 kg

Switching action : C = Maintain




Stop switch, IP 65


Equipment consisting of (schematic overview)



Actuator



Bayonet flange




Switching element


page 139

Each Part Number listed below includes all the black components shown in the 3D-drawing.


To obtain a complete unit, please select the red components from the pages shown.



Dimensions [mm]
X = Screw terminal



Product can differ from the current configuration.



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Additional Information

- The colour of anodized aluminium parts can vary due to technical production reasons
- Other terminal options from the part switching element see «Accessories»
- The standard lock Ronis 251
- Two keys are supplied with each key lock switch
- Further lock numbers see «Technical data»
- Max. 3 switching elements can be clipped on

Product attribute	Front ring	Lens	Marking	Switching action	Part No.	Wiring diagram	Weight
 Stop switch actuator, Front dimension Ø 40 mm							
Twist to unlock clockwise	Plastic grey	Plastic red	Arrows	C	704.074.2	1	0.047 kg
			Stop	C	704.074.3	1	0.047 kg
	Aluminium natural anodized	Plastic red	Arrows	C	704.075.2	1	0.047 kg
			Stop	C	704.075.3	1	0.047 kg
 Stop switch actuator, Front dimension Ø 40 mm							
Key to unlock clockwise	Plastic grey	Plastic red	without	C	704.076.0	1	0.063 kg
	Aluminium natural anodized	Plastic red	without	C	704.078.0	1	0.063 kg

Switching action : C = Maintain




Wiring diagram 1

04 Raised design

Mushroom-head pushbutton, IP 65




Product can differ from the current configuration.




Dimensions [mm]
X = Screw terminal


Equipment consisting of (schematic overview)



Actuator



Bayonet flange



Switching element


page 139

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.

Additional Information

- Other terminal options from the part switching element see «Accessories»
- The colour of anodized aluminium parts can vary due to technical production reasons
- Max. 3 switching elements can be clipped on



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Front ring	Lens	Switching action	Part No.	Wiring diagram	Weight
 Mushroom-head pushbutton actuator, Front dimension Ø 40 mm					
Plastic grey	Plastic black	B	704.070.0	1	0.044 kg
	Plastic red	B	704.070.2	1	0.044 kg
	Plastic yellow	B	704.070.4	1	0.044 kg
	Plastic green	B	704.070.5	1	0.044 kg
Aluminium natural anodized	Plastic black	B	704.071.0	1	0.044 kg
	Plastic red	B	704.071.2	1	0.044 kg
	Plastic yellow	B	704.071.4	1	0.044 kg
	Plastic green	B	704.071.5	1	0.044 kg
Plastic grey	Plastic black	C	704.072.0	2	0.044 kg
	Plastic red	C	704.072.2	2	0.044 kg
Aluminium natural anodized	Plastic black	C	704.073.0	2	0.044 kg
	Plastic red	C	704.073.2	2	0.044 kg
	Plastic yellow	C	704.073.4	2	0.044 kg
	Plastic green	C	704.073.5	2	0.044 kg

Front ring	Lens	Switching action	Part No.	Wiring diagram	Weight
 Mushroom-head pushbutton actuator, Front dimension Ø 60 mm					
Aluminium natural anodized	Aluminium red anodized	B	704.079.2	1	0.060 kg
		C	704.075.2I	2	0.069 kg

Switching action : B = Momentary, C = Maintain


E---	E~--
Wiring diagram 1	Wiring diagram 2

04 Raised design

Illuminated mushroom head pushbutton, IP 65




Product can differ from the current configuration.



Dimensions [mm]
X = Screw terminal


Additional Information


- The lamp block will be delivered with screw terminal
- Other terminal options from the part switching element see «Accessories»
- Max. 3 switching elements can be clipped on




Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal


Equipment consisting of (schematic overview)

**Actuator**

**Bayonet flange**

**LED** page 151

**Lamp block**


**Switching element** page 139

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.


Front ring	Lens	Switching action	Part No.	Wiring diagram	Weight
 Mushroom-head pushbutton actuator illuminated, Front dimension Ø 40 mm					
Plastic grey	Plastic red	B	704.084.2	1	0.044 kg
	Plastic yellow	B	704.084.4	1	0.044 kg
	Plastic green	B	704.084.5	1	0.044 kg
	Plastic blue	B	704.084.6	1	0.044 kg
	Plastic colourless	B	704.084.7	1	0.044 kg
	Plastic red	C	704.086.2	2	0.044 kg
	Plastic yellow	C	704.086.4	2	0.044 kg
	Plastic green	C	704.086.5	2	0.044 kg

Switching action : B = Momentary, C = Maintain




Keylock switch 2 positions, IP 65

Equipment consisting of (schematic overview)




Each Part Number listed below includes all the black components shown in the 3D-drawing.


To obtain a complete unit, please select the red components from the pages shown.



Dimensions [mm]
X = Screw terminal




Product can differ from the current configuration.



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Additional Information

- Other terminal options from the part switching element see «Accessories»
- The standard lock Ronis 251
- Two keys are supplied with each key lock switch
- Further lock numbers see «Technical data»
- Max. 3 switching elements can be clipped on





Switching positions (A = Rest, B = Momentary, C = Maintained)

Front ring	Front bezel	Switching action	Switching angle	Key remove	Part No.	Wiring diagram	Weight
 Keylock switch actuator 2 positions, Front dimension 30 x 30 mm							
	Plastic grey	A - B	B = 42°	A	704.343.0	1	0.070 kg
		A - C	C = 90°	C	704.340.0	2	0.070 kg
				A	704.341.0	2	0.070 kg
				A + C	704.342.0	2	0.070 kg

04 Raised design


Front ring	Front bezel	Switching action	Switching angle	Key remove	Part No.	Wiring diagram	Weight
Keylock switch actuator 2 positions, Front dimension Ø 29 mm							
Aluminium chrome		A - B	B = 42°	A	704.123.0	1	0.070 kg
		A - C	C = 90°	C	704.120.0	2	0.070 kg
				A	704.121.0	2	0.070 kg
				A + C	704.122.0	2	0.070 kg

Switching action : A = Rest, B = Momentary, C = Maintain

	
Wiring diagram 1	Wiring diagram 2


Keylock switch 3 positions, IP 65

Equipment consisting of (schematic overview)




Each Part Number listed below includes all the black components shown in the 3D-drawing.


To obtain a complete unit, please select the red components from the pages shown.



Dimensions [mm]
X = Screw terminal




Product can differ from the current configuration.



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Additional Information

- Other terminal options from the part switching element see «Accessories»
- The standard lock Ronis 251
- Two keys are supplied with each key lock switch
- Further lock numbers see «Technical data»
- Max. 3 switching elements can be clipped on







Switching positions (A = Rest, B = Momentary, C = Maintained)

Front ring	Front bezel	Switching action	Switching angle	Key remove	Part No.	Wiring diagram	Weight
	Plastic grey	C - A - B	C = 42°, B = 42°	C	704.337.0	2	0.070 kg
				C + A	704.344.0	2	0.070 kg
		B - A - B	B = 42° / 42°	A	704.335.0	3	0.070 kg
		C - A - C	C = 42° / 42°	A	704.334.0	4	0.070 kg
			C = 90° / 90°	C + A + C	704.333.0	4	0.070 kg

04 Raised design


Front ring	Front bezel	Switching action	Switching angle	Key remove	Part No.	Wiring diagram	Weight
 Keylock switch actuator 3 positions, Front dimension Ø 29 mm							
Aluminium chrome		B - A - C	B = 42°, C = 42°	A	704.118.0	1	0.070 kg
		C - A - B	C = 42°, B = 42°	C	704.117.0	2	0.070 kg
				C + A	704.124.0	2	0.070 kg
		B - A - B	B = 42° / 42°	A	704.115.0	3	0.070 kg
		C - A - C	C = 42° / 42°	A	704.114.0	4	0.070 kg
				C + C	704.116.0	4	0.070 kg
			C = 90° / 90°	C + A + C	704.113.0	4	0.070 kg

Switching action : A = Rest, B = Momentary, C = Maintain


			
Wiring diagram 1	Wiring diagram 2	Wiring diagram 3	Wiring diagram 4

Selector switch actuator illuminable, 2 positions short lever, IP 65

Equipment consisting of (schematic overview)




Actuator




Bayonet flange



LED *page 151*




Lamp block *page 138*



Switching element *page 139*

Each Part Number listed below includes all the black components shown in the 3D-drawing.


To obtain a complete unit, please select the red components from the pages shown.



Dimensions [mm]
X = Screw terminal




Product can differ from the current configuration.



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Additional Information

- Other terminal options from the part switching element see «Accessories»
- The colour of anodized aluminium parts can vary due to technical production reasons
- Max. 3 switching elements can be clipped on



Switching positions (A = Rest, B = Momentary, C = Maintained)



Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
							
Selector switch actuator illuminable, 2 positions, short lever, Front dimension 30 x 30 mm							
Plastic black		Plastic grey	A - B	B = 42°	704.512.0I	1	0.034 kg
			A - C	C = 90°	704.510.0I	2	0.034 kg

04

Raised design


Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator illuminable, 2 positions, short lever, Front dimension Ø 29 mm							
Plastic black	Plastic grey		A - C	C = 90°	704.410.01	2	0.034 kg
	Aluminium natural anodized		A - C	C = 90°	704.411.01	2	0.037 kg
	Plastic grey		A - B	B = 42°	704.412.01	1	0.034 kg
	Aluminium natural anodized		A - B	B = 42°	704.413.01	1	0.037 kg

Switching action : A = Rest, B = Momentary, C = Maintain


	
Wiring diagram 1	Wiring diagram 2

Selector switch actuator 2 positions short lever, IP 65


Equipment consisting of (schematic overview)



Actuator




Bayonet flange



Switching element *page 139*

Each Part Number listed below includes all the black components shown in the 3D-drawing.


To obtain a complete unit, please select the red components from the pages shown.



Dimensions [mm]
X = Screw terminal




Product can differ from the current configuration.



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Additional Information

- Other terminal options from the part switching element see «Accessories»
- The colour of anodized aluminium parts can vary due to technical production reasons
- Max. 3 switching elements can be clipped on





Switching positions (A = Rest, B = Momentary, C = Maintained)

Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator 2 positions, short lever, Front dimension 30 x 30 mm							
Plastic black		Plastic grey	A - B	B = 42°	704.512.0	1	0.034 kg
			A - C	C = 90°	704.510.0	2	0.034 kg

04 Raised design


Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator 2 positions, short lever, Front dimension Ø 29 mm							
Plastic black	Plastic grey		A - C	C = 90°	704.410.0	2	0.034 kg
	Aluminium natural anodized		A - C	C = 90°	704.411.0	2	0.037 kg
	Plastic grey		A - B	B = 42°	704.412.0	1	0.034 kg
	Aluminium natural anodized		A - B	B = 42°	704.413.0	1	0.037 kg

Switching action : A = Rest, B = Momentary, C = Maintain


	
Wiring diagram 1	Wiring diagram 2

Selector switch 2 positions 12 o'clock short lever , IP 65


Equipment consisting of (schematic overview)



Actuator




Bayonet flange



Switching element *page 139*

Each Part Number listed below includes all the black components shown in the 3D-drawing.


To obtain a complete unit, please select the red components from the pages shown.



Dimensions [mm]
X = Screw terminal



Product can differ from the current configuration.



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Additional Information

- Other terminal options from the part switching element see «Accessories»
- The colour of anodized aluminium parts can vary due to technical production reasons
- Max. 3 switching elements can be clipped on




Switching positions (A = Rest, B = Momentary, C = Maintained)

Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
							
Selector switch actuator 2 positions 12 o'clock, short lever , Front dimension 30 x 30 mm							
Plastic black		Plastic grey	A - C	C = 90°	704.510.0.12	1	0.034 kg

04 Raised design


Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator 2 positions 12 o'clock, short lever , Front dimension Ø 29 mm							
Plastic black	Plastic grey		A - C	C = 90°	704.410.0.12	1	0.034 kg
	Aluminium natural anodized		A - C	C = 90°	704.411.0.12	1	0.037 kg
			A - C	C = 90°	704.411.0B.12	1	0.037 kg

Switching action : A = Rest, C = Maintain



Selector switch illuminable, 2 positions, long lever, IP 65

Equipment consisting of (schematic overview)




Actuator




Bayonet flange



LED *page 151*




Lamp block *page 138*




Switching element *page 139*

Each Part Number listed below includes all the black components shown in the 3D-drawing.


To obtain a complete unit, please select the red components from the pages shown.



Switching positions (A = Rest, B = Momentary, C = Maintained)



Dimensions [mm]
X = Screw terminal



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal



Product can differ from the current configuration.

Additional Information

- Other terminal options from the part switching element see «Accessories»
- The colour of anodized aluminium parts can vary due to technical production reasons
- Max. 3 switching elements can be clipped on

Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator illuminable, 2 positions, long lever, Front dimension 30 x 30 mm							
Plastic black		Plastic grey	A - B	B = 42°	704.302.0I	1	0.034 kg
			A - C	C = 90°	704.300.0I	2	0.034 kg

04

Raised design


Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator illuminable, 2 positions, long lever, Front dimension Ø 29 mm							
Plastic black	Plastic grey		A - C	C = 90°	704.100.01	2	0.034 kg
	Aluminium natural anodized		A - C	C = 90°	704.101.01	2	0.037 kg
	Plastic grey		A - B	B = 42°	704.102.01	1	0.034 kg
	Aluminium natural anodized		A - B	B = 42°	704.103.01	1	0.037 kg

Switching action : A = Rest, B = Momentary, C = Maintain

	
Wiring diagram 1	Wiring diagram 2


Selector switch 2 positions long lever, IP 65

Equipment consisting of (schematic overview)



Each Part Number listed below includes all the black components shown in the 3D-drawing.


To obtain a complete unit, please select the red components from the pages shown.



Dimensions [mm]
X = Screw terminal




Product can differ from the current configuration.



Mounting cut-outs
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Additional Information

- Other terminal options from the part switching element see «Accessories»
- The colour of anodized aluminium parts can vary due to technical production reasons
- Max. 3 switching elements can be clipped on





Switching positions (A = Rest, B = Momentary, C = Maintained)

Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator 2 positions, long lever, Front dimension 30 x 30 mm							
Plastic black		Plastic grey	A - B	B = 42°	704.302.0	1	0.034 kg
			A - C	C = 90°	704.300.0	2	0.034 kg

04 Raised design


Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator 2 positions, long lever, Front dimension Ø 29 mm							
Plastic black	Plastic grey		A - C	C = 90°	704.100.0	2	0.034 kg
	Aluminium natural anodized		A - C	C = 90°	704.101.0	2	0.037 kg
	Plastic grey		A - B	B = 42°	704.102.0	1	0.034 kg
	Aluminium natural anodized		A - B	B = 42°	704.103.0	1	0.037 kg

Switching action: A = Rest, B = Momentary, C = Maintained


	
Wiring diagram 1	Wiring diagram 2

Selector switch 2 positions 12 o'clock long lever, IP 65


Equipment consisting of (schematic overview)



Actuator




Bayonet flange



Switching element *page 139*

Each Part Number listed below includes all the black components shown in the 3D-drawing.


To obtain a complete unit, please select the red components from the pages shown.



Dimensions [mm]
X = Screw terminal



Product can differ from the current configuration.



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Additional Information

- Other terminal options from the part switching element see «Accessories»
- The colour of anodized aluminium parts can vary due to technical production reasons
- Max. 3 switching elements can be clipped on




Switching positions (A = Rest, B = Momentary, C = Maintained)

Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
Selector switch actuator 2 positions 12 o'clock, long lever, Front dimension 30 x 30 mm							
Plastic black		Plastic grey	A - C	C = 90°	704.300.0.12	1	0.034 kg

04 Raised design


Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator 2 positions 12 o'clock, long lever, Front dimension Ø 29 mm							
Plastic black	Plastic grey		A - C	C = 90°	704.100.0.12	1	0.034 kg
	Aluminium natural anodized		A - C	C = 90°	704.101.0.12	1	0.037 kg
	Aluminium black anodized		A - C	C = 90°	704.101.0D.12	1	0.037 kg

Switching action : A = Rest, C = Maintain




Selector switch illuminable, 3 positions, short lever, IP 65

Equipment consisting of (schematic overview)




Actuator




Bayonet flange



LED *page 151*




Lamp block *page 138*



Switching element *page 139*

Each Part Number listed below includes all the black components shown in the 3D-drawing.


To obtain a complete unit, please select the red components from the pages shown.



Dimensions [mm]
X = Screw terminal




Product can differ from the current configuration.



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Additional Information

- Other terminal options from the part switching element see «Accessories»
- The colour of anodized aluminium parts can vary due to technical production reasons
- Max. 3 switching elements can be clipped on



Switching positions (A = Rest, B = Momentary, C = Maintained)

Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
							
Selector switch actuator illuminable, 3 positions, short lever, Front dimension 30 x 30 mm							
Plastic black		Plastic grey	C - A - C	C = 42° / 42°	704.502.0I	4	0.034 kg
			B - A - B	B = 42° / 42°	704.504.0I	3	0.034 kg
			C - A - B	C = 42°, B = 42°	704.506.0I	2	0.034 kg
			B - A - C	B = 42°, C = 42°	704.508.0I	1	0.034 kg

04 Raised design


Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator illuminable, 3 positions, short lever, Front dimension Ø 29 mm							
Plastic black	Plastic grey		C - A - C	C = 42° / 42°	704.402.01	4	0.034 kg
	Aluminium natural anodized		C - A - C	C = 42° / 42°	704.403.01	4	0.037 kg
	Plastic grey		B - A - B	B = 42° / 42°	704.404.01	3	0.034 kg
	Aluminium natural anodized		B - A - B	B = 42° / 42°	704.405.01	3	0.037 kg
	Plastic grey		C - A - B	C = 42°, B = 42°	704.406.01	2	0.034 kg
	Aluminium natural anodized		C - A - B	C = 42°, B = 42°	704.407.01	2	0.037 kg
	Plastic grey		B - A - C	B = 42°, C = 42°	704.408.01	1	0.034 kg
	Aluminium natural anodized		B - A - C	B = 42°, C = 42°	704.409.01	1	0.037 kg

Switching action : A = Rest, B = Momentary, C = Maintain


Wiring diagram 1	Wiring diagram 2	Wiring diagram 3	Wiring diagram 4

Selector switch 3 positions short lever, IP 65


Equipment consisting of (schematic overview)



Actuator



Bayonet flange




Switching element

page 139

Each Part Number listed below includes all the black components shown in the 3D-drawing.


To obtain a complete unit, please select the red components from the pages shown.



Dimensions [mm]
X = Screw terminal




Product can differ from the current configuration.



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Additional Information

- Other terminal options from the part switching element see «Accessories»
- The colour of anodized aluminium parts can vary due to technical production reasons
- Max. 3 switching elements can be clipped on



Switching positions (A = Rest, B = Momentary, C = Maintained)

Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator 3 positions, short lever, Front dimension 30 x 30 mm							
Plastic black		Plastic grey	C - A - C	C = 42° / 42°	704.502.0	4	0.034 kg
			B - A - B	B = 42° / 42°	704.504.0	3	0.034 kg
			C - A - B	C = 42°, B = 42°	704.506.0	2	0.034 kg
			B - A - C	B = 42°, C = 42°	704.508.0	1	0.034 kg

04 Raised design


Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator 3 positions, short lever, Front dimension Ø 29 mm							
Plastic black	Plastic grey		C - A - C	C = 42° / 42°	704.402.0	4	0.034 kg
	Aluminium natural anodized		C - A - C	C = 42° / 42°	704.403.0	4	0.037 kg
	Plastic grey		B - A - B	B = 42° / 42°	704.404.0	3	0.034 kg
	Aluminium natural anodized		B - A - B	B = 42° / 42°	704.405.0	3	0.037 kg
	Plastic grey		C - A - B	C = 42°, B = 42°	704.406.0	2	0.034 kg
	Aluminium natural anodized		C - A - B	C = 42°, B = 42°	704.407.0	2	0.037 kg
	Plastic grey		B - A - C	B = 42°, C = 42°	704.408.0	1	0.034 kg
	Aluminium natural anodized		B - A - C	B = 42°, C = 42°	704.409.0	1	0.037 kg

Switching action : A = Rest, B = Momentary, C = Maintain

			
Wiring diagram 1	Wiring diagram 2	Wiring diagram 3	Wiring diagram 4

Selector switch illuminable, 3 positions, long lever, IP 65

Equipment consisting of (schematic overview)



Actuator




Bayonet flange




LED

page 151



Lamp block

page 138




Switching element

page 139

Each Part Number listed below includes all the black components shown in the 3D-drawing.


To obtain a complete unit, please select the red components from the pages shown.



Dimensions [mm]
X = Screw terminal




Product can differ from the current configuration.



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Additional Information

- Other terminal options from the part switching element see «Accessories»
- The colour of anodized aluminium parts can vary due to technical production reasons
- Max. 3 switching elements can be clipped on



Switching positions (A = Rest, B = Momentary, C = Maintained)

Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
							
Selector switch actuator illuminable, 3 positions, long lever, Front dimension 30 x 30 mm							
Plastic black		Plastic grey	C - A - C	C = 42° / 42°	704.292.0I	4	0.034 kg
			B - A - B	B = 42° / 42°	704.294.0I	3	0.034 kg
			C - A - B	C = 42°, B = 42°	704.296.0I	2	0.034 kg
			B - A - C	B = 42°, C = 42°	704.298.0I	1	0.034 kg

04 Raised design


Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator illuminable, 3 positions, long lever, Front dimension Ø 29 mm							
Plastic black	Plastic grey		C - A - C	C = 42° / 42°	704.092.01	4	0.034 kg
	Aluminium natural anodized		C - A - C	C = 42° / 42°	704.093.01	4	0.037 kg
	Plastic grey		B - A - B	B = 42° / 42°	704.094.01	3	0.034 kg
	Aluminium natural anodized		B - A - B	B = 42° / 42°	704.095.01	3	0.037 kg
	Plastic grey		C - A - B	C = 42°, B = 42°	704.096.01	2	0.034 kg
	Aluminium natural anodized		C - A - B	C = 42°, B = 42°	704.097.01	2	0.037 kg
	Plastic grey		B - A - C	B = 42°, C = 42°	704.098.01	1	0.034 kg
	Aluminium natural anodized		B - A - C	B = 42°, C = 42°	704.099.01	1	0.034 kg

Switching action : A = Rest, B = Momentary, C = Maintain

Wiring diagram 1	Wiring diagram 2	Wiring diagram 3	Wiring diagram 4

Selector switch 3 positions long lever, IP 65


Equipment consisting of (schematic overview)



Actuator



Bayonet flange




Switching element

page 139

Each Part Number listed below includes all the black components shown in the 3D-drawing.


To obtain a complete unit, please select the red components from the pages shown.



Dimensions [mm]
X = Screw terminal




Product can differ from the current configuration.



Mounting cut-outs [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Additional Information

- Other terminal options from the part switching element see «Accessories»
- The colour of anodized aluminium parts can vary due to technical production reasons
- Max. 3 switching elements can be clipped on



Switching positions (A = Rest, B = Momentary, C = Maintained)

Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator 3 positions, long lever, Front dimension 30 x 30 mm							
Plastic black		Plastic grey	C - A - C	C = 42° / 42°	704.292.0	4	0.034 kg
			B - A - B	B = 42° / 42°	704.294.0	3	0.034 kg
			C - A - B	C = 42°, B = 42°	704.296.0	2	0.034 kg
			B - A - C	B = 42°, C = 42°	704.298.0	1	0.034 kg

04 Raised design


Lever	Front ring	Front bezel	Switching action	Switching angle	Part No.	Wiring diagram	Weight
 Selector switch actuator 3 positions, long lever, Front dimension Ø 29 mm							
Plastic black	Plastic grey		C - A - C	C = 42° / 42°	704.092.0	4	0.034 kg
	Aluminium natural anodized		C - A - C	C = 42° / 42°	704.093.0	4	0.037 kg
	Plastic grey		B - A - B	B = 42° / 42°	704.094.0	3	0.034 kg
	Aluminium natural anodized		B - A - B	B = 42° / 42°	704.095.0	3	0.037 kg
	Plastic grey		C - A - B	C = 42°, B = 42°	704.096.0	2	0.034 kg
	Aluminium natural anodized		C - A - B	C = 42°, B = 42°	704.097.0	2	0.037 kg
	Plastic grey		B - A - C	B = 42°, C = 42°	704.098.0	1	0.034 kg
	Aluminium natural anodized		B - A - C	B = 42°, C = 42°	704.099.0	1	0.037 kg

Switching action : A = Rest, B = Momentary, C = Maintain

Wiring diagram 1	Wiring diagram 2	Wiring diagram 3	Wiring diagram 4

Selector rotary switch short lever rounded, IP 65


Equipment consisting of (schematic overview)



Actuator




Bayonet flange



Switching element

page 142



Dimensions [mm]
 $L = (\text{Number of stages} \times 12) + 54.5 \text{ mm}$




Product can differ from the current configuration.

Additional Information

- The colour of anodized aluminium parts can vary due to technical production reasons

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.




Mounting cut-outs [mm]

Lever	Front ring	Front bezel	Switching positions	Part No.	Weight
Selector rotary switch actuator, short lever rounded, Front dimension 30 x 30 mm					
Plastic black		Plastic grey	Rest = 9 o'clock	704.510.1KNI	0.045 kg
Selector rotary switch actuator, short lever rounded, Front dimension Ø 29 mm					
Plastic black	Aluminium natural anodized		Rest = 9 o'clock	704.411.1KNI	0.045 kg

Selector rotary switch short lever, IP 65




Product can differ from the current configuration.



Dimensions [mm]
 $L = (\text{Anzahl Fluchten} \times 12) + 54.5 \text{ mm}$


Additional Information

- The colour of anodized aluminium parts can vary due to technical production reasons




Mounting cut-outs [mm]


Equipment consisting of (schematic overview)



Actuator



Bayonet flange



Switching element

page 141


Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.

Lever	Front ring	Front bezel	Switching positions	Part No.	Weight
Selector rotary switch actuator, short lever, Front dimension 30 x 30 mm					
Plastic black		Plastic grey	Rest = 9 o'clock	704.510.1KN	0.045 kg
Selector rotary switch actuator, short lever, Front dimension Ø 29 mm					
Plastic black	Aluminium natural anodized		Rest = 9 o'clock	704.411.1KN	0.045 kg

Selector rotary switch long lever rounded, IP 65


Equipment consisting of (schematic overview)



Actuator




Bayonet flange



Switching element *page 142*

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.




Dimensions [mm]
 $L = (\text{Number of stages} \times 12) + 54.5 \text{ mm}$



Product can differ from the current configuration.

Additional Information

- The colour of anodized aluminium parts can vary due to technical production reasons



Mounting cut-outs [mm]


Lever	Front ring	Front bezel	Switching positions	Part No.	Weight
 Rotary selector switch actuator, long lever rounded, Front dimension 30 x 30 mm					
Plastic black		Plastic grey	Rest = 9 o'clock	704.300.1KNI	0.045 kg
 Rotary selector switch actuator, long lever rounded, Front dimension Ø 29 mm					
Plastic black	Aluminium natural anodized		Rest = 9 o'clock	704.101.1KNI	0.045 kg

04 Raised design

Selector rotary switch long lever, IP 65




Product can differ from the current configuration.



Dimensions [mm]
L = (Anzahl Fluchten x 12) + 54.5 mm


Additional Information

- The colour of anodized aluminium parts can vary due to technical production reasons




Mounting cut-outs [mm]

Equipment consisting of (schematic overview)

**Actuator**

**Bayonet flange**

**Switching element** *page 146*


Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.

Lever	Front ring	Front bezel	Switching positions	Part No.	Weight
 Rotary selector switch actuator, long lever, Front dimension 30 x 30 mm					
Plastic black		Plastic grey	Rest = 9 o'clock	704.300.1KN	0.045 kg
 Rotary selector switch actuator, long lever, Front dimension Ø 29 mm					
Plastic black	Aluminium natural anodized		Rest = 9 o'clock	704.101.1KN	0.045 kg
			Rest = 12 o'clock	704.101.0KN	0.045 kg

Front**Legend frame****Additional Information**

- The colour of anodized aluminium parts can vary due to technical production reasons



Dimensions [mm]

Product attribute	Dimension	Material	Colour	Mounting type	Part No.	Weight
 Legend frame						
for raised design	30 x 50 x 0.75 mm	Aluminium	black anodized	adhesive	704.968.2	0.001 kg
for flush design	35 x 57.5 x 0.75 mm	Aluminium	black anodized	adhesive	704.968.3	0.001 kg

Legend plate**Additional Information**

- The colour of anodized aluminium parts can vary due to technical production reasons

Dimension	Material	Colour	Mounting type	Part No.	Weight
 Legend plate for legend frame					
14.5 x 23.5 mm	Aluminium	natural anodized	adhesive	704.968.0	0.001 kg
		black anodized	adhesive	704.968.1	0.001 kg

04 Accessories

Legend plate flush design

Additional Information

- For devices square with flush design
- The colour of anodized aluminium parts can vary due to technical production reasons

Dimension	Material	Colour	Mounting type	Part No.	Weight
 Legend plate for flush design					
18 x 35 mm	Aluminium	natural anodized	adhesive	704.968.4	0.001 kg
		black anodized	adhesive	704.968.5	0.001 kg

Legend plate rotary switch

Additional Information

- The colour of anodized aluminium parts can vary due to technical production reasons

Product attribute	Dimension	Material	Colour	Mounting type	Part No.	Weight
 Legend plate for rotary selector switch						
for raised design Ø 29 mm	48 x 48 mm	Aluminium	black anodized	adhesive	704.968.10	0.003 kg
for flush design Ø 35 mm	48 x 48 mm	Aluminium	black anodized	adhesive	704.968.11	0.003 kg
 Legend plate for rotary selector switch						
for raised design Ø 29 mm	48 x 60 mm	Aluminium	black anodized	adhesive	704.968.12	0.004 kg
for flush design Ø 35 mm	48 x 60 mm	Aluminium	black anodized	adhesive	704.968.13	0.004 kg

Lens plastic square

- Druckhauben sind für quadratische Geräte in erhabener und flacher Bauform verwendbar

Product attribute	Dimension	Lens	Part No.	Weight
 Lens plastic square				
non-illuminative	24.4 x 24.4 mm	black opaque	704.702.0	0.001 kg
illuminative	24.4 x 24.4 mm	red transparent	704.702.2	0.001 kg
		yellow transparent	704.702.4	0.001 kg
		green transparent	704.702.5	0.001 kg
		blue transparent	704.702.6	0.001 kg
		colourless transparent	704.702.7	0.001 kg
non-illuminative	24.4 x 24.4 mm	white opaque	704.702.9	0.001 kg

Lens plastic round flat

- Lenses are usable for square devices in raised design and flush design

Product attribute	Dimension	Lens	Symbol	Part No.	Weight
 Lens plastic round flat					
non-illuminative	Ø 23.7 mm	black opaque		704.602.0	0.001 kg
illuminative	Ø 23.7 mm	red transparent		704.602.2	0.001 kg
		yellow transparent		704.602.4	0.001 kg
		green transparent		704.602.5	0.001 kg
		blue transparent		704.602.6	0.001 kg
		colourless transparent		704.602.7	0.001 kg
 Lens plastic round flat					
illuminative	Ø 23.7 mm	colourless transparent	Ring	704.602.7A01	0.001 kg

04 Accessories

Lens plastic round encreased

Product attribute	Dimension	Lens	Part No.	Weight
 Lens plastic round encreased				
illuminative	Ø 23.7 mm	red transparent	704.611.2	0.002 kg
		yellow transparent	704.611.4	0.002 kg
		green transparent	704.611.5	0.002 kg
		colourless transparent	704.611.7	0.002 kg

Lens metal round

- The colour of anodized aluminium parts can vary due to technical production reasons

Product attribute	Dimension	Lens	Part No.	Weight
 Lens metal round				
non-illuminative	Ø 23.7 mm	Aluminium black anodized	704.601.0	0.001 kg
		Aluminium red anodized	704.601.2	0.001 kg
		Aluminium gold anodized	704.601.4	0.001 kg
		Aluminium olive-green anodized	704.601.5	0.001 kg
		Aluminium blue anodized	704.601.6	0.001 kg
		Aluminium natural anodized	704.601.8	0.001 kg
		Stainless-steel natural 304	704.601.9	0.001 kg
		Stainless-steel natural 316	704.601.10	0.001 kg

Lens metal spot round

- The colour of anodized aluminium parts can vary due to technical production reasons

Product attribute	Dimension	Lens	Part No.	Weight
 Lens metal with spot round				
illuminative	Ø 23.7 mm	Aluminium black anodized	704.601.01	0.001 kg
		Aluminium red anodized	704.601.21	0.001 kg
		Aluminium gold anodized	704.601.41	0.001 kg
		Aluminium olive-green anodized	704.601.51	0.001 kg
		Aluminium blue anodized	704.601.61	0.001 kg
		Aluminium natural anodized	704.601.81	0.001 kg
		Stainless-steel natural 304	704.601.91	0.001 kg
		Stainless-steel natural 316	704.601.101	0.001 kg

Lens holder square

Product attribute	Marking plate illumination	Marking plate	Part No.	Weight
 Lens holder for lens square				
	LED	colourless transparent	704.709.7	0.003 kg
can be marked	LED	white translucent	704.709.9	0.003 kg

Lens cap round

Lens cap	Part No.	Weight
 Lens cap round round, 29 mm		
Plastic red	704.603.2	0.003 kg
Plastic yellow	704.603.4	0.003 kg
Plastic green	704.603.5	0.003 kg
Plastic blue	704.603.6	0.003 kg
Plastic colourless	704.603.7	0.003 kg

04 Accessories

Lens cap square

Lens cap	Part No.	Weight
 Lens cap square square, 30 x 30 mm		
Plastic red	704.703.2	0.003 kg
Plastic yellow	704.703.4	0.003 kg
Plastic green	704.703.5	0.003 kg
Plastic blue	704.703.6	0.003 kg
Plastic colourless	704.703.7	0.003 kg

Marking foil square

Product attribute	Material	Colour	Optics	Part No.	Weight
 Marking foil for lens square, front illumination					
can be hot stamped	Plastic	colourless	transparent	704.707.7	0.001 kg
 Marking foil for lens square, full face illumination					
can be hot stamped	Plastic	colourless	transparent	704.706.7	0.001 kg

Marking plate round flat

Marking plate illumination	Marking plate	Part No.	Weight
 Marking plate for lens round flat			
non-illuminative	black opaque	704.609.0	0.001 kg
 Marking plate for lens round flat			
LED	colourless transparent ripped	704.609.7	0.001 kg
 Marking plate for lens round flat			
LED and filament lamp	white translucent	704.609.9	0.001 kg
 Marking plate for lens round flat			
Halo illumination	white translucent	704.609.9A01	0.001 kg

Marking cap round encreased

Marking cap illumination	Marking cap	Part No.	Weight
 Marking cap for lens round encreased			
LED	colourless transparent ripped	704.610.7	0.001 kg
 Marking cap for lens round encreased			
LED and filament lamp	white translucent	704.610.9	0.001 kg

04 Accessories

Marking cap lens cap round

Marking cap illumination	Marking cap	Part No.	Weight
 Marking cap for lens cap round			
LED	colourless transparent ripped	704.608.7	0.002 kg
 Marking cap for lens cap round			
LED and filament lamp	white translucent	704.608.9	0.002 kg

Diffusor cap lens cap round

Product attribute	Diffusor cap	Part No.	Weight
 Diffusor cap for lens cap square			
	colourless transparent	704.708.7	0.004 kg
can be marked	white translucent	704.708.9	0.004 kg

Front bezel set flush design

- The colour of anodized aluminium parts can vary due to technical production reasons

Mounting cut-out	Front ring	Part No.	Weight
 Front bezel set for indicator and pushbutton, flush design round, 35 mm			
Ø 30.5 mm	Aluminium black anodized	704.955.0	0.015 kg
	Aluminium natural anodized	704.955.1	0.015 kg
	Stainless-steel natural 304	704.955.9	0.033 kg
	Stainless-steel natural 316	704.955.10	0.033 kg

Front bezel square

Front be- zel		Part No.	Weight
			
	Front bezel square square, 30 x 30 mm		
	Plastic black	704.701.0	0.002 kg
	Plastic chrome	704.701.4	0.002 kg
	Plastic grey	704.701.6	0.002 kg

Front bezel set protective mem. , IP 67

Additional Information

- The colour of anodized aluminium parts can vary due to technical production reasons
- For pushbutton and illuminated pushbutton for IP 67 front protection
- Front ring to be mounted with a torque of 40 Ncm onto actuator

Product attribute	Dimension	Front ring	Part No.	Weight
				
Front bezel set with protective membrane, flush design				
with transparent silicone membrane	Ø 35 mm	Aluminium natural anodized	704.955.3	0.015 kg
		Aluminium black anodized	704.955.4	0.015 kg
with transparent silicone membrane, resistant to sea water	Ø 35 mm	Stainless-steel natural	704.955.9E	0.033 kg

04 Accessories

Front ring

- The colour of anodized aluminium parts can vary due to technical production reasons

Product attribute	Front ring	Part No.	Weight
	Front ring round, 29 mm		
	Plastic black	704.600.0	0.003 kg
	Plastic grey	704.600.6	0.003 kg
	Aluminium natural anodized	704.600.1	0.005 kg
	Aluminium black anodized	704.600.1A	0.005 kg
	Stainless-steel natural	704.600.9	0.006 kg
	Front ring round, 29 mm		
	16 mm high	Plastic grey	704.600.7

Front protective cap, IP 68

Additional Information

- For indicator, pushbutton and illuminated push-button for protection IP 68

Product attribute	Material	Colour	Optics	Part No.	Weight
 Front protective cap					
only together with lenses Part No. 704.602.X, 704.601.X and front rings Part No. 704.600.X	Silicone	colourless	transparent	704.953.0	0.002 kg

Front protective ring, IP 67

Additional Information


- For pushbutton and illuminated pushbutton with front illumination (IP 67)
- Front protective ring to be mounted with a torque of 40 Ncm onto actuator
- The colour of anodized aluminium parts can vary due to technical production reasons

Product attribute	Material	Colour	Part No.	Weight
 Front protective ring				
	Brass	chrome	704.600.2	0.005 kg
	Aluminium	natural anodized	704.600.3	0.005 kg
	Aluminium	natural anodized	704.600.5/A	0.005 kg
with transparent silicone membrane (extent resistant to sea water), temperature resistance -40 °C ... +85 °C				
with transparent Pebax membrane, temperature resistance -40 °C ... +85 °C				

Protective cover sq. flush des., IP 67

Additional Information

- Hinged
- Front panel thickness reduces by 2 mm
- Please note that bigger minimum distances are necessary



Dimensions [mm]


Product attribute	Dimension	Material	Optics	Part No.	Weight
 Protective cover square, flush design					
with means for sealing, for pushbutton with mounting cut-out 30 x 30 mm	38.5 x 45 mm	Plastic	transparent	704.925.8	0.007 kg
 Protective cover square, flush design					
with means for sealing, for selector switch with mounting cut-out 30 x 30 mm	38.5 x 45 mm	Plastic	transparent	704.925.9	0.007 kg

04 Accessories

Protective cover rd. flush des., IP 65

Additional Information

- Hinged
- Front panel thickness reduces by 2 mm
- The dimensions of the mounting cut-outs are shown in the product details
- Please note that bigger minimum distances are necessary
- The colour of anodized aluminium parts can vary due to technical production reasons




Dimensions [mm]

Product attribute	Dimension	Material	Colour	Optics	Part No.	Weight
 Protective cover round, flush design						
with means for sealing, for pushbutton with mounting cut-out Ø 30.5 mm	37 x 44.5 mm	Plastic	colourless	transparent	704.925.7	0.006 kg
 Protective cover round, flush design						
not with means for sealing, with spring fitted, with window, for pushbutton with mounting cut-out Ø 30.5 mm	38 x 50 mm	Aluminium	natural anodized		704.928.18	0.019 kg
 Protective cover round, flush design						
with means for sealing, for pushbutton and selector switch with mounting cut-out Ø 30.5 mm, short lever	38 x 50 mm	Aluminium	natural anodized		704.928.28	0.019 kg
 Protective cover round, flush design						
with means for sealing, for pushbutton and selector switch with mounting cut-out Ø 30.5 mm, short lever	38 x 50 mm	Aluminium	natural anodized		704.928.38	0.019 kg

Protective cover raised design, IP 65**Additional Information**

- Hinged, with means for sealing
- Protective cover Part-No. only for selector switch in basic position A applicable
- Front panel thickness reduces by 3 mm
- The dimensions of the mounting cut-outs are shown in the product details
- Please note that bigger minimum distances are necessary



Dimensions [mm]

Product attribute	Dimension	Material	Optics	Part No.	Weight
 Protection cover round, raised design					
for pushbutton with mounting cut-out Ø 22.5 mm	30 x 37 mm	Plastic	transparent	704.925.0	0.007 kg
with spring fitted, for pushbutton with mounting cut-out Ø 22.5 mm	30 x 37 mm	Plastic	transparent	704.925.3	0.007 kg
 Protection cover round, raised design					
for selector switch	Ø 22.5 mm	Plastic	transparent	704.925.2	0.007 kg

Spare key**Additional Information**

- The standard lock Ronis 251
- Optional lock numbers on request


Product attribute	Part No.	Weight
 Spare key		
for keylock number 251, keylock type Ronis	704.989.251	0.006 kg

04 Accessories

Blind plug, IP 65

Additional Information

- The dimensions of the mounting cut-outs are shown in the product details
- Please note that bigger minimum distances are necessary



Dimensions [mm]


Dimension	Mounting cut-out	Material	Colour	Part No.	Weight
 Blind plug					
Ø 28 mm	Ø 22.5 mm	Plastic	black	704.960.4	0.004 kg
 Blind plug					
30 x 30 mm	Ø 22.5 mm	Plastic	black	704.964.7	0.009 kg
 Blind plug					
Ø 36 mm	Ø 30.5 mm	Plastic	black	704.964.8	0.007 kg
 Blind plug					
35 x 35 mm	30 x 30 mm	Plastic	black	704.964.9	0.009 kg

Rear side

Flasher element


Additional Information

- Further information see «Technical data»




Dimensions [mm]
PIT = Push-in terminal,
X = Screw terminal

Product attribute	Operating voltage	Terminal	Part No.	Wiring diagram	Weight
					
Lamp voltage/-current 130 V, 20 mA	230 VAC ±6 %	Push-in Terminal	704.943.0P	1	0.021 kg
		Screw	704.943.0	1	0.024 kg
Lamp voltage/- current 60 V, 33 mA	115 VAC ±10 %	Push-in Terminal	704.943.1P	1	0.021 kg
		Screw	704.943.1	1	0.024 kg
Lamp voltage/-current 130 V, 3 mA	130 VDC ±10 %	Push-in Terminal	704.943.2P	1	0.021 kg
		Screw	704.943.2	1	0.024 kg
Lamp voltage/-current 24 V, 10 ... 85 mA	24 VDC ±15 %	Push-in Terminal	704.943.5P	1	0.021 kg
		Screw	704.943.5	1	0.024 kg




Bayonet flange



Dimensions [mm]


Material	Part No.	Weight
 Bayonet flange		
Plastic	704.950.5	0.015 kg
 Bayonet flange		
Metal	704.960.5	0.025 kg

Lamp block for selector switch 2 positions




Dimensions [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal

Product attribute	Terminal	Part No.	Wiring diagram	Weight
	Screw	704.950.0	1	0.012 kg
	Plug 6.3 x 0.8 mm	704.950.1	1	0.012 kg
Terminals nickel plated and blank Cu/Sn	Double plug 6.3 x 0.8 mm	704.950.1/D	1	0.013 kg
	Push-in Terminal	704.950.3	1	0.014 kg
Terminals nickel plated Cu/Sn	Double plug 6.3 x 0.8 mm	704.950.2/D	1	0.013 kg
for ring cable shoe	Screw	704.950.0B	1	0.013 kg




04 Accessories

Lamp block for selector switch 2 and 3 positions



Dimensions [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal


Product attribute	Terminal	Part No.	Wiring diagram	Weight
	Screw	704.951.0	1	0.012 kg
	Plug 6.3 x 0.8 mm	704.951.1	1	0.012 kg
	Double plug 6.3 x 0.8 mm	704.951.1/D	1	0.013 kg
	Push-in Terminal	704.951.3	1	0.014 kg
	Terminals nickel plated and blank Cu/Sn			



Switching element

Additional Information

- For the third switching element the terminal marking insert is to be ordered separately



Dimensions [mm]
PIT = Push-in terminal,
P3 = Plug-in terminal 6.3 x 0.8 mm,
P4 = Double plug-in terminal 6.3 x 0.8 mm,
X = Screw terminal


Switching voltage	Switching current	Switching system	Contacts	Contact material	Terminal	Part No.	Wiring diagram	Weight
 Switching element								
500 VAC	6 A	Snap-action switching element	1 NO	Gold	Push-in Terminal	704.907.1	3	0.020 kg
			1 NC	Gold	Push-in Terminal	704.907.2	1	0.020 kg
			2 NO	Gold	Push-in Terminal	704.907.3	5	0.027 kg
			2 NC	Gold	Push-in Terminal	704.907.4	4	0.027 kg
			1 NC + 1 NO	Gold	Push-in Terminal	704.907.5	2	0.027 kg
			1 NO	Silver	Push-in Terminal	704.908.1	3	0.020 kg
			1 NC	Silver	Push-in Terminal	704.908.2	1	0.020 kg
			2 NO	Silver	Push-in Terminal	704.908.3	5	0.027 kg
			2 NC	Silver	Push-in Terminal	704.908.4	4	0.027 kg
			1 NC + 1 NO	Silver	Push-in Terminal	704.908.5	2	0.027 kg
 Switching element								
500 VAC	6 A	Slow-make switching element	1 NO	Gold	Push-in Terminal	704.917.1	3	0.019 kg
			1 NC	Gold	Push-in Terminal	704.917.2	1	0.019 kg
			2 NO	Gold	Push-in Terminal	704.917.3	5	0.026 kg
			2 NC	Gold	Push-in Terminal	704.917.4	4	0.019 kg
			1 NC + 1 NO	Gold	Push-in Terminal	704.917.5	2	0.026 kg
			1 NO	Silver	Push-in Terminal	704.918.1	3	0.019 kg
			1 NC	Silver	Push-in Terminal	704.918.2	1	0.019 kg
			2 NO	Silver	Push-in Terminal	704.918.3	5	0.026 kg
			2 NC	Silver	Push-in Terminal	704.918.4	4	0.019 kg
			1 NC + 1 NO	Silver	Push-in Terminal	704.918.5	2	0.026 kg

04 Accessories


Switching voltage	Switching current	Switching system	Contacts	Contact material	Terminal	Part No.	Wiring diagram	Weight
 Switching element								
500 VAC	6 A	Snap-action switching element	1 NO	Silver	Plug 6.3 x 0.8 mm	704.905.1	3	0.021 kg
			1 NC	Silver	Plug 6.3 x 0.8 mm	704.905.2	1	0.021 kg
			2 NO	Silver	Plug 6.3 x 0.8 mm	704.905.3	5	0.028 kg
			2 NC	Silver	Plug 6.3 x 0.8 mm	704.905.4	4	0.028 kg
			1 NC + 1 NO	Silver	Plug 6.3 x 0.8 mm	704.905.5	2	0.028 kg
 Switching element								
500 VAC	6 A	Slow-make switching element	1 NO	Silver	Plug 6.3 x 0.8 mm	704.915.1	3	0.021 kg
			1 NC	Silver	Plug 6.3 x 0.8 mm	704.915.2	1	0.021 kg
			2 NO	Silver	Plug 6.3 x 0.8 mm	704.915.3	5	0.028 kg
			2 NC	Silver	Plug 6.3 x 0.8 mm	704.915.4	4	0.028 kg
			1 NC + 1 NO	Silver	Plug 6.3 x 0.8 mm	704.915.5	2	0.028 kg
 Switching element								
500 VAC	6 A	Snap-action switching element	1 NO	Gold	Double plug 6.3 x 0.8 mm	704.901.1/D	3	0.026 kg
			1 NC	Gold	Double plug 6.3 x 0.8 mm	704.901.2/D	1	0.026 kg
			2 NO	Gold	Double plug 6.3 x 0.8 mm	704.901.3/D	5	0.033 kg
			2 NC	Gold	Double plug 6.3 x 0.8 mm	704.901.4/D	4	0.033 kg
			1 NC + 1 NO	Gold	Double plug 6.3 x 0.8 mm	704.901.5/D	2	0.033 kg
			1 NO	Silver	Double plug 6.3 x 0.8 mm	704.905.1/D	3	0.026 kg
			1 NC	Silver	Double plug 6.3 x 0.8 mm	704.905.2/D	1	0.026 kg
			2 NO	Silver	Double plug 6.3 x 0.8 mm	704.905.3/D	5	0.033 kg
			2 NC	Silver	Double plug 6.3 x 0.8 mm	704.905.4/D	4	0.033 kg
			1 NC + 1 NO	Silver	Double plug 6.3 x 0.8 mm	704.905.5/D	2	0.033 kg
 Switching element								
500 VAC	6 A	Slow-make switching element	1 NO	Silver	Double plug 6.3 x 0.8 mm	704.915.1/D	3	0.025 kg
			1 NC	Silver	Double plug 6.3 x 0.8 mm	704.915.2/D	1	0.025 kg
			2 NO	Silver	Double plug 6.3 x 0.8 mm	704.915.3/D	5	0.032 kg
			2 NC	Silver	Double plug 6.3 x 0.8 mm	704.915.4/D	4	0.032 kg
			1 NC + 1 NO	Silver	Double plug 6.3 x 0.8 mm	704.915.5/D	2	0.032 kg

Switching voltage	Switching current	Switching system	Contacts	Contact material	Terminal	Part No.	Wiring diagram	Weight
 Switching element								
500 VAC	10 A	Snap-action switching element	1 NO	Gold	Screw	704.901.1	3	0.021 kg
			1 NC	Gold	Screw	704.901.2	1	0.021 kg
			2 NO	Gold	Screw	704.901.3	5	0.028 kg
			2 NC	Gold	Screw	704.901.4	4	0.028 kg
			1 NC + 1 NO	Gold	Screw	704.901.5	2	0.028 kg
			1 NO	Silver	Screw	704.900.1	3	0.021 kg
			1 NC	Silver	Screw	704.900.2	1	0.021 kg
			2 NO	Silver	Screw	704.900.3	5	0.028 kg
			2 NC	Silver	Screw	704.900.4	4	0.028 kg
			1 NC + 1 NO	Silver	Screw	704.900.5	2	0.028 kg
			1 NO	Palladium	Screw	704.902.1	3	0.021 kg
			1 NC	Palladium	Screw	704.902.2	1	0.021 kg
			2 NO	Palladium	Screw	704.902.3	5	0.028 kg
			2 NC	Palladium	Screw	704.902.4	4	0.028 kg
			1 NC + 1 NO	Palladium	Screw	704.902.5	2	0.028 kg
 Switching element								
500 VAC	10 A	Slow-make switching element	1 NO	Gold	Screw	704.911.1	3	0.021 kg
			1 NC	Gold	Screw	704.911.2	1	0.021 kg
			2 NO	Gold	Screw	704.911.3	5	0.028 kg
			2 NC	Gold	Screw	704.911.4	4	0.028 kg
			1 NC + 1 NO	Gold	Screw	704.911.5	2	0.028 kg
			1 NO	Silver	Screw	704.910.1	3	0.021 kg
			1 NC	Silver	Screw	704.910.2	1	0.021 kg
			2 NO	Silver	Screw	704.910.3	5	0.028 kg
			2 NC	Silver	Screw	704.910.4	4	0.028 kg
			1 NC + 1 NO	Silver	Screw	704.910.5	2	0.028 kg
			1 NO	Palladium	Screw	704.912.1	3	0.021 kg
			1 NC	Palladium	Screw	704.912.2	1	0.021 kg
			2 NO	Palladium	Screw	704.912.3	5	0.028 kg
			2 NC	Palladium	Screw	704.912.4	4	0.028 kg
			1 NC + 1 NO	Palladium	Screw	704.912.5	2	0.028 kg

Contacts: NC = Normally closed, NO = Normally open




Switching element ring cable shoe




Dimensions [mm]

Switching voltage	Switching current	Switching system	Contacts	Contact material	Terminal	Part No.	Wiring diagram	Weight
								
Switching element for ring cable shoe								
500 VAC	10 A	Snap-action switching element	1 NO	Silver	Screw	704.900.1B	3	0.021 kg
			1 NC	Silver	Screw	704.900.2B	1	0.021 kg
			2 NO	Silver	Screw	704.900.3B	5	0.028 kg
			2 NC	Silver	Screw	704.900.4B	4	0.028 kg
			1 NC + 1 NO	Silver	Screw	704.900.5B	2	0.028 kg
								
Switching element for ring cable shoe								
500 VAC	10 A	Slow-make switching element	1 NO	Gold	Screw	704.911.1B	3	0.021 kg
			1 NC	Gold	Screw	704.911.2B	1	0.021 kg
			2 NO	Gold	Screw	704.911.3B	5	0.028 kg
			2 NC	Gold	Screw	704.911.4B	4	0.028 kg
			1 NC + 1 NO	Gold	Screw	704.911.5B	2	0.028 kg
			1 NO	Silver	Screw	704.910.1B	3	0.021 kg
			1 NC	Silver	Screw	704.910.2B	1	0.021 kg
			2 NO	Silver	Screw	704.910.3B	5	0.028 kg
			2 NC	Silver	Screw	704.910.4B	4	0.028 kg
			1 NC + 1 NO	Silver	Screw	704.910.5B	2	0.028 kg

Contacts: NC = Normally closed, NO = Normally open



Switching element E-stop



Dimensions [mm]

PIT = Push-in terminal,

P3 = Plug-in terminal 6.3 x 0.8 mm,

P4 = Double plug-in terminal 6.3 x 0.8 mm,




X = Screw terminal


Switching voltage	Switching current	Switching system	Contacts	Contact material	Terminal	Part No.	Wiring diagram	Weight
 Switching element for emergency-stop switch								
250 VAC	6 A	Slow-make switching element	1 NO	Gold	Push-in Terminal	704.917.1	3	0.019 kg
			1 NC	Gold	Push-in Terminal	704.917.2	1	0.019 kg
			2 NO	Gold	Push-in Terminal	704.917.3	5	0.026 kg
			2 NC	Gold	Push-in Terminal	704.917.4	4	0.019 kg
			1 NC + 1 NO	Gold	Push-in Terminal	704.917.5	2	0.026 kg
			1 NO	Silver	Push-in Terminal	704.918.1	3	0.019 kg
			1 NC	Silver	Push-in Terminal	704.918.2	1	0.019 kg
			2 NO	Silver	Push-in Terminal	704.918.3	5	0.026 kg
			2 NC	Silver	Push-in Terminal	704.918.4	4	0.019 kg
			1 NC + 1 NO	Silver	Push-in Terminal	704.918.5	2	0.026 kg
 Switching element for emergency-stop switch								
500 VAC	6 A	Slow-make switching element	1 NO	Silver	Plug 6.3 x 0.8 mm	704.915.1	3	0.021 kg
			1 NC	Silver	Plug 6.3 x 0.8 mm	704.915.2	1	0.021 kg
			2 NO	Silver	Plug 6.3 x 0.8 mm	704.915.3	5	0.028 kg
			2 NC	Silver	Plug 6.3 x 0.8 mm	704.915.4	4	0.028 kg
			1 NC + 1 NO	Silver	Plug 6.3 x 0.8 mm	704.915.5	2	0.028 kg

04 Accessories

Switching voltage	Switching current	Switching system	Contacts	Contact material	Terminal	Part No.	Wiring diagram	Weight
 Switching element for emergency-stop switch								
500 VAC	6 A	Slow-make switching element	1 NO	Silver	Double plug 6.3 x 0.8 mm	704.915.1/D	3	0.025 kg
			1 NC	Silver	Double plug 6.3 x 0.8 mm	704.915.2/D	1	0.025 kg
			2 NO	Silver	Double plug 6.3 x 0.8 mm	704.915.3/D	5	0.032 kg
			2 NC	Silver	Double plug 6.3 x 0.8 mm	704.915.4/D	4	0.032 kg
			1 NC + 1 NO	Silver	Double plug 6.3 x 0.8 mm	704.915.5/D	2	0.032 kg
 Switching element for emergency-stop switch								
500 VAC	10 A	Slow-make switching element	1 NO	Gold	Screw	704.911.1	3	0.021 kg
			1 NC	Gold	Screw	704.911.2	1	0.021 kg
			2 NO	Gold	Screw	704.911.3	5	0.028 kg
			2 NC	Gold	Screw	704.911.4	4	0.028 kg
			1 NC + 1 NO	Gold	Screw	704.911.5	2	0.028 kg
			1 NO	Silver	Screw	704.910.1	3	0.021 kg
			1 NC	Silver	Screw	704.910.2	1	0.021 kg
			2 NO	Silver	Screw	704.910.3	5	0.028 kg
			2 NC	Silver	Screw	704.910.4	4	0.028 kg
			1 NC + 1 NO	Silver	Screw	704.910.5	2	0.028 kg
			1 NO	Palladium	Screw	704.912.1	3	0.021 kg
			1 NC	Palladium	Screw	704.912.2	1	0.021 kg
			2 NO	Palladium	Screw	704.912.3	5	0.028 kg
			2 NC	Palladium	Screw	704.912.4	4	0.028 kg
			1 NC + 1 NO	Palladium	Screw	704.912.5	2	0.028 kg

Contacts: NC = Normally closed, NO = Normally open

 Wiring diagram 1	 Wiring diagram 2	 Wiring diagram 3	 Wiring diagram 4	 Wiring diagram 5
--	--	--	--	--

Switching element failsafe

Dimensions [mm]

PIT = Push-in terminal,

P3 = Plug-in terminal 6.3 x 0.8 mm,

P4 = Double plug-in terminal 6.3 x 0.8 mm,


X = Screw terminal

Product attribute	Switching voltage	Switching current	Switching system	Contacts	Contact material	Terminal	Part No.	Wiring diagram	Weight
 Switching element failsafe									
	500 VAC	10 A	Slow-make switching element	1 NC + 1 FS	Silver	Screw	704.910.4FS	1	0.027 kg
					Gold	Screw	704.911.4FS	1	0.027 kg
 Switching element failsafe									
for ring cable shoe	500 VAC	10 A	Slow-make switching element	1 NC + 1 FS	Silver	Screw	704.910.4BFS	1	0.027 kg
					Gold	Screw	704.911.4BFS	1	0.027 kg
 Switching element failsafe									
	500 VAC	10 A	Slow-make switching element	1 NC + 1 FS	Silver	Plug-in connection	704.915.4FS	1	0.027 kg
 Switching element failsafe									
	500 VAC	10 A	Slow-make switching element	1 NC + 1 FS	Gold	Double plug 6.3 x 0.8 mm	704.911.4DFS	1	0.027 kg
					Silver	Double plug 6.3 x 0.8 mm	704.915.4DFS	1	0.027 kg

04 Accessories

Product attribute	Switching voltage	Switching current	Switching system	Contacts	Contact material	Terminal	Part No.	Wiring diagram	Weight
 Switching element failsafe									
	500 VAC	10 A	Slow-make switching element	1 NC + 1 FS	Gold	Push-in Terminal	704.917.4FS	1	0.027 kg
					Silver	Push-in Terminal	704.918.4FS	1	0.027 kg

Contacts: NC = Normally closed, FS = Failsafe




Rotary switching element 30°

Additional Information

- Switching positions and functions of the rotary switching element are being produced according to customer specifications. Please contact your local EAO Sales Office


Product attribute	Switching positions	Rotary positions	Multi-step switch	Stages	Terminal	Part No.	Wiring diagram	Weight
 Rotary switching element 30°								
	A = Rest, I = End	9	1 pole	5	Screw	704.8A236	2	0.073 kg
	A = Rest, K = End	20	1 pole	5	Screw	704.8A237	3	0.073 kg
	A = Rest, L = End	11	1 pole	6	Screw	704.8A238	4	0.082 kg
	A = Rest, M = End	12	1 pole	6	Screw	704.8A239	1	0.082 kg
without stop	A = Rest	12	1 pole	6	Screw	704.8A639	1	0.082 kg



Rotary switching element 45°**Additional Information**

- Switching positions and functions of the rotary switching element are being produced according to customer specifications. Please contact your local EAO Sales Office

Switching positions	Rotary positions	Multi-step switch	Stages	Terminal	Part No.	Wiring diagram	Weight
 Rotary switching element 45°							
A = Rest, G = End	7	1 pole	4	Screw	704.8A234	1	0.064 kg
		2 pole	7	Screw	704.8A254	2	0.091 kg
A = Rest, H = End	8	1 pole	4	Screw	704.8A235	3	0.064 kg
		2 pole	8	Screw	704.8A255	4	0.100 kg






04 Accessories

Rotary switching element 60°

Additional Information

- Switching positions and functions of the rotary switching element are being produced according to customer specifications. Please contact your local EAO Sales Office


Switching positions	Rotary positions	Multi-step switch	Stages	Terminal	Part No.	Wiring diagram	Weight
 Rotary switching element 60°							
A = Rest, C = End	3	1 pole	2	Screw	704.8A230	1	0.046 kg
		1 pole, electrically isolated	2	Screw	704.8A730	2	0.046 kg
		2 pole	3	Screw	704.8A250	3	0.055 kg
		3 pole	5	Screw	704.8A270	4	0.073 kg
A = Rest, D = End	4	1 pole	2	Screw	704.8A231	5	0.046 kg
		1 pole, electrically isolated	2	Screw	704.8A731	6	0.046 kg
		2 pole	4	Screw	704.8A251	7	0.064 kg
		3 pole	6	Screw	704.8A271	8	0.082 kg
A = Rest, E = End	5	1 pole	3	Screw	704.8A232	9	0.055 kg
		2 pole	5	Screw	704.8A252	10	0.073 kg
		3 pole	8	Screw	704.8A272	11	0.100 kg
A = Rest, F = End	6	1 pole	3	Screw	704.8A233	12	0.055 kg
		2 pole	6	Screw	704.8A253	13	0.082 kg



5713152123 12391011171819 Wiring diagram 8	59 1237 Wiring diagram 9	591711 123713121519 Wiring diagram 10
5917112529 12371312151921222327 Wiring diagram 11	59 1237117 Wiring diagram 12	591721 12371314152319 Wiring diagram 13

Terminal cover

- Additional Information
- For covering of screw terminal



Dimensions [mm]

Part No.	Weight
 Terminal cover	
704.964.5	0.003 kg

04 Accessories

Terminal marking

Product attribute	Marking	Part No.	Weight
 Terminal marking			
2 NO for 1st or 2nd switching element	13/23 33/43	704.965.1	0.001 kg
	24/14 44/34	704.965.2	0.001 kg
2 NO for 3rd switching element	53/63 73/83	704.965.3	0.001 kg
	64/54 84/74	704.965.4	0.001 kg
2 NC for 1st or 2nd switching element	11/21 31/41	704.965.5	0.001 kg
	22/12 42/32	704.965.6	0.001 kg
2 NC for 3rd switching element	51/61 71/81	704.965.7	0.001 kg
	62/52 82/72	704.965.8	0.001 kg
1 NC + 1 NO for 1st or 2nd switching element	13/21 33/41	704.965.9	0.001 kg
	22/14 42/34	704.966.0	0.001 kg
1 NC + 1 NO for 3rd switching element	53/61 73/81	704.966.1	0.001 kg
	62/54 82/74	704.966.2	0.001 kg

Contacts: NC = Normally closed, NO = Normally open

Contact bridge


Additional Information

- For switching element with screw terminals
- Do not insert by Emergency-stop switches and by stop switches
- Available in unit of 10 pieces

Part No.	Weight
 Contact bridge	
704.990.1	0.001 kg

Illumination**LED, BA9s****Additional Information**

- The specified 6 VDC, 24 VDC Bi-colour; 130 VAC, 130 DC und 230 VAC versions are built with a protection diode
- The specified 12, 24, 28, 48 VAC/DC versions are built with a bridge rectifier
- The specified 130 VAC types are developed to run on a supply voltage of 130 VAC only. An operation at a higher supply voltage using commercial lampholders with integrated resistors, is not approved
- If the 24VDC Bi-colour lamp is driven with normal polarity (plus on middle contact of the lamp) the first mentioned colour will light up, with inverted polarity the second colour will light up
- Luminous intensity data of the LEDs on direct voltage
- Electrical and optical data are measured at 25 °C
- Luminosity and wave length variations caused by LED manufacturing processes may cause slight differences regarding the illumination



Dimensions [mm]

LED colour	Operating voltage	Operation current	Lumi. intensity	Dom. wavelength	Part No.	Weight
 Single-LED						
Single-LED red	6 VDC +10 %	17 mA ±15 %	400 mcd	630 nm	10-2506.1082	0.002 kg
	12 VAC/DC +10 %	16 mA ±15 %	390 mcd	630 nm	10-2509.1142	0.002 kg
	24 VAC/DC +10 %	15 mA ±15 %	350 mcd	630 nm	10-2512.1142	0.002 kg
	28 VAC/DC +10 %	13 mA ±15 %	300 mcd	630 nm	10-2513.1142	0.002 kg
	48 VAC/DC +10 %	8 mA ±15 %	200 mcd	630 nm	10-2519.1052	0.002 kg
	130 VDC +10 %	3 mA ±15 %	120 mcd	630 nm	10-2524.3042	0.002 kg
	130 VAC +10 %	5 mA ±15 %	180 mcd	630 nm	10-2H24.2052	0.002 kg
	230 VAC +10 %	3 mA ±15 %	120 mcd	630 nm	10-2H25.2042	0.002 kg
Single-LED yellow	6 VDC +10 %	17 mA ±15 %	340 mcd	587 nm	10-2506.1084	0.002 kg
	12 VAC/DC +10 %	16 mA ±15 %	340 mcd	587 nm	10-2509.1144	0.002 kg
	24 VAC/DC +10 %	15 mA ±15 %	300 mcd	587 nm	10-2512.1144	0.002 kg
	28 VAC/DC +10 %	13 mA ±15 %	270 mcd	587 nm	10-2513.1144	0.002 kg
	48 VAC/DC +10 %	8 mA ±15 %	180 mcd	587 nm	10-2519.1054	0.002 kg
	130 VDC +10 %	3 mA ±15 %	110 mcd	587 nm	10-2524.3044	0.002 kg
	130 VAC +10 %	5 mA ±15 %	160 mcd	587 nm	10-2H24.2054	0.002 kg
	230 VAC +10 %	3 mA ±15 %	110 mcd	587 nm	10-2H25.2044	0.002 kg
Single-LED green	6 VDC +10 %	7 mA ±15 %	1050 mcd	525 nm	10-2506.1085	0.002 kg
	12 VAC/DC +10 %	7 mA ±15 %	1050 mcd	525 nm	10-2509.1145	0.002 kg
	24 VAC/DC +10 %	7 mA ±15 %	1050 mcd	525 nm	10-2512.1145	0.002 kg
	28 VAC/DC +10 %	7 mA ±15 %	1050 mcd	525 nm	10-2513.1145	0.002 kg
	48 VAC/DC +10 %	4 mA ±15 %	600 mcd	525 nm	10-2519.1055	0.002 kg
	130 VDC +10 %	2 mA ±15 %	300 mcd	525 nm	10-2524.3045	0.002 kg
	130 VAC +10 %	3 mA ±15 %	450 mcd	525 nm	10-2H24.2055	0.002 kg
	230 VAC +10 %	2 mA ±15 %	300 mcd	525 nm	10-2H25.2045	0.002 kg

04 Accessories

LED colour	Operating voltage	Operation current	Lumi. intensity	Dom. wavelength	Part No.	Weight
Single-LED blue	6 VDC +10 %	17 mA ±15 %	780 mcd	470 nm	10-2506.1086	0.002 kg
	12 VAC/DC +10 %	16 mA ±15 %	720 mcd	470 nm	10-2509.1146	0.002 kg
	24 VAC/DC +10 %	15 mA ±15 %	680 mcd	470 nm	10-2512.1146	0.002 kg
	28 VAC/DC +10 %	13 mA ±15 %	590 mcd	470 nm	10-2513.1146	0.002 kg
	48 VAC/DC +10 %	8 mA ±15 %	400 mcd	470 nm	10-2519.1056	0.002 kg
	130 VDC +10 %	3 mA ±15 %	200 mcd	470 nm	10-2524.3046	0.002 kg
	130 VAC +10 %	5 mA ±15 %	230 mcd	470 nm	10-2H24.2056	0.002 kg
	230 VAC +10 %	3 mA ±15 %	200 mcd	470 nm	10-2H25.2046	0.002 kg
Single-LED white	6 VDC +10 %	17 mA ±15 %	850 mcd	x0.31/y0.32 nm	10-2506.1089	0.002 kg
	12 VAC/DC +10 %	16 mA ±15 %	800 mcd	x0.31/y0.32 nm	10-2509.1149	0.002 kg
	24 VAC/DC +10 %	15 mA ±15 %	750 mcd	x0.31/y0.32 nm	10-2512.1149	0.002 kg
	28 VAC/DC +10 %	13 mA ±15 %	650 mcd	x0.31/y0.32 nm	10-2513.1149	0.002 kg
	48 VAC/DC +10 %	8 mA ±15 %	400 mcd	x0.31/y0.32 nm	10-2519.1059	0.002 kg
	130 VDC +10 %	3 mA ±15 %	150 mcd	x0.31/y0.32 nm	10-2524.3049	0.002 kg
	130 VAC +10 %	5 mA ±15 %	250 mcd	x0.31/y0.32 nm	10-2H24.2059	0.002 kg
	230 VAC +10 %	3 mA ±15 %	150 mcd	x0.31/y0.32 nm	10-2H25.2049	0.002 kg
 Single-LED super bright						
Single-LED red	28 VAC/DC +10 %	14 mA ±15 %	7700 mcd	630 nm	10-2413.1132R	0.002 kg
Single-LED green	28 VAC/DC +10 %	13 mA ±15 %	12400 mcd	525 nm	10-2413.1125R	0.002 kg
Single-LED yellow	28 VAC/DC +10 %	14 mA ±15 %	4200 mcd	589 nm	10-2413.1134R	0.002 kg
 Bi-colour LED						
Bi-colour LED red/green	24 VDC +10 %	15 mA ±15 %	1200/900 mcd	625/525 nm	10-2H12.314A	0.002 kg
Bi-colour LED red/yellow	24 VDC +10 %	15 mA ±15 %	1200/550 mcd	625/589 nm	10-2H12.314B	0.002 kg
Bi-colour LED yellow/green	24 VDC +10 %	15 mA ±15 %	900/550 mcd	525/589 nm	10-2H12.314C	0.002 kg


Filament lamp, BA9s

Additional Information

- The max. overall length of the lamp may not exceed 28 mm


Operating voltage	Operation current	Part No.	Weight
 Filament lamp			
6 VAC/DC	200 mA±10 %	10-1406.1369	0.002 kg
12 VAC/DC	100 mA±10 %	10-1409.1329	0.002 kg
24 VAC/DC	50 mA±10 %	10-1412.1279	0.002 kg
36 VAC/DC	56 mA±10 %	10-1416.1289	0.002 kg
48 VAC/DC	42 mA±10 %	10-1419.1249	0.002 kg
60 VAC/DC	33 mA±10 %	10-1420.1219	0.002 kg
110 VAC/DC	22 mA±10 %	10-1422.1179	0.002 kg
130 VAC/DC	20 mA±10 %	10-1424.1179	0.002 kg

Diode block



Dimensions [mm]
PIT = Push-in terminal,
X = Screw terminal

Diode 1N4007	Terminal	Part No.	Wiring diagram	Weight
				
2	Push-in Terminal	704.942.5P	1	0.016 kg
	Screw	704.942.5	1	0.019 kg




Wiring diagram 1

Lamp transformer


Additional Information

- Lamp voltage/-current 24 VAC, 50 mA, 50/60 Hz




Dimensions [mm]

Operating voltage	Terminal	Part No.	Wiring diagram	Weight
 Lamp transformer				
115 / 24 VAC	Screw	704.970.3	1	0.100 kg
230 / 24 VAC	Screw	704.970.4	1	0.100 kg
400 / 24 VAC	Screw	704.970.5	1	0.100 kg
440 / 24 VAC	Screw	704.970.6	1	0.100 kg




Resistor block



Dimensions [mm]
PIT = Push-in terminal,
X = Screw terminal


Product attribute	Operating voltage	Terminal	Part No.	Wiring diagram	Weight
	Lamp voltage/-current 130 V, 20 mA	230 / 130 VAC	Push-in Terminal	704.941.0P	1 0.014 kg
		230 / 130 VAC	Screw	704.941.0	1 0.017 kg
	Lamp voltage/- current 60 V, 33 mA	125 / 60 VAC	Push-in Terminal	704.941.5P	1 0.014 kg
		125 / 60 VAC	Screw	704.941.5	1 0.017 kg



Resistor-diode block


Zusätzliche Informationen

- Lamp voltage/-current 130 V, 20 mA



Dimensions [mm]
PIT = Push-in terminal,
X = Screw terminal

Operating voltage	Terminal	Part No.	Wiring diagram	Weight
	Screw	704.941.9	1	0.017 kg
		704.941.9P	1	0.014 kg



Terminal plate empty

Additional Information

- For fitting with series resistors

Product attribute	Dimension	Part No.	Weight
 Terminal plate empty			
5 spaces	62.5 x 60 x 15 mm	02-912.1	0.025 kg
10 spaces	125 x 60 x 15 mm	02-912.2	0.045 kg
15 spaces	187.6 x 60 x 15 mm	02-912.3	0.090 kg
20 spaces	250 x 60 x 15 mm	02-912.4	0.095 kg


Emergency-stop switch**Emergency-stop legend****Additional Information**

- Front panel thickness 3 mm max.

Dimension	Mounting cut-out	Marking	Colour	Part No.	Weight
 Emergency-stop legend					
Ø 90 x 1 mm	Ø 22.5 mm	NOT AUS	yellow	704.963.0	0.011 kg
		EMERGENCY STOP	yellow	704.963.1	0.011 kg
		ARRET D'URGENCE	yellow	704.963.2	0.011 kg
		NOT HALT	yellow	704.963.3	0.011 kg
Ø 59 x 1 mm	Ø 22.5 mm	NOT AUS	yellow	704.963.5	0.011 kg
		EMERGENCY STOP	yellow	704.963.6	0.011 kg
		ARRET D'URGENCE	yellow	704.963.7	0.011 kg
		NOT HALT	yellow	704.963.8	0.011 kg

E-stop protective shroud, IP 65**Additional Information**

- Use only for Part No. 704.064.2 und 704.066.2
- The protection shroud is not suitable for a proper use of emergency-stop. It can obstruct a spontaneous operation of the emergency-stop




Dimensions [mm]

Dimension	Material	Colour	Standard	Part No.	Weight
 E-stop protective shroud					
Ø 50 mm	Plastic	yellow		704.927.8	0.052 kg
 E-stop protective shroud					
Ø 83 mm	Plastic	yellow	SEMI S2-93/12.4.c	704.927.9	0.067 kg

E-stop protective shroud, IP 67

- Additional Information**
- Front panel thickness 1 2.5 mm other actuators
 - Front panel thickness 1 5 mm Emergency-stop switch
 - With anti-twist device
 - When using a protective shroud the e-stop or stop switch has to be turned by 180° to be mounted. See dimensional drawing
 - Do not use solvents when cleaning




Dimensions mm]

Dimension	Marking	Colour	Protection degree	Part No.	Weight
 E-stop protective shroud					
Ø 65 mm		yellow	IK 07	704.927.6	0.017 kg
	NOT-AUS	yellow	IK 07	704.927.6A	0.017 kg
	EMERGENCY-STOP	yellow	IK 07	704.927.6B	0.017 kg
	EMERGENCY-STOP / NOT-AUS	yellow	IK 07	704.927.6C	0.017 kg
	NOT-HALT	yellow	IK 07	704.927.6D	0.017 kg

Emergency-stop enclosure**Additional Information**

- Bottom grey similar RAL 7035; cover lead-sealable, yellow similar RAL 1004
- Openings for cable gland M16 or M20



Dimensions [mm]

Product attribute	Dimension	Part No.	Weight
 Emergency-stop enclosure with mounting cut-out 1 x Ø 22.5 mm, with anti-twist device	L 94 x B 94 x H 81 mm	704.945.0	0.195 kg
	L 65 x B 65 x H 81 mm	704.945.7	0.127 kg
 Emergency-stop enclosure with mounting cut-out 1 x Ø 22.5 mm, with anti-twist device	L 94 x B 65 x H 81 mm	704.945.8	0.157 kg
	L 65 x B 65 x H 81 mm	704.945.6	0.111 kg

Cable gland, IP 68**Additional Information**

- With traction relief
- With fixing nut

Product attribute	Thread	Material	Colour	Part No.	Weight
 Cable gland Clamping range Ø 4 ... 10 mm, thread length 8 mm	M16 x 1.5	Plastic	grey	61-9481.6	0.007 kg
	M20 x 1.5	Plastic	grey	704.945.6	0.011 kg

04 Accessories

Mounting


Anti-twist ring

Part No.	Weight
 Anti-twist ring, flush design	
704.954.0	0.002 kg

Reducing ring

Additional Information

- Devices Ø 22.5 mm in mounting cut-out Ø 30.5 mm
- With the metal bayonet flange you can use one reduction ring. If you have a plastic bayonet flange you need to install two reduction rings
- The colour of anodized aluminium parts can vary due to technical production reasons




Dimensions [mm]

Product attribute	Material	Colour	Part No.	Weight
 Reducing ring				
	Aluminium	black anodized	704.960.0	0.004 kg
		natural anodized	704.960.8	0.004 kg
 Reducing ring with opening for anti rotation pin				
with slot for anti-twist device	Aluminium	natural anodized	704.960.8A	0.004 kg

Mounting plate

Additional Information

- For separate mounting of lamp transformer, resistor block or capacitor block




Dimensions [mm]

Material	Colour	Part No.	Weight
 Mounting plate			
Plastic	grey	704.940.8	0.006 kg

Snap-on base

Additional Information

- To snap-on, for separate mounting of lamp transformer, resistor block or capacitor block



Dimensions [mm]

Product attribute	Part No.	Weight
 Snap-on base		
DIN mounting bar EN 50035	704.940.9	0.006 kg
 Snap-on base		
DIN mounting bar EN 50022	704.941.1	0.006 kg

04 Accessories

Reinforcement ring

Additional Information

- For thin front panel and plastic case

Dimension	Mounting cut-out	Material	Colour	Part No.	Weight
 Reinforcement ring					
44 x 29 x 3 mm	Ø 22.5 mm	Steel sheet	galvanized, yellow passivated	704.960.9	0.014 kg

Lens plug

Additional Information

- With lamp remover function (BA9s)
- For mounting and dismantling of the round lens, flush design

Part No.	Weight
 Lens plug for round lens, flush design	
700.006.0	0.003 kg

Lens remover

Additional Information

- For dismantling of the square lens, flush design

Part No.	Weight
 Lens remover	
98-968	0.004 kg

Mounting tool indicator**Additional Information**

- For Indicators full-face illumination, compact
- for tightening or loosening of the fixing nut

Product attribute	Part No.	Weight
	Mounting tool for indicator	
	700.005.0	0.020 kg

Mounting tool key insert switch**Additional Information**

- for tightening or loosening of the fixing nut

Product attribute	Part No.	Weight
	Mounting tool for key insert switch	
	704.990.0	0.020 kg

Cable gland, IP 68**Additional Information**

- With traction relief
- With fixing nut


Product attribute	Thread	Material	Colour	Part No.	Weight
 Cable gland					
Clamping range Ø 4 ... 10 mm, thread length 8 mm	M16 x 1.5	Plastic	grey	61-9481.6	0.007 kg
Clamping range Ø 6 ... 12 mm, thread length 9 mm	M20 x 1.5	Plastic	grey	704.945.6	0.011 kg

04 Accessories

Enclosure, IP 66

Additional Information

- Cover lead-sealable
- Openings for cable gland M16 or M20



Dimensions [mm]

Product attribute	Dimension	Material	Colour	Part No.	Weight
 Enclosure with mounting cut-out 1 x Ø 22.5 mm, with anti-twist device	L 94 x B 94 x H 81 mm	Plastic	grey, similar RAL 7035	704.945.1	0.211 kg
 Enclosure with mounting cut-out 2 x Ø 22.5 mm, with anti-twist device	L 130 x B 94 x H 81 mm	Plastic	grey, similar RAL 7035	704.945.2	0.251 kg
 Enclosure with mounting cut-out 3 x Ø 22.5 mm, with anti-twist device	L 180 x B 94 x H 81 mm	Plastic	grey, similar RAL 7035	704.945.3	0.313 kg
 Enclosure with mounting cut-out 4 x Ø 22.5 mm, with anti-twist device	L 180 x B 182 x H 110 mm	Plastic	grey, similar RAL 7035	704.945.4	0.572 kg
 Enclosure with mounting cut-out 6 x Ø 22.5 mm, with anti-twist device	L 180 x B 182 x H 110 mm	Plastic	grey, similar RAL 7035	704.945.5	0.568 kg

Slow-make switching element

Switching system

The double-break, slow-make switching element is equipped with one or two independent contact systems, acting as normally open or normally closed contact. The normally closed contact has forced opening.

Slow-make contacts with forced action are ideal for high switch ratings.

Up to three switching elements can be snapped to each actuator. For the emergency-stop pushbutton use the slow-make switching element (max. 3).

Material

Material of contact

Hardsilver, gold-silver, silver-palladium (for aggressive atmospheres)

Switch housing

Polycarbonate (PC)

Mechanical characteristics

Terminals

Screw terminals

Plug-in terminals 6.3 x 0.8 mm

max. wire cross-section 2 x 2.5 mm²

max. wire cross-section of stranded cable 2 x 1.5 mm²

For switches with plug-in terminals it is necessary to provide insulation sleeves and to maintain a spacing of 65 mm between rows (mounting cut-outs)

Tightening torque

Screws at the mounting flange max. 25–30 Ncm

Screws at switching element max. 50 Ncm

Actuating force

1 Normally closed 2 N

1 Normally open 3.1 N

Actuating travel

5.8 mm ± 0.2 mm

Rebound time

≤ 1 ms

Mechanical lifetime

(with 1 switching element)

Pushbutton maintained action 1.5 million Cycles of operation

Pushbutton momentary action 3 million Cycles of operation

Selector switch maintained action 1.25 million Cycles of operation

Selector switch momentary action 2.5 million Cycles of operation

Emergency-stop switch 50 000 Cycles of operation

Keylock switch maintained action 25 000 Cycles of operation

Keylock switch momentary action 50 000 Cycles of operation

Electrical characteristics

Standards

The switches comply with the “Standards for low-voltage switching devices” EN IEC 60947-5-1

Rated Insulation Voltage U_i

500 VAC/600 VDC, as per EN IEC 60947-5-1

Contact resistance

New state ≤ 50 mΩ as per DIN IEC 60512-2-4

Isolation resistance

≥ 10 MΩ between open contacts at 500 VDC, as per DIN IEC 60512-3-1

Electrical life

6050 cycles of operations

Conventional free air thermal current I_{th}

As per EN IEC 60947-5-1

6 A for plug-in terminals

10 A for screw terminals

the maximum current in continuous operation and at ambient temperature must not exceed the quoted maximum values.

Switch rating

At switch rating AC for gold-silver, silver-palladium and hardsilver contacts, service category AC-15, as per EN IEC 60947-5-1 (cos φ 0.3)

Voltage	230 VAC	400 VAC	500 VAC
Current	7 A	5 A	4 A

At switch rating DC for gold-silver and hardsilver contacts, service category DC-13, as per EN IEC 60947-5-1

Voltage	24 VDC	60 VDC	110 VDC	250 VDC
Current	10 A	5 A	2.5 A	0.6 A

Recommended minimum operational data

Gold-silver contacts:

Voltage	24 VDC	110 VDC
Current	5 mA	2 mA

Hardsilver contacts:

Voltage	24 VDC	110 VDC
Current	50 mA	10 mA

Protection class

Indicators and switches, fit for mounting into devices with protection class II

04 Technical data

Environmental conditions

Storage temperature

-40 °C ... +85 °C

Operating temperature

-40 °C ... +55 °C

(other temperatures on request)

Protection degree

IP 00

Shock resistance

(single impacts, semi-sinusoidal)

300 m/s² puls width 11 ms, as per EN IEC 60068-2-27

Vibration resistance

(sinusoidal)

100 m/s² at 10 Hz ... 500 Hz, amplitude 0.75 mm, as per

EN IEC 60068-2-6

Approvals

Approbations

CB (IEC 60947)

CCC

CSA

Germanischer Lloyd

GOST

NFF 16-102

UL

Declaration of conformity

CE

Snap-action switching element

Switching system

The double-break, snap-action switching element is equipped with one or two independent contact systems, acting as normally open or normally closed contact. The snap-action switching element is fitted with self-cleaning contacts.

Up to three switching elements can be snapped to each actuator. Snap-action switching elements are not permissible for emergency-stop pushbuttons!

Material

Material of contact

Hardsilver, gold-silver, silver-palladium (for aggressive atmospheres)

Switch housing

Polycarbonate (PC)

Mechanical characteristics

Terminals

Screw terminals

Plug-in terminals 6.3 x 0.8 mm

max. wire cross-section 2 x 2.5 mm²

max. wire cross-section of stranded cable 2 x 1.5 mm²

For switches with plug-in terminals it is necessary to provide insulation sleeves and to maintain a spacing of 65 mm between rows (mounting cut-outs)

Tightening torque

Screws at the mounting flange max. 25–30 Ncm

Screws at switching element max. 50 Ncm

Actuating force

1 Normally closed 1.9 N

1 Normally open 2 N

Actuating travel

5.8 mm ± 0.2 mm

Rebound time

≤ 3 ms

Mechanical lifetime

(with 1 switching element)

Pushbutton maintained action 1.5 million Cycles of operation

Pushbutton momentary action 3 million Cycles of operation

Selector switch maintained action 1.25 million Cycles of operation

Selector switch momentary action 2.5 million Cycles of operation

Keylock switch maintained action 25 000 Cycles of operation

Keylock switch momentary action 50 000 Cycles of operation

Electrical characteristics

Standards

The switches comply with the "Standards for low-voltage switching devices" EN IEC 60947-5-1

Rated Insulation Voltage U_i

500 VAC/600 VDC, as per EN IEC 60947-5-1

Contact resistance

New state ≤ 50 mΩ as per DIN IEC 60512-2-4

Isolation resistance

≥ 10 MΩ between open contacts at 500 VDC, as per DIN IEC 60512-3-1

Electrical life

50 000 cycles of operations

Conventional free air thermal current I_{th}

As per EN IEC 60947-5-1

6 A for plug-in terminals

10 A for screw terminals

the maximum current in continuous operation and at ambient temperature must not exceed the quoted maximum values.

Switch rating

At switch rating AC for gold-silver, silver-palladium and hardsilver contacts, service category AC-15, as per EN IEC 60947-5-1 ($\cos\phi$ 0.3)

Voltage	230 VAC	400 VAC	500 VAC
Current	6 A	4 A	2.5 A

At switch rating DC for gold-silver and hardsilver contacts, service category DC-13, as per EN IEC 60947-5-1

Voltage	24 VDC	60 VDC	110 VDC
Current	10 A	3 A	1 A

Recommended minimum operational data

Gold-silver contacts:

Voltage	5 VDC	24 VDC	110 VDC
Current	15 mA	5 mA	2 mA

Hardsilver contacts:

Voltage	24 VDC	110 VDC
Current	50 mA	10 mA

Protection class

Indicators and switches, fit for mounting into devices with protection class II

Environmental conditions

Storage temperature

-40 °C ... +85 °C

Operating temperature

-40 °C ... +55 °C

(other temperatures on request)

Protection degree

IP 00

Shock resistance

(single impacts, semi-sinusoidal)

300 m/s² puls width 11 ms, as per EN IEC 60068-2-27

Vibration resistance

(sinusoidal)

100 m/s² at 10 Hz ... 500 Hz, amplitude 0.75 mm, as per EN IEC 60068-2-6

Approvals

Approbations

CB (IEC 60947)

CCC

CSA

Germanischer Lloyd

GOST

NFF 16-102

UL

Declaration of conformity

CE

Slow-make switching element PIT

Switching system

The double-break, slow-make switching element is equipped with one or two independent contact systems, acting as normally open or normally closed contact. The normally closed contact has forced opening.

Slow-make contacts with forced action are ideal for high switch ratings.

Up to three switching elements can be snapped to each actuator. For the emergency-stop pushbutton use the slow-make switching element (max. 3).

Material

Material of contact

Hardsilver and gold-silver

Switch housing

Polycarbonate (PC)

Mechanical characteristics

Terminals

PIT push-in terminal

Stripping 8 mm

Wire cross-section:

Wire 0.2 to 1.0 mm²

Stranded wire 0.2 to 1.0 mm² without core and sleeve

Stranded wire 0.2 to 0.75 mm² with core and sleeve

Tightening torque

Screws at the mounting flange max. 25 Ncm

Actuating force

1 Normally closed 2 N

1 Normally open 3.1 N

Actuating travel

5.8 mm ± 0.2 mm

Rebound time

≤ 1 ms

04 Technical data

Mechanical lifetime

(with 1 switching element)

Pushbutton maintained action	1.5 million Cycles of operation
Pushbutton momentary action	3 million Cycles of operation
Selector switch maintained action	1.25 million Cycles of operation
Selector switch momentary action	2.5 million Cycles of operation
Emergency-stop switch	50 000 Cycles of operation
Keylock switch maintained action	25 000 Cycles of operation
Keylock switch momentary action	50 000 Cycles of operation

Electrical characteristics

Standards

The switches comply with EN IEC 60947-1/EN IEC 60947-5-1

Rated Insulation Voltage U_i

500 VAC/600 VDC, as per EN IEC 60947-5-1

Contact resistance

New state $\leq 50 \text{ m}\Omega$ as per DIN IEC 60512-2-4

Isolation resistance

$\geq 10 \text{ M}\Omega$ between open contacts at 500 VDC, as per DIN IEC 60512-3-1

Electrical life

6050 cycles of operations

Conventional free air thermal current I_{th}

6 A, as per EN IEC 60947-5-1

the maximum current in continuous operation and at ambient temperature must not exceed the quoted maximum values.

Switch rating

At switch rating AC for gold-silver and hardsilver contacts, service category AC-15, as per EN IEC 60947-5-1 ($\cos\phi$ 0.3)

Voltage	250 VAC
Current	6 A

At switch rating DC for gold-silver and hardsilver contacts, service category DC-13, as per EN IEC 60947-5-1

Voltage	24 VDC	110 VDC
Current	6 A	1.0 A

Recommended minimum operational data

Gold-silver contacts:

Voltage	24 VDC
Current	5 mA

Hardsilver contacts:

Voltage	24 VDC
Current	50 mA

Protection class

Indicators and switches, fit for mounting into devices with protection class II

Environmental conditions

Storage temperature

-40 °C ... +85 °C

Operating temperature

-40 °C ... +55 °C
(other temperatures on request)

Protection degree

IP 20

Shock resistance

(single impacts, semi-sinusoidal)
300 m/s² puls width 11 ms, as per EN IEC 60068-2-27

Approvals

Approbations

CB (IEC 60947)
CSA
Germanischer Lloyd
GOST
NFF 16-102
UL

Declaration of conformity

CE

Snap-action switching element PIT

Switching system

The double-break, snap-action switching element is equipped with one or two independent contact systems, acting as normally open or normally closed contact. The snap-action switching element is fitted with self-cleaning contacts.

Up to three switching elements can be snapped to each actuator. Snap-action switching elements are not permissible for emergency-stop pushbuttons!

Material

Material of contact

Hardsilver and gold-silver

Switch housing

Polycarbonate (PC)

Mechanical characteristics

Terminals

PIT push-in terminal
 Skinning 8mm
 Wire cross-section:
 Wire 0.2 to 1.0mm²
 Stranded wire 0.2 to 1.0mm² without core and sleeve
 Stranded wire 0.2 to 0.75mm² with core and sleeve

Tightening torque

Screws at the mounting flange max. 25Ncm

Actuating force

1 Normally closed 1.9N
 1 Normally open 2N

Actuating travel

5.8mm ± 0.2mm

Rebound time

≤ 3ms

Mechanical lifetime

(with 1 switching element)
 Pushbutton maintained action 1.5 million Cycles of operation
 Pushbutton momentary action 3 million Cycles of operation
 Selector switch maintained action 1.25 million Cycles of operation
 Selector switch momentary action 2.5 million Cycles of operation
 Emergency-stop switch 50 000 Cycles of operation
 Keylock switch maintained action 25 000 Cycles of operation
 Keylock switch momentary action 50 000 Cycles of operation

Electrical characteristics

Standards

The switches comply with EN IEC 60947-1/EN IEC 60947-5-1

Rated Insulation Voltage U_i

500VAC/600VDC, as per EN IEC 60947-5-1

Contact resistance

New state ≤ 50mΩ as per DIN IEC 60512-2-4

Isolation resistance

≥ 10MΩ between open contacts at 500 VDC, as per DIN IEC 60512-3-1

Electrical life

50 000 cycles of operations

Conventional free air thermal current I_{th}

6A, as per EN IEC 60947-5-1
 the maximum current in continuous operation and at ambient temperature must not exceed the quoted maximum values.

Switch rating

At switch rating AC for gold-silver and hardsilver contacts, service category AC-15, as per EN IEC 60947-5-1 (cosφ 0.3)

Voltage 250VAC
 Current 6A

At switch rating DC for gold-silver and hardsilver contacts, service category DC-13, as per EN IEC 60947-5-1

Voltage 24VDC 110VDC
 Current 6A 1.0A

Recommended minimum operational data

Gold-silver contacts:

Voltage 24VDC
 Current 5mA

Hardsilver contacts:

Voltage 24VDC
 Current 50mA

Protection class

Indicators and switches, fit for mounting into devices with protection class II

Environmental conditions

Storage temperature

-40°C ... +85°C

Operating temperature

-40°C ... +55°C
 (other temperatures on request)

Protection degree

IP 20

Shock resistance

(single impacts, semi-sinusoidal)
 300m/s² puls width 11 ms, as per EN IEC 60068-2-27

Vibration resistance

(sinusoidal)
 100m/s² at 10Hz ... 500Hz, as per EN IEC 60068-2-6 and EN 61373 Increased broad band noise, class 1B

Approvals

Approbations

CB (IEC 60947)
 CSA
 Germanischer Lloyd
 GOST
 NFF 16-102
 UL

Declaration of conformity

CE

04 Technical data

Lamp block

Material

Housing

Polycarbonate (PC)

Mechanical characteristics

Terminals

Screw terminals

Plug-in terminals 6.3 x 0.8 mm

max. wire cross-section 2 x 2.5 mm²

max. wire cross-section of stranded cable 2 x 1.5 mm²

For switches with plug-in terminals it is necessary to provide insulation sleeves and to maintain a spacing of 65 mm between rows (mounting cut-outs)

Electrical characteristics

Standards

The switches comply with EN IEC 60947-1/EN IEC 60947-5-1

Illumination

Voltage 250 V max.

Power 2.6 W max.

BA9s standard adaptable.

Environmental conditions

Storage temperature

-40 °C ... +85 °C

Operating temperature

-40 °C ... +55 °C

(other temperatures on request)

Protection degree

IP 00

Shock resistance

(single impacts, semi-sinusoidal)

300 m/s² puls width 11 ms, as per EN IEC 60068-2-27

Vibration resistance

(sinusoidal)

100 m/s² at 10 Hz ... 500 Hz, as per EN IEC 60068-2-6 and

EN 61373 Increased broad band noise, class 1B

Lamp block PIT

Material

Housing

Polycarbonate (PC)

Mechanical characteristics

Terminals

PIT push-in terminal

Skinning 8 mm

Wire cross-section:

Wire 0.2 to 1.0 mm²

Stranded wire 0.2 to 1.0 mm² without core and sleeve

Stranded wire 0.2 to 0.75 mm² with core and sleeve

Electrical characteristics

Standards

The switches comply with EN IEC 60947-1/EN IEC 60947-5-1

Illumination

Voltage 250 V max.

Power 2.6 W max.

BA9s standard adaptable.

Environmental conditions

Storage temperature

-40 °C ... +85 °C

Operating temperature

-40 °C ... +55 °C

(other temperatures on request)

Protection degree

IP 20

Shock resistance

(single impacts, semi-sinusoidal)

300 m/s² puls width 11 ms, as per EN IEC 60068-2-27

Vibration resistance

(sinusoidal)

100 m/s² at 10 Hz ... 500 Hz, as per EN IEC 60068-2-6 and

EN 61373 Increased broad band noise, class 1B

Buzzer

Buzzer system

System

Piezo disc

Material

Buzzer case

Polyamide

Front cap

Plastic Polyamide

Metal Nickel-plated brass (sea-water proof)

Mechanical characteristics

Terminals

Plug-in terminal 2.8 x 0.5 mm

Tightening torque

for fixing nut max. 25 Ncm

Electrical characteristics

Frequency (tone)

approx. 2.8 kHz continuous tone only

Sound pressure

95 db (A) ± 8 dB at a distance of 0.1 m

Operation Voltage/Current

Operation Voltage 24 VDC $\pm 10\%$

Operation Current ≤ 25 mA

Environmental conditions

Storage temperature

-40 °C ... +85 °C

Operating temperature

-40 °C ... +55 °C

(other temperatures on request)

Protection degree

as per EN IEC 60529, frontside

IP 40, devices flush design

IP 65, devices raised design

Approvals

Declaration of conformity

CE

Actuator

Material

Front ring

Polyamide, Aluminium or Stainless steel

Mounting flange

Polyethylene terephthalate

Actuator housing

Polycarbonate, Polyamide

Mechanical characteristics

Actuating force

Mounting style square flush 6.2 N

other mounting styles 8 N

Actuating travel

5.8 mm ± 0.2 mm

Mechanical lifetime

(with 1 switching element)

Pushbutton ≤ 3 million Cycles of operation

Selector switch ≤ 2.5 million Cycles of operation

Stop switch $\leq 50\,000$ Cycles of operation

Fool proofed E-stop $\geq 50\,000$ Cycles of operation

Keylock switch $\leq 50\,000$ Cycles of operation

Key insert switches $\leq 250\,000$ Cycles of operation

Keylock switch

The standard lock number is 251, the last digit of the device Part No. = 0 (example: 704.335.0).

Additional lock numbers are available:

252 last digit = 1; 253 last digit = 2; 254 last digit = 3

255 last digit = 4; 256 last digit = 5; 257 last digit = 6

258 last digit = 7; 259 last digit = 8; 260 last digit = 9

04 Technical data

Electrical characteristics

Standards

The switches comply with the “Rules for low-voltage switching devices” EN IEC 60947-5-1

Environmental conditions

Storage temperature

-40 °C ... +85 °C

Operating temperature

-40 °C ... +55 °C

(other temperatures on request)

Protection degree

As per EN IEC 60529

frontside IP 65 (IP 67 Key insert switch)

Rotary selector switching element

Mechanical characteristics

Terminals

Screw terminals

Terminal lead material copper wires only

max. permissible wire gage:

Single-core or stranded wire 2 x 1.5 mm² (2 x AWG 14)

flexible wire 2 x 1.5 mm² (2 x AWG 16)

Tightening torque

for fixing nut max. 25 Ncm

Number of stages

1 to 8 positions max.

Number of contacts

1 to 16 max. normally open contacts

(contact positioning according circuit drawing)

Switching angle

Basic position of switching position “A” is 9 o'clock

Maintained action	Switching angle
12 max.	30°
8 max.	45°
6 max.	60°
4 max.	90°

Momentary action with release 24°

(provide at the beginning or at the end)

Standard type of Kraus & Naimer

CG4 Hard Silver contacts with 1 µm Gold layer

CG4-1 Hard Silver contacts with 35 µm Gold layer

Electrical characteristics

Minimum Voltage

20 V

Rated Impulse Withstand Voltage U_{imp}

4 kV

Short Circuit Protection

Max. fuse size (gL-characteristic) 10 A

Rated short-time withstand current (1s-current) 90 A

Electrical characteristics for AC

Standards

The devices comply with: EN IEC 60947-3, VDE 0660 part 107

Rated Operational Voltage U_e

440 V

Rated Insulation Voltage U_i

440 V

Rated Thermal Current I_u / I_{th}

10 A

Rated Operational Current I_e

AC-15 Switching of control devices, contactors, valves etc.

110 V–120 V 2.5 A

220 V–240 V 2.5 A

380 V–440 V 1.5 A

No load operation
10A

AC-21A Switching of resistive loads, including moderate overloads
For switchin of power > 1 kW
10A

AC-22A Switching of combined resistive or low inductive loads
including moderate overloads
220V–240V 10A

Rated Utilization Category

AC-2 Slip ring motor starting, reversing and plugging, star-delta
starting 3 phase, 3 pole

220V–240V 2.5kW
380V–440V 4.5kW

AC-3 Direct-on-line starting, star-delta starting

3 phase, 3 pole	220V–240V	2.50kW
	380V–440V	2.20kW
1 phase, 2 pole	110V–120V	0.30kW
	220V–240V	0.55kW
	380V–440V	0.75kW

AC-Direct-on-line starting, reversing, plugging and inching

3 phase, 3 pole	220V–240V	0.37kW
	380V–440V	0.55kW
1 phase, 2 pole	110V–120V	0.15kW
	220V–240V	0.25kW
	380V–440V	0.50kW

AC-23A Frequent switching of motors or other high inductive
loads

3 phase, 3 pole	220V–240V	1.80kW
	380V–440V	3.00kW
1 phase, 2 pole	110V–120V	0.37kW
	220V–240V	0.75kW
	380V–440V	1.10kW

Overvoltage category

III, valid for lines with grounded common neutral termination

Degree of pollution

3, valid for lines with grounded common neutral termination

Electrical characteristics for AC (UL/Canada)

Rated operational voltage

300V

Rated Insulation Voltage U_i

300V

Rated Thermal Current

10A

Ampere Rating

Resistive or low inductive loads, for switching of power > 1 kW, 10A

Ratings

Standard motor load, DOL Rating (similar AC-3)

3 phase, 3 pole	110V–120V	0.75HP
	220V–240V	1.00HP
1 phase, 2 pole	110V–120V	0.33HP
	220V–240V	0.75HP
	277V–277V	0.75HP

Pilot Duty, Heavy

300VAC

Electrical characteristics for DC

Switch Rating DC

Resistive loads $T \leq 1$ ms

Number of series contact(s)							Switch Capacity
1	2	3	4	5	6	8	
24V	48V	70V	95V	120V	145V	190V	10.0A
48V	95V	140V	190V	240V	290V	350V	6.0A
60V	120V	180V	240V	300V	360V	450V	2.5A
110V	220V	330V	440V	550V	660V		0.7A
220V	440V	660V					0.3A
440V	660V						0.2A

Inductive loads $T = 50$ ms

Number of series contact(s)							Switch Capacity
1	2	3	4	5	6	8	
24V	48V	70V	95V	120V	145V	190V	6.0A
30V	60V	90V	120V	150V	180V	240V	3.0A
48V	95V	140V	190V	240V	290V	350V	1.0A
60V	120V	180V	240V	300V	360V	450V	0.7A
110V	220V	330V	440V	550V	660V		0.3A

Environment conditions

Operating temperature

Ambient Temperatures of Stages

open at 100% I_u / I_{th} 55°C during 24 h with peaks up to 60°C
enclosed at 100% I_{the} 35°C during 24 h with peaks up to 40°C

04 Technical data

Flasher

Material

Housing

Polycarbonat (PC), nach UL 94 V0

Mechanical characteristics

Terminals

Screw terminal

Electrical characteristics

Flasher frequency

1.5 Hz

Relative duty factor

ca. 50 %

Environment conditions

Operating temperature

0° ... +50 °C

Protection degree

Rear side IP30

EAO reserves the right to alter specifications without further notice.

General notes

1. Engraving

In addition to the most commonly used world languages, in DIN1451-3 close spacing, other typefaces are available as Scandinavian, Slavic, Greek, Russian and Polish. The engraved marking caps and plates are filled with black or white colour. Standard height of letters is 3 mm. If the height is not specified, we will supply 3 mm engraved letters.

2. Hot stamping

Standard legends and ISO symbols are hot stamped. For larger series it is worth considering markings by means of hot stamping. We will be pleased to advise you.


3. Film inserts

Instead of using engraving the square lenses can be fitted with film inserts, as an alternative. Film thickness is 0.25 mm. Max. film size: for Indicator 24.5 x 24.5 mm, for illuminated Pushbutton 21.5 x 21.5 mm.

Engraving marking cap for Indicator round, full face illumination

All dimensions in mm

Height of letters h	Number of lines	Number of letters per line (target value)			Line spacing d
		b1	b2	b3	
3	3	11	10	9	4.6
4	2	8	7	–	6.6
8	1	4	–	–	–




The gap between two words results in each case a letter less.

Engraving marking cap for Indicator and illuminated Pushbutton round, front illumination

All dimensions in mm

Height of letters h	Number of lines	Number of letters per line (target value)			Line spacing d
		b1	b2	b3	
3	3	9	9	7	4.6
4	2	7	6	–	6.6
8	1	3	–	–	–




The gap between two words results in each case a letter less.

04 Marking

Engraving diffusor cap for Indicator square, full face illumination

All dimensions in mm

Height of letters h	Number of lines	Number of capital letters per line(target value)	Number of small letters per line (target value)
2.5	6	13	14
3.0	5	11	12
4.0	4	8	8-9
5.0	3	6-7	7
6.0	2	5-6	6
8.0	1	4	4-5




The gap between two words results in each case a letter less.

Engraving lens holder for Indicator and Illuminate Pushbutton square, front illumination

All dimensions in mm

Height of letters h	Number of lines	Number of capital letters per line(target value)	Number of small letters per line (target value)
2.5	5	9	9-10
3.0	4	7-8	8
4.0	3	5-6	6
5.0	2	4-5	4-5
6.0	2	3-4	4
8.0	1	2-3	3



The gap between two words results in each case a letter less.

Important: Consider lens holder mounting orientation before specifying engraving charachters!

Engraving legend plates


All dimensions in mm

Dimension	Devices mounting style	Height of letters h	Number of lines	Number of letters per line (target value)	Image
30 x 50	round, raised	3	2	12	B1
		4	1	7	B1
		8	1	4	B1
35 x 57.5	round, flush	3	2	12	B2
		4	1	7	B2
		8	1	4	B2
18 x 35	square, flush	3	3	16	B3
		4	2	10	B3

B1

B2

B3



The gap between two words results in each case a letter less.

Standard texts for marking plates and marking caps for Indicator and Illuminated Pushbutton

Height of letters 6 mm

I Part Nr. 704.609.912001	II Part Nr. 704.609.912002	III Part Nr. 704.609.912003	O Part Nr. 704.609.912004
EIN Part Nr. 704.609.912005	AUS Part Nr. 704.609.912006	AUF Part Nr. 704.609.912007	AB Part Nr. 704.609.912008
START Part Nr. 704.609.912009	STOP Part Nr. 704.609.912010	HAND Part Nr. 704.609.912011	AUTO Part Nr. 704.609.912012
ZU Part Nr. 704.609.912013	ON Part Nr. 704.609.912014	OFF Part Nr. 704.609.912015	ARRET Part Nr. 704.609.912016
MARCHE Part Nr. 704.609.912017	RESET Part Nr. 704.609.912018		

Symbols for marking plates and marking caps for Indicator and Illuminated Pushbutton

All marking plates with the printed article-numbers are available for flat lenses, marking cap only on request.

	Part Nr. 704.609.910001 Direction of linear rectilinear motion (also for $\rightarrow \downarrow \uparrow$)		Part Nr. 704.609.910002 Linear motion in 2 directions (also for $\uparrow$)		Part Nr. 704.609.910003 Interrupted linear motion $\uparrow \downarrow$ (also for $\leftarrow \leftarrow \uparrow \downarrow$)		Part Nr. 704.609.910004 Limited linear motion (also for $\leftarrow \uparrow \downarrow$)
	Part Nr. 704.609.910005 Limited linear motion and return		Part Nr. 704.609.910006 Oscillating linear motion (continuous)		Part Nr. 704.609.910007 Direction of continuous rotation (right)		Part Nr. 704.609.9100071 Direction of continuous rotation (left)
	Part Nr. 704.609.910008 Rotation in 2 directions		Part Nr. 704.609.910009 Direction of interrupted rotation (right)		Part Nr. 704.609.9100091 Direction of interrupted rotation (left)		Part Nr. 704.609.910010 Limited rotation (right)
	Part Nr. 704.609.9100101 Limited rotation (left)		Part Nr. 704.609.910011 Limited rotation and return		Part Nr. 704.609.910012 Oscillating rotary movement (continuous)		Part Nr. 704.609.910013 Direction of spindle rotation
	Part Nr. 704.609.910014 One revolution		Part Nr. 704.609.910015 Number of revolutions per minute (spindle speed)		Part Nr. 704.609.910016 Feed		Part Nr. 704.609.910017 Feed per revolution
	Part Nr. 704.609.910018 Feed per minute		Part Nr. 704.609.910019 Reduced feed		Part Nr. 704.609.910020 Rapid feed		Part Nr. 704.609.910021 Normal feed
	Part Nr. 704.609.910022 Direction of feed (orientation not specified)		Part Nr. 704.609.910024 Transverse feed		Part Nr. 704.609.910025 Vertical feed		Part Nr. 704.609.910026 Rapid traverse
	Part Nr. 704.609.910027 Threading		Part Nr. 704.609.910028 Increase of value (speed, for instance)		Part Nr. 704.609.910029 Decrease of value (speed, for instance)		Part Nr. 704.609.910030 Speed of planing cut
	Part Nr. 704.609.910031 Speed of turning cut		Part Nr. 704.609.910032 Speed of drilling cut		Part Nr. 704.609.910033 Speed of milling cut (similar symbol for speed of grinding)		Part Nr. 704.609.910034 Conventional milling
	Part Nr. 704.609.910035 Climb milling (down milling)		Part Nr. 704.609.910041 Electric motor		Part Nr. 704.609.910042 Rectangular work table or slide element		Part Nr. 704.609.910043 Round work table or rotating element
	Part Nr. 704.609.910044 Turning spindle		Part Nr. 704.609.910045 Drilling spindle		Part Nr. 704.609.910046 Milling spindle		Part Nr. 704.609.910047 Schleifscheibenfutter
	Part Nr. 704.609.910048 Pump (general symbol)		Part Nr. 704.609.910049 Cooling pump		Part Nr. 704.609.910050 Lubricant pump		Part Nr. 704.609.910051 Hydraulic system pump
	Part Nr. 704.609.910052 Hydraulic motor		Part Nr. 704.609.910053 Tracer		Part Nr. 704.609.910061 Stepless regulation		Part Nr. 704.609.910062 Adjustable

 Part Nr. 704.609.9100631 Lock or tighten	 Part Nr. 704.609.9100632 Lock or tighten	 Part Nr. 704.609.9100641 Unlock, unclamp	 Part Nr. 704.609.9100642 Unlock, unclamp
 Part Nr. 704.609.910065 Brake on	 Part Nr. 704.609.910066 Brake off	 Part Nr. 704.609.910067 Automatic (or semi-automatic) cycle	 Part Nr. 704.609.910068 Hand control
 Part Nr. 704.609.910069 Start, on	 Part Nr. 704.609.910070 Stop, off	 Part Nr. 704.609.910071 Start and stop with same button	 Part Nr. 704.609.910072 In action as long as button is operated
 Part Nr. 704.609.910074 Engaging (mechanical start)	 Part Nr. 704.609.910075 Disengaging (mechanical stop)	 Part Nr. 704.609.910076 Close lock-nut	 Part Nr. 704.609.910077 Open lock-nut
 Part Nr. 704.609.910078 Engage sensor	 Part Nr. 704.609.910079 Disengage sensor	 Part Nr. 704.609.910080 Change speed only in stopped position	 Part Nr. 704.609.910081 Change speed only in motion
 Part Nr. 704.609.910091 Shear pin construction	 Part Nr. 704.609.910092 Danger (high voltage)!	 Part Nr. 704.609.910093 Caution!	 Part Nr. 704.609.910094 Main switch
 Part Nr. 704.609.910101 Coolant fluid	 Part Nr. 704.609.910102 Machine lighting	 Part Nr. 704.609.910103 Weight	 Part Nr. 704.609.910104 Filter opening
 Part Nr. 704.609.910105 Overflow	 Part Nr. 704.609.910106 Drain	 Part Nr. 704.609.910107 Oil, lubricant	 Part Nr. 704.609.910108 Blast
 Part Nr. 704.609.910109 Suction			

04 Marking

Terminal Markings

We supply the switch elements with terminal marking labels inserted, the figures always being visible for the first element (immediately following the actuator). Therefore, when two switch elements are used, these inserts have to be turned for the second element.


Then the numbers appear as described under III.

If more than two switch elements are used, this should be noted on your order, in order that we may insert and deliver the marking labels accordingly.


I. Consecutive numbering of switch systems

(2 per switch element)

First switch element




Second switch element




When more than 2 switch elements are used, the numbering is sequenced accordingly (5, 6 etc.).

III. Example of the correct insertion of the labels for 2 switch elements with normally open contacts

First switch element




Second switch element




Labels for normally closed and normally closed/normally open contacts should be inserted accordingly.

II. Marking of normally closed contact, normally open contact and their combinations


Normally closed (1–2)



Normally open (3–4)



Normally closed/open



Suppressor circuits


When switching inductive loads such as relays, DC motors, and DC solenoids, it is always important to absorb surges (e.g. with a diode) to protect the contacts. When these inductive loads are switched off, a counter emf can severely damage switch contacts and greatly shorten lifetime.

Fig. 1 shows an inductive load with a free-wheeling diode connected in parallel. This free-wheeling diode provides a path for the inductor current to flow when the current is interrupted by the switch. Without this free-wheeling diode, the voltage across the coil will be limited only by dielectric breakdown voltages of the circuit or parasitic elements of the coil. This voltage can be kilovolts in amplitude even when nominal circuit voltages are low (e.g. 12VDC) see Fig. 2.


The free-wheeling diode should be chosen so that the reverse breakdown voltage is greater than the voltage driving the inductive load. The DC blocking voltage (V_R) of the free-wheeling diode can be found in the datasheet of a diode. The forward current should be equal or greater than the maximum current flowing through the load.

To get an efficient protection, the free-wheeling diode must be connected as close as possible to the inductive load!

Switching with inductive load
Fig. 1



Counter EMF
over load without free-wheeling diode
Fig. 2



Index from Part No.

Part No.	Seite	Part No.	Seite	Part No.	Seite	Part No.	Seite	Part No.	Seite	Part No.	Seite
02-912.1	152	704.001.5	58	704.012.518	14	704.042.6	76	704.092.0l	110	704.120.0	90
02-912.2	152	704.001.5	66	704.012.6	75	704.042.618	14	704.093.0	112	704.120.018	24
02-912.3	152	704.001.6	58	704.012.618	14	704.042.7	76	704.093.010	45	704.121.0	90
02-912.4	152	704.001.6	66	704.012.7	75	704.042.718	14	704.093.010l	43	704.121.018	24
10-1406.1369	149	704.001.7	58	704.012.718	14	704.043.0	76	704.093.018	45	704.122.0	90
10-1409.1329	149	704.001.7	66	704.013.0	76	704.043.2	76	704.093.018l	43	704.122.018	24
10-1412.1279	149	704.002.2	62	704.013.2	76	704.043.4	76	704.093.0l	110	704.123.0	90
10-1416.1289	149	704.002.2	70	704.013.4	76	704.043.5	76	704.093.0x28	52	704.123.018	24
10-1419.1249	149	704.002.4	62	704.013.5	76	704.043.6	76	704.094.0	112	704.123.018KN	50
10-1420.1219	149	704.002.4	70	704.013.6	76	704.043.7	76	704.094.0l	110	704.123.118KN	50
10-1422.1179	149	704.002.5	62	704.013.7	76	704.059.2	80	704.095.0	112	704.124.0	92
10-1424.1179	149	704.002.5	70	704.020.2	55	704.059.4	80	704.095.010	45	704.124.018	26
10-2506.1082	147	704.002.6	62	704.020.4	55	704.059.5	80	704.095.010l	43	704.151.XXX	54
10-2506.1084	147	704.002.6	70	704.020.5	55	704.059.6	80	704.095.018	45	704.152.XXX	54
10-2506.1085	147	704.002.7	62	704.020.6	55	704.059.7	80	704.095.018l	43	704.153.XXX	54
10-2506.1086	148	704.002.7	70	704.020.7	55	704.060.2	80	704.095.0l	110	704.154.XXX	54
10-2506.1089	148	704.003.2	62	704.021.2	55	704.060.4	80	704.095.0x28	52	704.155.XXX	54
10-2509.1142	147	704.003.2	70	704.021.4	55	704.060.5	80	704.096.0	112	704.199.2	57
10-2509.1144	147	704.003.4	62	704.021.5	55	704.060.6	80	704.096.0l	110	704.199.2	65
10-2509.1145	147	704.003.4	70	704.021.6	55	704.060.7	80	704.097.0	112	704.199.4	57
10-2509.1146	148	704.003.5	62	704.021.7	55	704.062.2	80	704.097.010	45	704.199.4	65
10-2509.1149	148	704.003.5	70	704.022.2	55	704.062.218	18	704.097.010l	43	704.199.5	57
10-2512.1142	147	704.003.6	62	704.022.4	55	704.062.4	80	704.097.018	45	704.199.5	65
10-2512.1144	147	704.003.6	70	704.022.5	55	704.062.418	18	704.097.018l	43	704.199.6	57
10-2512.1145	147	704.003.7	62	704.022.6	55	704.062.5	80	704.097.0l	110	704.199.6	65
10-2512.1146	148	704.003.7	70	704.022.7	55	704.062.518	18	704.097.0x28	52	704.199.7	57
10-2512.1149	148	704.006.2	62	704.029.2	80	704.062.6	80	704.098.0	112	704.199.7	65
10-2513.1142	147	704.006.2	70	704.029.4	80	704.062.618	18	704.098.0l	110	704.200.2	57
10-2513.1144	147	704.006.218	5	704.029.5	80	704.062.7	80	704.099.0	112	704.200.2	65
10-2513.1145	147	704.006.218	9	704.029.6	80	704.062.718	18	704.099.010	45	704.200.4	57
10-2513.1146	148	704.006.4	62	704.029.7	80	704.063.2	81	704.099.010l	43	704.200.4	65
10-2513.1149	148	704.006.4	70	704.030.2	80	704.063.4	81	704.099.018	45	704.200.5	57
10-2519.1052	147	704.006.418	5	704.030.4	80	704.063.5	81	704.099.018l	43	704.200.5	65
10-2519.1054	147	704.006.418	9	704.030.5	80	704.063.6	81	704.099.0l	110	704.200.6	57
10-2519.1055	147	704.006.5	62	704.030.6	80	704.063.7	81	704.099.0x28	52	704.200.6	65
10-2519.1056	148	704.006.5	70	704.030.7	80	704.064.2	84	704.100.0	102	704.200.7	57
10-2519.1059	148	704.006.518	5	704.032.2	80	704.066.2	84	704.100.0.12	104	704.200.7	65
10-2524.3042	147	704.006.518	9	704.032.218	18	704.070.0	86	704.100.0l	100	704.202.2	61
10-2524.3044	147	704.006.6	62	704.032.4	80	704.070.2	86	704.101.0	102	704.202.2	69
10-2524.3045	147	704.006.6	70	704.032.418	18	704.070.4	86	704.101.0.12	104	704.202.208	4
10-2524.3046	148	704.006.618	5	704.032.5	80	704.070.5	86	704.101.010	35	704.202.208	8
10-2524.3049	148	704.006.618	9	704.032.518	18	704.071.0	86	704.101.010.12	37	704.202.4	61
10-2H12.314A	148	704.006.7	62	704.032.6	80	704.071.2	86	704.101.010l	33	704.202.4	69
10-2H12.314B	148	704.006.7	70	704.032.618	18	704.071.210	22	704.101.018	35	704.202.408	4
10-2H12.314C	148	704.006.718	5	704.032.7	80	704.071.218	22	704.101.018.12	37	704.202.408	8
10-2H24.2052	147	704.006.718	9	704.032.718	18	704.071.4	86	704.101.018l	33	704.202.5	61
10-2H24.2054	147	704.009.0	75	704.033.2	80	704.071.410	22	704.101.018KN	49	704.202.5	69
10-2H24.2055	147	704.009.2	75	704.033.4	80	704.071.418	22	704.101.018KNI	48	704.202.508	4
10-2H24.2056	148	704.009.4	75	704.033.5	80	704.071.5	86	704.101.0D.12	104	704.202.508	8
10-2H24.2059	148	704.009.5	75	704.033.6	80	704.072.0	86	704.101.0l	100	704.202.6	61
10-2H25.2042	147	704.009.6	75	704.033.7	80	704.072.2	86	704.101.0KN	116	704.202.6	69
10-2H25.2044	147	704.009.7	75	704.039.0	75	704.073.0	86	704.101.0x28	51	704.202.608	4
10-2H25.2045	147	704.010.0	75	704.039.2	75	704.073.2	86	704.101.110KN	49	704.202.608	8
10-2H25.2046	148	704.010.2	75	704.039.4	75	704.073.4	86	704.101.110KNI	48	704.202.7	61
10-2H25.2049	148	704.010.4	75	704.039.5	75	704.073.5	86	704.101.118KN	49	704.202.7	69
14-810.002	73	704.010.5	75	704.039.6	75	704.074.2	85	704.101.118KNI	48	704.202.708	4
14-810.902	73	704.010.6	75	704.039.7	75	704.074.210	21	704.101.1KN	116	704.202.708	8
14-810.910	12	704.010.7	75	704.040.0	75	704.074.3	85	704.101.1KNI	115	704.203.2	61
14-810.918	12	704.011.0	75	704.040.2	75	704.075.2	85	704.102.0	102	704.203.2	70
61-9481.6	155	704.011.018	14	704.040.4	75	704.075.218	21	704.102.0l	100	704.203.4	61
61-9481.6	159	704.011.2	75	704.040.5	75	704.075.2l	87	704.103.0	102	704.203.4	70
700.005.0	159	704.011.218	14	704.040.6	75	704.075.3	85	704.103.018	35	704.203.5	61
700.006.0	158	704.011.4	75	704.040.7	75	704.075.310	21	704.103.018l	33	704.203.5	70
704.000.2	58	704.011.418	14	704.041.0	75	704.075.318	21	704.103.0l	100	704.203.6	61
704.000.2	66	704.011.5	75	704.041.2	75	704.076.0	85	704.103.0x28	51	704.203.6	70
704.000.4	58	704.011.518	14	704.041.4	75	704.078.0	85	704.113.0	92	704.203.7	61
704.000.4	66	704.011.6	75	704.041.5	75	704.079.2	87	704.113.018	26	704.203.7	70
704.000.5	58	704.011.618	14	704.041.6	75	704.079.2F	22	704.114.0	92	704.206.2	61
704.000.5	66	704.011.8	75	704.041.8	75	704.084.2	88	704.114.018	26	704.206.2	69
704.000.6	58	704.011.818	14	704.042.0	76	704.084.4	88	704.115.0	92	704.206.200	4
704.000.6	66	704.012.0	75	704.042.018	14	704.084.5	88	704.115.018	26	704.206.200	8
704.000.7	58	704.012.018	14	704.042.2	76	704.084.6	88	704.116.0	92	704.206.4	61
704.000.7	66	704.012.2	75	704.042.218	14	704.084.7	88	704.116.018	26	704.206.4	69
704.001.2	58	704.012.218	14	704.042.4	76	704.086.2	88	704.117.0	92	704.206.400	4
704.001.2	66	704.012.4	75	704.042.418	14	704.086.4	88	704.117.018	26	704.206.400	8
704.001.4	58	704.012.418	14	704.042.5	76	704.086.5	88	704.118.0	92	704.206.5	61
704.001.4	66	704.012.5	75	704.042.518	14	704.092.0	112	704.118.018	26	704.206.5	69

Part No.	Seite	Part No.	Seite	Part No.	Seite	Part No.	Seite	Part No.	Seite	Part No.	Seite
704.206.500.....	4	704.240.008.....	14	704.334.0.....	91	704.411.110KN.....	47	704.601.8.....	120	704.732.1.....	82
704.206.500.....	8	704.240.2.....	74	704.334.000.....	25	704.411.118KN.....	47	704.601.81.....	121	704.733.0.....	63
704.206.6.....	61	704.240.208.....	14	704.334.008.....	25	704.411.118KNI.....	46	704.601.9.....	120	704.733.0.....	71
704.206.6.....	69	704.240.4.....	74	704.335.0.....	91	704.411.1KN.....	114	704.601.91.....	121	704.733.1.....	63
704.206.600.....	4	704.240.408.....	14	704.335.000.....	25	704.411.1KNI.....	113	704.602.0.....	119	704.733.1.....	71
704.206.600.....	8	704.240.5.....	74	704.335.008.....	25	704.412.0.....	96	704.602.2.....	119	704.741.0.....	15
704.206.7.....	61	704.240.508.....	14	704.336.000.....	25	704.412.0l.....	94	704.602.4.....	119	704.741.0.....	19
704.206.7.....	69	704.240.6.....	74	704.336.008.....	25	704.413.0.....	96	704.602.5.....	119	704.741.8.....	15
704.206.700.....	4	704.240.608.....	14	704.337.0.....	91	704.413.010.....	30	704.602.6.....	119	704.741.8.....	19
704.206.700.....	8	704.240.7.....	74	704.337.000.....	25	704.413.010l.....	28	704.602.7.....	119	704.742.0.....	15
704.207.2.....	61	704.240.708.....	14	704.337.008.....	25	704.413.018.....	30	704.602.7A01.....	119	704.742.0.....	19
704.207.2.....	70	704.259.2.....	80	704.338.000.....	25	704.413.018l.....	28	704.603.2.....	121	704.742.8.....	15
704.207.4.....	61	704.259.200.....	17	704.338.008.....	25	704.413.0l.....	94	704.603.4.....	121	704.742.8.....	19
704.207.4.....	70	704.259.4.....	80	704.340.0.....	89	704.502.0.....	107	704.603.5.....	121	704.743.0.....	6
704.207.5.....	61	704.259.400.....	17	704.340.000.....	23	704.502.000.....	40	704.603.6.....	121	704.743.0.....	10
704.207.5.....	70	704.259.5.....	80	704.340.008.....	23	704.502.000l.....	38	704.603.7.....	121	704.743.8.....	6
704.207.6.....	61	704.259.500.....	17	704.341.0.....	89	704.502.008.....	40	704.608.7.....	124	704.743.8.....	10
704.207.6.....	70	704.259.6.....	80	704.341.000.....	23	704.502.008l.....	38	704.608.9.....	124	704.8A230.....	144
704.207.7.....	61	704.259.600.....	17	704.341.008.....	23	704.502.0l.....	105	704.609.0.....	123	704.8A231.....	144
704.207.7.....	70	704.259.7.....	80	704.342.0.....	89	704.504.0.....	107	704.609.7.....	123	704.8A232.....	144
704.209.0.....	74	704.259.700.....	17	704.342.000.....	23	704.504.000.....	40	704.609.9.....	123	704.8A233.....	144
704.209.000.....	13	704.260.2.....	79	704.342.008.....	23	704.504.000l.....	38	704.609.9A01.....	123	704.8A234.....	143
704.209.2.....	74	704.260.208.....	18	704.343.0.....	89	704.504.008.....	40	704.610.7.....	123	704.8A235.....	143
704.209.200.....	13	704.260.4.....	79	704.343.000.....	23	704.504.008l.....	38	704.610.9.....	123	704.8A236.....	142
704.209.4.....	74	704.260.408.....	18	704.343.008.....	23	704.504.0l.....	105	704.611.2.....	120	704.8A237.....	142
704.209.400.....	13	704.260.5.....	79	704.344.0.....	91	704.506.0.....	107	704.611.4.....	120	704.8A238.....	142
704.209.5.....	74	704.260.508.....	18	704.344.000.....	25	704.506.000.....	40	704.611.5.....	120	704.8A239.....	142
704.209.500.....	13	704.260.6.....	79	704.344.008.....	25	704.506.000l.....	38	704.611.7.....	120	704.8A250.....	144
704.209.6.....	74	704.260.608.....	18	704.402.0.....	108	704.506.008.....	40	704.630.1.....	60	704.8A251.....	144
704.209.600.....	13	704.260.7.....	79	704.402.0l.....	106	704.506.008l.....	38	704.630.1.....	68	704.8A252.....	144
704.209.7.....	74	704.260.708.....	18	704.403.0.....	108	704.506.0l.....	105	704.631.1.....	16	704.8A253.....	144
704.209.700.....	13	704.292.0.....	111	704.403.010.....	41	704.508.0.....	107	704.631.1.....	20	704.8A254.....	143
704.210.0.....	74	704.292.000.....	44	704.403.010l.....	39	704.508.000.....	40	704.631.1.....	78	704.8A255.....	143
704.210.008.....	13	704.292.000l.....	42	704.403.018.....	41	704.508.000l.....	38	704.631.1.....	83	704.8A270.....	144
704.210.2.....	74	704.292.008.....	44	704.403.018l.....	39	704.508.008.....	40	704.632.1.....	16	704.8A271.....	144
704.210.208.....	13	704.292.008l.....	42	704.403.0l.....	106	704.508.008l.....	38	704.632.1.....	20	704.8A272.....	144
704.210.4.....	74	704.292.0l.....	109	704.404.0.....	108	704.508.0l.....	105	704.632.1.....	78	704.8A639.....	142
704.210.408.....	13	704.294.0.....	111	704.404.0l.....	106	704.510.0.....	95	704.632.1.....	83	704.8A730.....	144
704.210.5.....	74	704.294.000.....	44	704.405.0.....	108	704.510.0.12.....	97	704.633.1.....	7	704.8A731.....	144
704.210.508.....	13	704.294.000l.....	42	704.405.010.....	41	704.510.000.....	29	704.633.1.....	11	704.900.1.....	137
704.210.6.....	74	704.294.008.....	44	704.405.010l.....	39	704.510.000.12.....	31	704.633.1.....	64	704.900.1B.....	138
704.210.608.....	13	704.294.008l.....	42	704.405.018.....	41	704.510.000l.....	27	704.633.1.....	72	704.900.2.....	137
704.210.7.....	74	704.294.0l.....	109	704.405.018l.....	39	704.510.008.....	29	704.642.0.....	56	704.900.2B.....	138
704.210.708.....	13	704.296.0.....	111	704.405.0l.....	106	704.510.008.12.....	31	704.642.1.....	56	704.900.3.....	137
704.229.2.....	79	704.296.000.....	44	704.406.0.....	108	704.510.008l.....	27	704.642.2.....	56	704.900.3B.....	138
704.229.200.....	17	704.296.000l.....	42	704.406.0l.....	106	704.510.0l.....	93	704.701.0.....	125	704.900.4.....	137
704.229.4.....	79	704.296.008.....	44	704.407.0.....	108	704.510.100KN.....	47	704.701.4.....	125	704.900.4B.....	138
704.229.400.....	17	704.296.008l.....	42	704.407.010.....	41	704.510.108KN.....	47	704.701.6.....	125	704.900.5.....	137
704.229.5.....	79	704.296.0l.....	109	704.407.010l.....	39	704.510.1KN.....	114	704.702.0.....	119	704.900.5B.....	138
704.229.500.....	17	704.298.0.....	111	704.407.018.....	41	704.510.1KNI.....	113	704.702.2.....	119	704.901.1.....	137
704.229.6.....	79	704.298.000.....	44	704.407.018l.....	39	704.512.0.....	95	704.702.4.....	119	704.901.1/D.....	136
704.229.600.....	17	704.298.000l.....	42	704.407.0l.....	106	704.512.000.....	29	704.702.5.....	119	704.901.2.....	137
704.229.7.....	79	704.298.008.....	44	704.408.0.....	108	704.512.000l.....	27	704.702.6.....	119	704.901.2/D.....	136
704.229.700.....	17	704.298.008l.....	42	704.408.0l.....	106	704.512.008l.....	27	704.702.7.....	119	704.901.3.....	137
704.230.2.....	79	704.298.0l.....	109	704.409.0.....	108	704.512.018l.....	29	704.702.9.....	119	704.901.3/D.....	136
704.230.208.....	17	704.300.0.....	101	704.409.010.....	41	704.512.0l.....	93	704.703.2.....	122	704.901.4.....	137
704.230.4.....	79	704.300.0.12.....	103	704.409.010l.....	39	704.600.0.....	126	704.703.4.....	122	704.901.4/D.....	136
704.230.408.....	17	704.300.000.....	34	704.409.018.....	41	704.600.1.....	126	704.703.5.....	122	704.901.5.....	137
704.230.5.....	79	704.300.000.12.....	36	704.409.018l.....	39	704.600.1A.....	126	704.703.6.....	122	704.901.5/D.....	136
704.230.508.....	17	704.300.000l.....	32	704.409.0l.....	106	704.600.2.....	127	704.703.7.....	122	704.902.1.....	137
704.230.6.....	79	704.300.008.....	34	704.410.0.....	96	704.600.3.....	127	704.706.7.....	122	704.902.2.....	137
704.230.608.....	17	704.300.008.12.....	36	704.410.0.12.....	98	704.600.5/A.....	127	704.707.7.....	122	704.902.3.....	137
704.230.7.....	79	704.300.008l.....	32	704.410.0l.....	94	704.600.6.....	126	704.708.7.....	124	704.902.4.....	137
704.230.708.....	17	704.300.0l.....	99	704.411.0.....	96	704.600.7.....	126	704.708.9.....	124	704.902.5.....	137
704.239.0.....	75	704.300.100KN.....	49	704.411.0.12.....	98	704.600.9.....	126	704.709.7.....	121	704.905.1.....	136
704.239.000.....	13	704.300.108KN.....	49	704.411.010.....	30	704.601.0.....	120	704.709.9.....	121	704.905.1/D.....	136
704.239.2.....	75	704.300.1KN.....	116	704.411.010.12.....	31	704.601.01.....	121	704.730.0.....	59	704.905.2.....	136
704.239.200.....	13	704.300.1KNI.....	115	704.411.010l.....	28	704.601.10.....	120	704.730.0.....	67	704.905.2/D.....	136
704.239.4.....	75	704.302.0.....	101	704.411.010KN.....	47	704.601.101.....	121	704.730.1.....	59	704.905.3.....	136
704.239.400.....	13	704.302.000.....	34	704.411.010KNI.....	46	704.601.12.....	120	704.730.1.....	67	704.905.3/D.....	136
704.239.5.....	75	704.302.000l.....	32	704.411.018.....	30	704.601.21.....	121	704.731.0.....	77	704.905.4.....	136
704.239.500.....	13	704.302.008.....	34	704.411.018.12.....	31	704.601.4.....	120	704.731.0.....	82	704.905.4/D.....	136
704.239.6.....	75	704.302.008l.....	32	704.411.018l.....	28	704.601.41.....	121	704.731.1.....	77	704.905.5.....	136
704.239.600.....	13	704.302.0l.....	99	704.411.018KN.....	47	704.601.5.....	120	704.731.1.....	82	704.905.5/D.....	136
704.239.7.....	75	704.333.0.....	91	704.411.018KNI.....	46	704.601.51.....	121	704.732.0.....	77	704.907.1.....	135
704.239.700.....	13	704.333.000.....	25	704.411.0B.12.....	98	704.601.6.....	120	704.732.0.....	82	704.907.2.....	135
704.240.0.....	74	704.333.008.....	25	704.411.0l.....	94	704.601.61.....	121	704.732.1.....	77	704.907.3.....	135

Part No.	Seite	Part No.	Seite	Part No.	Seite
704.907.4.....	135	704.917.2.....	139	704.955.0.....	124
704.907.5.....	135	704.917.3.....	135	704.955.1.....	124
704.908.1.....	135	704.917.3.....	139	704.955.10.....	124
704.908.2.....	135	704.917.4.....	135	704.955.3.....	125
704.908.3.....	135	704.917.4.....	139	704.955.4.....	125
704.908.4.....	135	704.917.4FS	142	704.955.9.....	124
704.908.5.....	135	704.917.5.....	135	704.955.9E	125
704.910.1.....	137	704.917.5.....	139	704.960.0.....	156
704.910.1.....	140	704.918.1.....	135	704.960.4.....	130
704.910.1B	138	704.918.1.....	139	704.960.5.....	132
704.910.2.....	137	704.918.2.....	135	704.960.8.....	156
704.910.2.....	140	704.918.2.....	139	704.960.8A	156
704.910.2B	138	704.918.3.....	135	704.960.9.....	158
704.910.3.....	137	704.918.3.....	139	704.963.0.....	153
704.910.3.....	140	704.918.4.....	135	704.963.1.....	153
704.910.3B	138	704.918.4.....	139	704.963.2.....	153
704.910.4.....	137	704.918.4FS	142	704.963.3.....	153
704.910.4.....	140	704.918.5.....	135	704.963.5.....	153
704.910.4B	138	704.918.5.....	139	704.963.6.....	153
704.910.4BFS	141	704.925.0.....	129	704.963.7.....	153
704.910.4FS	141	704.925.2.....	129	704.963.8.....	153
704.910.5.....	137	704.925.3.....	129	704.964.5.....	145
704.910.5.....	140	704.925.7.....	128	704.964.7.....	130
704.910.5B	138	704.925.8.....	127	704.964.8.....	130
704.911.1.....	137	704.925.9.....	127	704.964.9.....	130
704.911.1.....	140	704.927.6.....	154	704.965.1.....	146
704.911.1B	138	704.927.6A	154	704.965.2.....	146
704.911.2.....	137	704.927.6B	154	704.965.3.....	146
704.911.2.....	140	704.927.6C	154	704.965.4.....	146
704.911.2B	138	704.927.6D	154	704.965.5.....	146
704.911.3.....	137	704.927.8.....	153	704.965.6.....	146
704.911.3.....	140	704.927.9.....	153	704.965.7.....	146
704.911.3B	138	704.928.18.....	128	704.965.8.....	146
704.911.4.....	137	704.928.28.....	128	704.965.9.....	146
704.911.4.....	140	704.928.38.....	128	704.966.0.....	146
704.911.4B	138	704.940.8.....	157	704.966.1.....	146
704.911.4BFS	141	704.940.9.....	157	704.966.2.....	146
704.911.4DFS	141	704.941.0.....	151	704.968.0.....	117
704.911.4FS	141	704.941.0P	151	704.968.1.....	117
704.911.5.....	137	704.941.1.....	157	704.968.10.....	118
704.911.5.....	140	704.941.5.....	151	704.968.11.....	118
704.911.5B	138	704.941.5P	151	704.968.12.....	118
704.912.1.....	137	704.941.9.....	152	704.968.13.....	118
704.912.1.....	140	704.941.9P	152	704.968.2.....	117
704.912.2.....	137	704.942.5.....	149	704.968.3.....	117
704.912.2.....	140	704.942.5P	149	704.968.4.....	118
704.912.3.....	137	704.943.0.....	131	704.968.5.....	118
704.912.3.....	140	704.943.0P	131	704.970.3.....	150
704.912.4.....	137	704.943.1.....	131	704.970.4.....	150
704.912.4.....	140	704.943.1P	131	704.970.5.....	150
704.912.5.....	137	704.943.2.....	131	704.970.6.....	150
704.912.5.....	140	704.943.2P	131	704.989.251.....	129
704.915.1.....	136	704.943.5.....	131	704.990.0.....	159
704.915.1.....	139	704.943.5P	131	704.990.1.....	146
704.915.1/D.....	136	704.945.0.....	155	98-968	158
704.915.1/D.....	140	704.945.1.....	160		
704.915.2.....	136	704.945.2.....	160		
704.915.2.....	139	704.945.3.....	160		
704.915.2/D.....	136	704.945.4.....	160		
704.915.2/D.....	140	704.945.5.....	160		
704.915.3.....	136	704.945.6.....	155		
704.915.3.....	139	704.945.6.....	159		
704.915.3/D.....	136	704.945.7.....	155		
704.915.3/D.....	140	704.945.8.....	155		
704.915.4.....	136	704.950.0.....	133		
704.915.4.....	139	704.950.0B	133		
704.915.4/D.....	136	704.950.1.....	133		
704.915.4/D.....	140	704.950.1/D	133		
704.915.4DFS	141	704.950.2/D	133		
704.915.4FS	141	704.950.3.....	133		
704.915.5.....	136	704.950.5.....	132		
704.915.5.....	139	704.951.0.....	134		
704.915.5/D.....	136	704.951.1.....	134		
704.915.5/D.....	140	704.951.1/D	134		
704.917.1.....	135	704.951.3.....	134		
704.917.1.....	139	704.953.0.....	126		
704.917.2.....	135	704.954.0.....	156		